•



May 21, 2021

♥ Fungal isolate identification using ITS-LSU regions

Cassie Ettinger¹

¹University of California, Riverside





dx.doi.org/10.17504/protocols.io.butvnwn6

EisenLab Early Career Ocean Scientists 2 more workspaces



ABSTRACT

This protocol was written as a companion to the 'Swabs to Genomes' workflow to enable undergraduate interns to take Sanger sequences for the ITS-LSU region from unidentified fungal isolates associated with seagrasses and identify preliminary taxonomy via databases searches and then build phylogenies to further assess putative identities.

ATTACHMENTS

Fungal ITS-LSU
Identification.docx

DOI

dx.doi.org/10.17504/protocols.io.butvnwn6

PROTOCOL CITATION

Cassie Ettinger 2021. Fungal isolate identification using ITS-LSU regions. **protocols.io** https://dx.doi.org/10.17504/protocols.io.butvnwn6

KEYWORDS

Fungal isolate identification, ITS-LSU regions, Sanger sequences

LICENSE

This is an open access protocol distributed under the terms of the Creative Commons Attribution License, which permits unrestricted use, distribution, and reproduction in any medium, provided the original author and source are credited

CREATED

May 07, 2021

LAST MODIFIED

May 21, 2021

OWNERSHIP HISTORY

May 07, 2021 Urmilas

University of California, Riverside

PROTOCOL INTEGER ID

49749

Process Sanger sequences following the 'Swabs to Genome' workflow using Seqtrace

1

 $\textbf{Citation:} \ \ \textbf{Cassie} \ \ \textbf{Ettinger} \ \ \textbf{(05/21/2021)}. \ \ \textbf{Fungal isolate} \ \ \textbf{identification using ITS-LSU regions.} \ \ \underline{\textbf{https://dx.doi.org/10.17504/protocols.io.butvnwn6}} \ \ \textbf{(05/21/2021)}. \ \ \textbf$

Follow directions here on how to install and use Seqtrace: https://peerj.com/articles/960/#sanger- sequence-processing. If on undergraduate computer in the Eisen lab, you can type in 'seqtrace' into 'terminal' to start. Otherwise you may need to type 'python seqtrace.py' Create a new project (File > New Project). 2.1 Choose the directory your Sanger sequences are in. 2.2 If your files have the primer names in them, you can enter their names under 'search strings...". Add your forward and reverse primer names (sequences not necessary). 2.3 1. Possible forward primers: ITS5, ITS1F. 2. Possible reverse primers: LR3, ITS4. 2.4 Now click on the 'Sequencing Processing' tab. 1. Under "Sequence trimming", unclick the 'Automatically trim sequence ends' button. 2. Under "Consensus" decrease the min. confidence score to 15. To add files, go to "Traces" and click on "Add trace files", then select the reads (.abi files) you want to work with. Group your forward and reverse reads by highlighting both of them and clicking "Group selected forward/reverse files" (under "Traces").

2

3

5

Under "Sequences" go to "Generate Finished Sequences" and click on "for all trace files".

page. The "Trace View" shows the quality scores, the chromatogram (trace) display, and the raw base calls from both the forward and reverse reads, as well as the consensus sequence. The consensus sequence is the middle list of nucleotides. To export the consensus from the trace view, go to "Sequence", hover on "Export Sequences", and select "Export Sequences from Selected Trace Files". This will create a file containing the consensus sequence. Identify fungal sequences using existing databases Go to NCBI's BLAST (https://blast.ncbi.nlm.nih.gov/Blast.cgi). 8.1 Click nucleotide blast. 8.2 Upload the fasta file containing your consensus sequences or copy / paste them in the box. 8.3 For each sequence write down the top hit & its % identity (this is how much the top hit matches your sequence). Note that the top match is database dependent, and for our purposes here is just a hypothesis. We will check our sequences against several databases and build a tree to determine how confident we are in this hypothesis. Go to Ribosomal Database Project (RDP) website (https://rdp.cme.msu.edu/). 9.1 Make your way to the "Classifier" (https://rdp.cme.msu.edu/classifier/classifier.jsp). 9.2 Upload/paste your sequences. For "choose a gene", we are selecting what database to use for ITS1-ITS4 this is UNITE; for ITS5-

To view your consensus sequence, click on the read pair group and then click on the magnifying glass at the top of the

LR3 you will want to do this process three times, once using UNITE and once using "Fungal LSU

training set", and one using "WARCUP".

- 9.3 Click on "Show assignment detail for Root".
 - 1. Write down the assignment for each sequence and the %.

Stop here and decide on next steps! There are now two options to build fungal phylogenies, the first is to try to build a tree using SILVA (described below), but this is not very effective for fungi that SILVA does not have lots of data for (e.g. works well for Penicillium, but not for more novel or less studied taxa). The second way is to build a phylogeny manually - which involves (1) downloading fungal sequences to include in the tree from BLAST and the literature (2) generating an alignment (3) trimming the alignment and checking it manually (4) picking an evolutionary model for tree building and (5) building a phylogeny. Steps (2), (4), and (5) can be performed on CIPRES (https://www.phylo.org/portal2/home.action).

Build a tree for the LSU region (if available)

10

Go to SILVA ACT (https://www.arb-silva.de/aligner/).

11 🖵

You will need at **least 4 sequences** to build a tree - so wait until you have 4 sequences or add in sequences you already have to get to 4.

11.1

We want to add in a bacteria as an outgroup so you actually only need **3 fungal sequences** to build your tree. We can download an outgroup from https://www.arb-silva.de/browser/.

Pick a **named** bacteria, click its name to add it to your cart and then click "Download" to get the sequence as a fasta file.

- 11.2 Paste at the end of your fasta file or add to box if copy/pasting.
- 11.3 Alternatively use the bacterial sequence below:

>OUTGROUP Bacteria; Chloroflexi; Chloroflexia; Chloroflexales; Chloroflexaceae; Roseiflexus; Roseiflexus castenholzii DSM 13941

GGCGAGGGGAGUGAAAGAGAACCUGAAACCGUGUGCUUCCAUGCAGUCGGAGCCCCCGUGAGGGGGU GACGGCGUGCCUUUUGGAGUAUGAUCCGGCGAGUUACCCUCGGUGGCCAGGUUAAGGCAGUGACAGC CGGAGCCGGAGCGAAAGCGAGUCUGAAGAGGGCGCGCGGUCGCCGGGGGUAGACCCGAAACCGCUUG AGCUACCCAUGGGCAGGGUGAAGCGCGCGUAACAGCGCGUGGAGGCCCGCACCGGUGUGGAUUGCAA ACCGCUCGGAUGACCUGUGGGUAGGGGUGAAAUGCCAAACGAAAGCGGAGAUAGCUGGUUCUCCCCGA AAUGCAUUGAGGUGCAGCCUGCGGAAUGCCGCGCGCGGAGGUAGAGCGCUGGUGUGGUGCGGGGGCU UCACCGCCUACCAAACGACGCCAAACUGCGAAUGCCGCGGGGGAAGCGCAGAGUGAGACGUGCGGCG CAAACGUUGUACGUCGAGAGGGAAACAACCCAGACCUGCAGCUAAGGUCCCGAAAUCGACCCUGAGUG GGAAAGGAUGUGUCGUUGCGGAGACAACCAGGAGGUUGGCUUAGAAGCAGCCACCCUUGAAAGAGUG CGUAACAGCUCACUGGUCGAGUGACGAUGCGCCGACAAUCCAGCGGGGCAAAGGGUCGUACCGAAGCU CAGGACCGGAAGGGUGGUAGGGGAGCGUCGUGGACGCGGCGAAGCGGCGGAAGCCGGUCGUGG AGCGUCGACGAGUGCGAAUGCCGGAACGAGUAACAGCGAAGCGGGGUGCGAACCCCCGCCACCGGAA GGGGUAGGCGCUGCGGUCAGACGAGGACCGUCCAAGCUGGUAGGGAGACGGCGGAGGGAAGUCCGCG GAGGAAGCUAAGGUGGACGAGUGAUCCCUGGUUAAGGAACUCGGCAAAUUGACCCCGUACCUUCGGAA GAAGGGGUGCUCGGUCGACUCCGGCGGCGGAGGGAGCCGAUGCGAGUCGCAGCAAAGCGGCCCA GGCGACUGGAUACCAGAACCACAGGUCCGUGCUGAAGCCGAAAGGCGACGUAUACGGGCUGAUGCCUG CCCAGUGCCGGAAGGUUAAGGGGAGGGCUGUAAGGUCUGAACCGAAGCCCCGGUGAACGGCGGCUGU AACUAUAACAGUCCUAAGGUAGCGAAAUUCCUUGUCGGGUAAGUUCCGACCCGCACGAAAGGCAUCAC GAUCUGGGCAGUGUCUCGACCAGGGGCUCGGUGAAACUGCGCUGGCCGUUAGGACGCGGCCAACCCG UAGCAGGACAAAAAGACCCCGUGGAGCUUUACUACAGCUUGCCAUUGUGCGCGCUCCGGGCUUGCGUA GGAUAGGUGGGAGCCGGAGAACGGACCCUUGCGGGGGUGCGGGAGGCGACGGUGAAAUACCACUCUG GCCUCCUAAAAGGUAACGGAGGCGCGCAACGGCGCCCUCAGGCGGGAUGGCAAUCCGCCGGUGAGUG CAAAGGCAGAAGGGCGCUUGACUGCAAGGCAGACAGGCCGCGCAGAGAUGAAAGUCGGCCUUAGUGA UCCUACGGUUCCGCGUGGAAGGGCCGUAGCAUAACGGAUAAAAGCUACCCCGGGGAUAACAGGCUGAU CGUGCCCAAGAGUUCACAUCGACGGCACGGUUUGGCACCUCGAUGUCGGCUCGUCGCAUCCUGGGGGCU GGAGUCGGUCCCAAGGGUUGGGCUGUUCGCCCAUUAAAGCGGCACGCGAGCUGGGUUCAGAACGUCG UGAGACAGUUCGGUCUCUAUCCGCUACGGGCGGUUAGUGGCGUGCGGGGAGCUGCUCUUAGUACGAG CGGCGGCAAGAACCGCUGAAAGCAUCUAAGUGGGAAAUGCCCCCCAAGAUGACGCCACUCACGACGGA AGGUCGGUAAGUCCCCAGAAGACGACUGGGAAGGCCGCCAGCUGGAGGCCCCGUGAGGGGUAGA GGCGAGGCGUGCGCAUGGACGAGGGCUU.

12



12.1 Choose "LSU".

12.2 Click "removed".

13 __

Click next to "Search and Classify".

13.1 Change "Min. Identity with query" to 0.7.

14	
	Click next to "Compute tree".
	Olick Hext to Compute tree .
15	닏
	Under "Output settings".
	15.1 Change "reject sequences below" to 50.
16	
	Under "advanced tree building parameters".
	16.1 Click "include neighbors from".
17	
17	
	Give the job a name and click run, the job will now show up under "Alignment Taskmanager".
18	
	When the job is finished, click on it and click "show results".
	18.1 An "Alignment Results Table" will now appear.
	10.0 Click on "Evacut to COV" to count this information
	18.2 Click on "Export to CSV" to save this information.
19	
	Go back to the "Alignment Taskmanager" and click on your job.
	19.1 Now click on "Download file" and then "zip" to download your tree.
viewir	ng tree using Dendroscope

	16s-rdna-tre	additional details and how to download Dendroscope: https://peerj.com/articles/960/#building-a-pee <a #building-a-pee<="" 960="" a="" articles="" href="https://peerj.com/articles/960/#building-a-pee <a #building-a-pee<="" 960="" a="" articles="" href="https://peerj.com/articles/960/#building-a-pee <a #building-a-pee<="" 960="" a="" articles="" href="https://peerj.com/articles/960/#building-a-pee <a #building-a-pee<="" 960="" a="" articles="" href="https://peerj.com/articles/960/#building-a-pee <a #building-a-pee<="" 960="" a="" articles="" href="https://peerj.com/articles/960/#building-a-pee <a #building-a-pee<="" 960="" a="" articles="" href="https://peerj.com/articles/960/#building-a-pee <a #building-a-pee<="" 960="" a="" articles="" href="https://peerj.com/articles/960/#building-a-pee <a #building-a-pee<="" 960="" a="" articles="" href="https://peerj.com/articles/960/#building-a-pee <a #building-a-pee<="" 960="" a="" articles="" href="https://peerj.com/articles/960/#building-a-pee <a href="https://peerj.com/articles/960/#building-</th></tr><tr><th></th><th></th><th>in Dendroscope.</th></tr><tr><th>21</th><th></th><th></th></tr><tr><td>۷1</td><td></td><td></td></tr><tr><th></th><th>Re-root the tre</th><th>e to the outgroup.</th></tr><tr><th>22</th><th></th><th></th></tr><tr><th></th><th>Expand the tre</th><th>ee by clicking the expansion button, then scroll through the tree to locate the outgroup.</th></tr><tr><th>23</th><th></th><th></th></tr><tr><th></th><th>Click on the bo</th><th>eginning of the taxon name, to select it, and reroot the tree by going to edit and selecting " re-root".<="" th="">
	Click off the be	eginning of the taxon name, to select it, and refoot the free by going to edit and selecting free foot.
24		
	Change the vie	ew to "phylogram" to make it easier to look at.
		The phylogram to make k easier to look at.
25		
	Write down wh	no is the closest sister taxa/group and check to see who that taxa/group is. Now assess your phylogeny.
	Where do yo	our sequences fall on the tree? Does this make sense with your BLAST/RDP assignments?
Build p	ohylogeny ma	nually
26		
	Download fun	gal sequences to include in the tree from BLAST and the literature.
	26.1	Based on the fungal taxonomy of your sequences, decide which of your fungi to group into a single tree.
		e.g. all the fungi that blast to Penicillium or all fungi in the same "Genus" or "Family" based on RDP.
	26.2	Next write down the accession numbers for fungal sequences from BLAST that are close matches.

© protocols.io 7 05/21/2021

e.g. the top hits on BLAST - maybe take the top 3 hits for each taxa. As you make your list for all the top hits to your taxa, you may have duplicates if many of your fungal taxa are similar, but we don't want duplicate sequences in our tree so you can remove the duplicate accession numbers from your list now.




26.3

Identify an outgroup and also some close relatives from other closely related genera (**this is the** 'hardest' part).

You can do this through literature searches (e.g. Google Scholar, "Fusarium phylogeny") and writing down accession numbers used to build trees previously. Or you can use BLAST/GenBank Taxonomy Viewer to pick some fungal taxa. For example:

- 1. Click on the Accession number of a top hit for one of your sequences.
- 2. Click on the "Organism".




3. This will take you the GenBank Taxonomy Browser where you can browse for fungal data by taxonomy.



4. Check "nucleotide".

These are all fungi where there is available DNA data in the database (the number next to the taxa is the number of DNA sequences available).




5. You can also click on other levels in the "Lineage". e.g. "Family" (Debaryomyces, etc) to obtain close relatives outside of the group of interest.


When building a tree you want to have:

- i. 2-3 very close relatives (obtained previously based on 'top hits').
- ii. And then 2-3 sequences from the same Genus (e.g. Candida) that are not the closest hits (so not from the same species (so in our example, not $\it Candida\ saitoana$)).
 - iii. 2-3 sequences that are outside the Genus (so from other Genera in the Debaryomyces).
 - iv. 1-2 sequences that are even more distant (so from another Order of fungi, etc).

- 6. If you now want to obtain the Accession numbers of these fungal taxa to use in your tree, (in this example we are going for a sequence in the same Genus (Candida), but that is not *Candida saitona*).
 - a. Click on the name of the Genus you are interested in.




b. Then on the right, click on the number by "Nucleotide", this will take us to a list of all the DNA sequences for this organism.



c. At this point, you may see a sequence already that says "large subunit ribosomal RNA gene", this what we want, if not, you can search for this - just paste "large subunit ribosomal RNA gene" after what is already included in the search bar.



You should now have a list of Accession numbers that looks like this - with a new Accession number on each line - save this as a text file (e.g. .txt). We now want to obtain the sequences for all of these.




⋈ protocols.io 11 05/21/2021

Go to https://www.ncbi.nlm.nih.gov/sites/batchentrez.

- 1. "Database" should be "Nucleotide".
- 2. Select your file of Accession numbers.
- 3. Click "Retrieve".
- 4. It will then take you to a screen where it tells you if it had any issues with your Accession numbers (e.g. duplicates, etc), and here you want to click on "Retrieve records".



5. This will take you back to NCBI which will now list all the sequences you want, you now want to find "Send to" on the right of the screen and pick "File", Format of "Fasta".



6. Yay, you've just downloaded all the sequences! Now you just need to combine these sequences into one file with your sequences (so copy + paste into one file). You should now have one "fasta" file that contains all your fungal sequences and all of the close relatives and outgroup




Generating an alignment.

- 27.1
- We now need to align these sequences so that we know how each of the nucleotides in each sequence lines up.


Go to CIPRES (https://www.phylo.org/portal2/home.action) and create an account.

- 27.2 Log in to CIPRES. (https://www.phylo.org/portal2/home.action) and create an account.
- 27.3 Make a new project folder (e.g. Test).

This folder has both "Data" and a "Tasks" folders inside.



- 27.4 Click on "Data".
- 27.5 Upload your fasta file with all your fungal sequences.
- 27.6 Now click on "Tasks".
- 27.7 You want to create a new "Task".




mprotocols.io

05/21/2021

- 27.8 Enter something that makes sense in the "Description" to name the task, eg. Fungal alignment with MAFFT.
- 27.9 Next click "Select Input Data" and pick your uploaded fasta file.
- 27.10 Next "Select tool" and pick MAFFT (alignment software).



You should now have something that looks like this:



- 27.11 Click "Save and Run Task".
- 27.12 You will get an email when it is finished running and then you can go back to CIPRES, to "Tasks" and now click on "View Output".



27.13 You want to click "Download" next to the "output.mafft" file.

⋈ protocols.io 14 05/21/2021




You now have your aligned sequences!

28




Trim the alignment (remove parts that don't overlap).

- 28.1 Go to http://phylemon2.bioinfo.cipf.es/.
- 28.2 Sign in / make an account or work as an "anonymous user".
- 28.3 Go to "Utilities".
- 28.4 Click on "Alignment Utilities".
- 28.5 Click on "TrimAl".
 - i. Upload your aligned sequence file from CIPRES.




⋈ protocols.io 15 05/21/2021

ii. Now edit the parameters for TrimAl, click on the checkmark by "delete spurious" and add the values 0.75 and 50 respectively (or for advanced users, your values of choice) and then also select "gappyout".



iii. Now run the job!.



If its running, it should show up in the job list!

iv. When its finished running you want to download the new fasta file, just click on "outfile.out" to download.



29

Now we want to look at our alignment! (optional, but recommended).

29.1 Download JalView (http://www.jalview.org/).

29	2	Open JalView and dra	ig your trimmed alignm	ent file into JalView	and it should open it up.

For beginners - you just want to make sure that it looks like things "line up" and that nothing looks too "weird"

30

Next, we can either make a slower, potentially more accurate phylogeny or a faster, potentially less accurate phylogeny. To make a slow phylogeny skip to steps 32 and 33. To make a fast phylogeny go to step 31.

31

 $\label{prop:build} \mbox{Build a phylogeny using FastTree2}.$


- 31.1 Go back to CIPRES.
- 31.2 Click on "Data".
- 31.3 Upload your fasta file (outfile.out) with your aligned trimmed sequences.
- 31.4 Now click on "Tasks".
- 31.5 Create a new "Task".
- 31.6 Enter something in the description (e.g. fasttree of Candida).
- 31.7 Next "Select input data" and select your uploaded file.
- 31.8 Next "select tool" and pick FastTreeMP on XSEDE.
- 31.9 Click on "Parameters".

⋈ protocols.io 17 05/21/2021

31.10	Change "Maximum Hours to Run (up to 168 hours)" to 2.				
31.11	Save parameters and submit task.				
31.12	When finished "View output".				
31.13	Download the file that ends in ".tre".				
	Yay we have a tree!. You can stop here unless you want to make a more accurate tree in steps 31 and 32 below.				
Pick an evolutionary model!.					
32.1	Back to CIPRES!.				
32.2	Click on "Data".				
32.3	Upload your fasta file (outfile.out) with all your trimmed and aligned sequences.				
32.4	Now click on "Tasks".				
32.5	You want to create a new "Task".				
32.6	Enter something that makes sense in the "Description" to name the task, eg. Fungal model test.				

ு protocols.io 18 05/21/2021 € 05/21/2021

32.7 Next click "Select Input Data" and pick your uploaded file.



- 32.10 Save parameters and submit task.
- 32.11 When finished "View output".
- 32.12 Next click on "View" next to STDOUT.



32.13 Scroll to the bottom and find this information:



This tells us which evolutionary model works best, hopefully they all match! Very likely it will say GTR + I + G or GTR.

33

Build a phylogeny !! Finally!!

33.1 Also on CIPRES!.

- 33.2 Now click on "Tasks".

 33.3 You want to create a new "Task".


 33.4 Enter something that makes sense in the "Description" to name the task, eg. Fungal phylogeny.

 33.5 Next click "Select Input Data" and pick the same file you just used for the model test above (the trimmed and aligned file).

 33.6 Next "Select tool" and pick MrBayes. Note for advanced users: CIPRES also supports RAXML

 MrBayes on XSEDE (3.2.7a) Tree Inference Using Bayesian Analysis run on XSEDE

 33.7 Click on "Parameters".
- 33.8 Pick "MrBayes 3.2.6".



- 33.9 Save parameters and submit task.
- 33.10 You will get an email when it is finished running and then you can go back to CIPRES, to "Tasks" and now click on "View Output".