

Jun 18, 2025

Maps

DOI

dx.doi.org/10.17504/protocols.io.3byl4k4zzvo5/v1

Dakota Betz¹

¹ucsd

Rouse Lab



Dakota Betz

ucsd

OPEN  ACCESS



DOI: dx.doi.org/10.17504/protocols.io.3byl4k4zzvo5/v1

Protocol Citation: Dakota Betz 2025. Maps. **protocols.io** <https://dx.doi.org/10.17504/protocols.io.3byl4k4zzvo5/v1>

License: This is an open access protocol distributed under the terms of the **Creative Commons Attribution License**, which permits unrestricted use, distribution, and reproduction in any medium, provided the original author and source are credited

Protocol status: Working

We use this protocol and it's working

Created: August 23, 2021

Last Modified: June 18, 2025

Protocol Integer ID: 52641

Abstract

Basic MarMap instructions for plotting maps in R studio.



Programs and Dependencies

- 1
- 2 Once you have R and R Studio installed, install marmap
- 3 Marmap depends on some other packages, and you may encounter errors if they're not up to date.
- 4

Getting Started-Quick Maps

- 5 Before making any maps, be sure that you have the marmap package loaded. Run the following code:

Command

```
library(marmap)
```

- 6 To start with, you'll want to make some quick/rough maps to make sure you've got your desired geographic range, etc. To make a map, R will first have to query the NOAA database for data for a given geographic range that you provide. Visualizing this by creating maps is really helpful for deciding on the exact range that you want, but you don't want to waste time creating high-quality maps at this stage.

To query the NOAA database, use the following code:

Command

Where a and b are your chosen longitudes (forming a range) and c and d are your chosen latitudes. Keep the resolution at 10 (poor) for now to make map generation fast. Change the antimeridean setting if it applies to you (you have points spanning that longitude)

```
map1 <- getNOAA.bathy(lon1 = a, lon2 = b, lat1 = c lat2 = d,  
resolution = 10,  
keep = TRUE, antimeridian = FALSE)
```

To see a quick summary of your plot and generate a quick map in black and white:

Command

```
summary(map1)  
plot(map1)
```

Color Maps

7 This is my favorite color scheme:

Command

```
plot(map1, image = TRUE, bpal = blues(100),
     deep = c(-10000, -5000, 0),
     shallow = c(-7000, -10, 0),
     step = c(3000, 3000, 3000),
     lwd = c(0.8, 0.8, 0), lty = c(1, 1, 0),
     col = c("steelblue4", "steelblue", "seashell3"),
     drawlabel = c(FALSE, FALSE, FALSE))
# Creating a custom palette of blues
# USE THIS ONE FOR WINDOWS:
blues <- c("lightsteelblue4", "lightsteelblue3",
           "lightsteelblue2", "lightsteelblue1")
# Plotting the bathymetry with different colors for land and sea
plot(map1, image = TRUE, land = TRUE, lwd = 0, lty=0,
     bpal = list(c(0, max(map1), "seashell3"),
                 c(min(wrld),0,blues)))
```

Troubleshooting Errors

8 Message:

```
Error in if (ncol(x) == 3 & !exists("bathy", inherits = FALSE)) {
: argument is of length zero
```

This error occurs when the packages **rgdal** and **raster** are not up to date. Update them using



Command

The package name goes inside the parentheses, surrounded by quotes, eg `update.packages("rgdal")`

```
update.packages()
```