





Version 9 ▼ Oct 05, 2022

Wastewater QC workflow in GalaxyTrakr (SSQuAWK4) V.9

Jasmine Amirzadegan¹, Tunc Kayikcioglu¹, hugh.rand¹, Ruth Timme², Maria Balkey¹

¹Center for Food Safety and Applied Nutrition, U.S. Food and Drug Administration, College Park, Maryland, USA; ²US Food and Drug Administration

dx.doi.org/10.17504/protocols.io.kxygxzk5dv8j/v9

GenomeTrakr
Tech. support email: genomeTrakr@fda.hhs.gov

Jasmine Amirzadegan

DISCLAIMER

Please note that this protocol is public domain, which supersedes the CC-BY license default used by protocols.io.

ABSTRACT

PURPOSE:

Step-by-step instructions for checking sequence quality for SARS-CoV-2 wastewater samples using SSQuAWK: SARS - CoV - 2 Sequence Quality Assurance Workflow and Kontraption. The SSQuAWK workflow, implemented in CFSAN's custom Galaxy instance (GalaxyTrakr) will produce quality assessments for raw reads (Illumina MiSeq paired-end fastq files).

SCOPE: This protocol covers the following tasks:

- 1. Set up an account in GalaxyTrakr
- 2. Create a new history
- 3. Upload data and reference files
- 4. Execute the SSQuAWK workflow
- 5. Interpret the results

Protocol and SSQuAWK workflow version history:

- Protocol V9 SSQuAWK version 4: Protocol version 9 includes some additional primer bed files.
 All SSQuAWK4 protocol steps listed in this guide are applicable to SSQuAWK4.0.2.
- Protocol V8 SSQuAWK version 4: Protocol version 8 has minor text corrections. The SSQuAWK version 4 workflow required minor edits on an updated backend system of GalaxyTrakr, and thus is now labeled as "SSQuAWK4.0.2" in GalaxyTrakr. All SSQuAWK4 protocol steps listed in this guide are applicable to SSQuAWK4.0.2.
- Protocol V7 SSQuAWK version 4: Protocol now includes a QC determination guidance table. The SSQuAWK version 4 workflow required minor bug edits on the backend, thus is now labeled as "SSQuAWK4.0.1" in GalaxyTrakr. All SSQuAWK4 protocol steps listed in this guide are applicable to SSQuAWK4.0.1.
- Protocol V6 SSQuAWK version 4: Best practice guidance on fastq.gz file uploads and new QC metric.
- Protocol V5 SSQuAWK version 3: Previous protocol version had broken links for FASTA and BED files, this
 version fixes the links.
- Protocol V4 SSQuAWK version 3: Metrics now reported with fewer softwares, fewer underlying GalaxyTrakr jobs, and about 50% fewer underlying GalaxyTrakr steps. Cleaner output table formats now include QC placeholder columns for SRA metadata template.
- Protocol V3, SSQuAWK version 2: Addition of 5 new genome mapping metrics
- Protocol V2, SSQuAWK version 1: Addition of a detailed 12 minute video tutorial
- Protocol V1, SSQuAWK version 1: Basic protocol steps with screenshots

Participation was supported by the:

- Research Participation Program at the U.S. Food and Drug Administration administered by the Oak Ridge Institute for Science and Education (ORISE) through an interagency agreement between the U.S.
 Department of Energy and the U.S. Food and Drug Administration.
- Joint Institute for Food Safety and Applied Nutrition (JIFSAN), University of Maryland by the Food and Drug Administration (FDA) of the U.S. Department of Health and Human Services (HHS).
- The American Rescue Plan Act of 2021, Congress provided temporary funding for FDA to develop the capacity to sequence SARS-CoV-2 RNA from wastewater samples and to conduct a sampling and sequencing project through 2022.

DOI

dx.doi.org/10.17504/protocols.io.kxygxzk5dv8j/v9

EXTERNAL LINK

https://galaxytrakr.org



1

PROTOCOL CITATION Jasmine Amirzadegan, Tunc Kayikcioglu, hugh.rand, Ruth Timme, Maria Balkey 2022. Wastewater QC workflow in GalaxyTrakr (SSQuAWK4). protocols.io https://dx.doi.org/10.17504/protocols.io.kxygxzk5dv8j/v9 Version created by Jasmine Amirzadegan B KEYWORDS WGS, Quality Control, GalaxyTrakr, GenomeTrakr, microbial pathogen survielliance LICENSE This is an open access protocol distributed under the terms of the Creative Commons Attribution License, which permits unrestricted use, distribution, and reproduction in any medium, provided the original author and source are credited CREATED Oct 05, 2022 LAST MODIFIED Oct 05, 2022 PROTOCOL INTEGER ID 70879 DISCLAIMER:


Please note that this protocol is public domain, which supersedes the CC-BY license default used by protocols.io.

Account set up

1. Create a GalaxyTrakr account here: https://account.galaxytrakr.org/Account/Register



1.1 Log into your GalaxyTrakr account: https://galaxytrakr.org



Create a new history

2 Create a new history.

We recommend creating a new history for each new MiSeq sequence set with details and date in the history name.

Save your SSQuAWK output here with any other relevant analyses.

After all the analysis output from this run is saved to your internal data network or computer, older history's should

protocols.io

2


be purged/deleted so as not to occupy the limited storage space in your account.

In some cases it may be useful to save, for a limited time, multiple histories or to run analyses concurrently in multiple histories.

In these cases you need to pay attention to your % usage bar (shows % used of allocated storage space) in the upper right corner of the GalaxyTrakr page.

If you need additional space you can contact $\underline{galaxytrakrsupport@fda.hhs.gov} \ and \ request \ additional \ storage.$

2.1 <u>Create a new history</u> with the "+" symbol in the upper right hand corner. Name your history and press "enter" on your keyboard to save the name.




Upload Sequence Data

- 3 This section will describe the process for uploading raw fastq files into your active History panel. After the files have been uploaded they will stay in your account until they are deleted.
 - 3.1 <u>Upload sequence data to your history</u>, using either of the two options circled in red below.



A window will appear in the middle of your screen. This is where you select your files using the "Choose local files" button at the bottom of the window. The "Choose local files" button is highlighted in green. These fastq.gz files should be paired (two per sample).




3.2

Before initiating the file upload, double check that the file "Type" is appropriately set.


Do not use the "Auto - Detect" option.

Sequence data uploaded using the "auto - detect" option may be subject to file corruption.


This can result in various downstream analysis issues, including empty output metrics and job errors.



Instead, use the "Type (set all)" dropdown to select the correct file type.



Once the file type is set, press "Start" to initiate your data upload to GalaxyTrakr. The "Start" button is circled in green.



3.3 As the file uploads complete, each row will turn green. If samples are shown with yellow background, then are still uploading.



3.4 You have just upload a set of forward and reverse reads. For further analysis these files need to be paired properly so the platform knows which R1 and R2 files go with each sample. GalaxyTrakr does this by creating a List of Dataset Pairs.

Within your newly created History panel, click the "check box," then select all the files you just uploaded by clicking "All" or by individually selecting the ones you want to pair.



3.5 Check all the files belonging to a pair. In this example, all the files belong to a pair, so I will use the "All" button (circled in red).

Then, use the "For all selected..." dropdown (circled in green), and click on "Build List of Dataset Pairs" (circled in blue).





3.6 GalaxyTrakr will automatically pair the files, but it's good to double check.

Paired reads will pair in the middle column and turn green.


If everything looks good, then choose a name for your pairs (circled red) and "Create List" (also circled red).



Alternatively, instead of auto-pairing you can click "choose filters" and select the appropriate filter for the pairing:




3.7 This paired dataset will now be available for analysis in your history panel. You can run multiple analyses on the same dataset in a history rather than upload the same sequence data to a new history to perform additional analyses. This will help you use your allocated storage space efficiently.



Upload reference data

4 To the existing history, also upload (1) the **provided reference.fasta file** and (1) a primer.bed file.




protocols.io

7

4.1 SSQuAWK is only compatible with the 22903 nt reference genome file obtained from NCBI 'NC_045512.2'. It is provided here for your convenience:

NC_045512.2.fa

4.2 The primer.bed file should correspond to the SARS - CoV - 2 enrichment primer panel kit used.




Run the SSQuAWK workflow

5 Access the SSQuAWK4.0.2* workflow with the "workflows" panel.

*SSQuAWK4.0.1: SARS - CoV - 2 Sequence Quality Assurance Workflow Kontraption, version 4.0.2

5.1 Navigate to the "Shared Data" drop down and choose workflows



Then, from the SSQuaWK4.0.1 drop down menu, select "Run".





8



5.2 Select the paired list you created earlier by selecting the folder icon (boxed in red), and then the list of pairs (boxed in green).

Boxed in gold: Select the reference fasta file from your history.

Boxed in blue: Select the bed file from your history.

Click Run Workflow (boxed in purple).



Running the workflow can take some time depending on the number of samples you are analyzing. Once GalaxyTrakr adds the workflow invocation to the queue, you can choose to log out of GalaxyTrakr and log back in at a later time to see if the job is completed.



5.3 Upon completion of the pipeline, the output file for SSQuAWK4.0.2 will be green. Click on the "Eye" icon to view in GalaxyTrakr window.




Interpret the results

- 6 Download and interpret the results:
 - 6.1 Click the output file text for "SSQuAWK4.0.2" (circled in red) and then the floppy disc save icon

protocols.io

9

(circled in blue). The tabular file can be opened in a text reader or converted to a format that can be opened in Excel.



6.2 The SSQuAWK4.0.1 output file includes the following metrics:

Α	В	С
Parameter	Tool	Description
Sample	List of Pairs	Sample name from list of pairs
0xGenomeCov	Bowtie2, samtools, ivar_trim	Percentage of nucleotides that do not cover the genome at all (zero times)
<10xGenomeCov	Bowtie2, samtools, ivar_trim	Percentage of nucleotides that barely cover the genome (less than 10 times)
nReads	Bowtie2	Total number of reads
avgLen	Bowtie2, samtools	Average read length
avgLenPassFilt	Bowtie2, samtools, ivar_trim	Average read length after iVar_trim filtering*
avgQual	Bowtie2, samtools	Average read quality
avgQualPassFilt	Bowtie2, samtools, ivar_trim	Average read length after iVar_trim filtering*
avgCovPassQual	Bowtie2, samtools, ivar_trim	Average number and percentage of nts from sequence reads that map to the genome
readsAlign	Bowtie2, samtools	Number and percentage of reads that aligned to the reference sequence.
readsAlignPassFilt	Bowtie2, samtools, ivar_trim	Number and percentage of reads that aligned to the reference sequence after iVar_trim filtering*.
SNR	Bowtie2, ivar_trim, Python3 and Pandas	SNR is "Signal to Noise Ratio". When the sequence dataset contains one paired sequence set containing "negativeControl" in its name, SNR will be calculated. Otherwise, the SNR metric will return "NA". The SNR calculation is as follows, for each sequence file pair: readsAlignPassFilt / readsAlignPassFilt_negativeContol
humanReads	Kraken2	Number and percentage of reads classified as <i>Homo sapiens</i>
SARS-CoV-2Reads	Kraken2	Number and percentage of reads classified as SARS - CoV - 2
syntheticSeqsReads	Kraken2	Number and percentage of reads classified as non - biological sequences
quality_control_method_name	SSQuAWK	Name of the method or pipline used to evaluate sequence quality
quality_control_method_version	4.0.2	Version number of the quality control pipeline or method used
quality_control_determination		Result of the quality control accessment. Blank if pass/fail thresholds have not been estabolished or "sequence flagged for potential quality control issues" if relevant.
quality_control_issues		More information for sequences that have a QC flag issue


^{*} The iVar_trim filter parameters: minReadLen = 30, minQual_slidingWindow = 20, and slidingWindow = 4 nt.

6.3 What is nucleotide coverage?! Let's look at 2 simple pictures



In the figure above, let the burgundy line represent the entire reference genome.

The blue lines are the reads, as sequenced nucleotides.



In the figure above, each star, drawn on the burgundy line (reference genome) is a nucleotide position.

There are 28 stars, so we will say our genome is 28 nucleotides long.

We can use coverage to determine the quality of our sequences (blue lines).

The lime green stars along the genome represent 0X coverage, because we did not sequence any reads with **nucleotides positions covering that reference nucleotide position**. There are no blue lines that we sequenced there!

There are 3 nucleotide positions with 0x coverage. The total genome is 28 nucleotides long.

 $percent_nt0Xcov = (nucleotidePositions0Xcov / genomeLength)*100$

percent_nt0Xcov = (3 / 28) *100

percent_nt0xcov = 10.71%

In most ideal scenarios, higher coverage indicates better sequence quality.

For example, 100x coverage is better than 10x coverage.

Since we want $\mbox{higher coverage}$, percent_nt0Xcov and percent_ntLess10Xcov are ideally $\mbox{lower percentages}$.

0x coverage and 10x coverage indicate "no coverage" and "poor coverage", respectively.

Generally, we expect avgReadCov in 100's or 1000's*

If **percent_nt0Xcov** is a higher percentage, say 50%*, that means half of the genome was not covered by our sequences. The quality is not ideal.

6.4 Example output for the first 3 pairs run through the SSQuAWK4.0.2 workflow:

Α	В	С	D	E	F	G	Н	I	J	К
Sample	0xGenomeCov	<10xGenomeCov	nReads	avgLen	avgLenPassFilt	avgQual	avgQualPassFilt	avgCovPassQual	readsAlign	readsAlignPassFilt
SRR16828363.fastq.gz	107nt (0%)	138nt (0%)	632664	151	151	37.8	37.9	688X	138637	136327 (21%)
									(21%)	
SRR16828364.fastq.qz	76nt (0%)	107nt (0%)	458116	151	151	37.8	37.9	890X	179913	176348 (38%)
									(39%)	,
SRR16828365.fastq.gz	76nt (0%)	153nt (0%)	351980	151	151	37.8	37.9	272X	54928 (15%)	53958 (15%)
									(13%)	

6.5 QC metric guidance for QC attributes on SRA metadata



^{*} These values are not official threshold and only used for illustrative purposes.

Α	В	С	D	E	F	G
QC bin	Subjective	% Genome	Average	Other	SRA	FDA CFSAN
	definition	uncovered	coverage	observations	submission	Dashboard
		(10X)				
Α		~5%	~1000X	Majority of	"quality_control_determination"	Included
	No QC issues			reads are	= no quality control issues	
	evident			SARS-CoV-2	identified	
В	Minor QC	6% - 40%	~100X		"quality_control_determination"	Included
	issues				= minor quality control	
					issues identified	
С	Insufficient	40% - 95%	< 100X	Insufficient	"quality_control_determination"	Excluded
	coverage			data mapped	= sequence flagged for	
				for confidence	potential quality control issues	
F	Significant	>95%	< 10X	Suspected	Do not submit	N/A
	QC and/or			contamination		
	study			(SNR low),		
	design issues			low sequence		
				quality,		
				other process		
				errors		
				identified		

Video Tutorial

7 Thanks for using SSQuAWK!

