

APR 14, 2024

# OPEN BACCESS



DOI:

dx.doi.org/10.17504/protocols.io.y xmvme785g3p/v1

**Protocol Citation:** Raymond Murray, Helen Schwerdt 2024. FSCV and Ephys Recording Setup. **protocols.io** https://dx.doi.org/10.17504/protocols.io.yxmvme785g3p/v1

License: This is an open access protocol distributed under the terms of the Creative Commons Attribution License, which permits unrestricted use, distribution, and reproduction in any medium, provided the original author and source are credited

Protocol status: Working

Created: Apr 07, 2024

Last Modified: Apr 14, 2024

# FSCV and Ephys Recording Setup

Raymond Murray<sup>1</sup>, Helen Schwerdt<sup>1,2</sup>

<sup>1</sup>Department of Bioengineering, University of Pittsburgh;

<sup>2</sup>Aligning Science Across Parkinson's (ASAP) Collaborative Research Network, Chevy Chase, MD

#### ASAP Collaborative Research Network



### Raymond Murray

Department of Bioengineering, University of Pittsburgh

#### **ABSTRACT**

Methods detailing the recording setup using both electrophysiological (Ephys) and fastscan cyclic voltammetry (FSCV) are described. PROTOCOL integer ID: 97884

## **Recording Setup**

- One to four selected probes were utilized to record dopamine concentrations using fast scan cyclic voltammetry (FSCV) while electrophysiological (Ephys) activity was recorded from all other implanted probes not connected to FSCV. Probes used to record dopamine in a given recording session were switched to record local field potentials (LFPs) in later recordings sessions to allow for recording both types of signals from the same site, and vise versa for probes originally recording LFPs.
- 2 A current-to-voltage converting head stage circuit was employed on probes recording FSCV, allowing the recording of current during concurrent application of a triangle wave via the FSCV system.
- Remaining probes were alternatively connected to a voltage-follower head stage circuit for Ephys recording to be amplified and digitized using the Digital Lynx SX system from Neuralynx.
- Ag/AgCl electrodes surgically implanted in the animal's epidural tissue or brain matter were grounded by the FSCV system, also serving as the FSCV and Ephys reference. The Ephys system ground was connected to the experimental rig.
- FSCV scans consisted of applying a triangle wave to each probe at a rate of 400 V/s at a frequency of 10 Hz. Specifically, each scan lasted 8.5 ms consisting of an initial ramp from -0.4 V to + 1.3 V, then returning -0.4 V. Color plots were generated by background subtracting currents at a specific timepoint and plotting scan voltage on the y-axis, time on the x-axis, and current change amplitude as color.
- **6** Dopamine redox was identified according to current changes at -0.2 and 0.6 V relative to the reference Ag/AgCl electrodes during each scan.
- Principal component regression analyses and correlation to dopamine and pH standards recorded from an in vitro flow cell environment were performed to ensure recorded currents were mostly related to dopamine redox.



- 8 The Ephys system recorded voltage inputs with a ± 1 mV range at 30 kHz with an applied bandpass filter from 0.1 Hz to 7500 Hz.
- 9 This system also recorded time stamps of identified task events utilizing parallel ports that conveyed 8-bit event codes. Software functions and a messaging system used concurrently with the Ephys system allowed for common time stamp output between the Ephys and FSCV systems.