



MAR 07, 2024

🌐 Homology Modelling of Pacer RH domain in SWISS-MODEL

📁 In 1 collection

Dan Tudorica¹

¹University of California, Berkeley



Dan Tudorica
Hurley Lab, QB3, UC Berkeley

ABSTRACT

Using the Rubicon RH - Rab7 crystal structure as a template (6wcw)

OPEN  ACCESS



DOI:

dx.doi.org/10.17504/protocols.io.bp2l6xmr1lqe/v1

Protocol Citation: Dan Tudorica 2024. Homology Modelling of Pacer RH domain in SWISS-MODEL. **protocols.io** <https://dx.doi.org/10.17504/protocols.io.bp2l6xmr1lqe/v1>

License: This is an open access protocol distributed under the terms of the [Creative Commons Attribution License](#), which permits unrestricted use, distribution, and reproduction in any medium, provided the original author and source are credited

Protocol status: Working

Created: Nov 09, 2023

Last Modified: Mar 07, 2024

Swiss-M

- 1 In Swiss Model,
 - > start new modelling project
 - > upload target sequence. Here, used the human Pacer (RUBCNL) sequence acquired from uniprot:


```
>sp|Q9H714|PACER_HUMAN Protein associated with UVRAG as autophagy enhancer OS=Homo sapiens
OX=9606 GN=RUBCNL PE=1 SV=3
MVSQSTVRQDSPVEPWEGISDHSGIIDGSPRLLNTDHPPCQLDIRLMRHKAVWINPQDVQ
QQPQDLQSQVPAAGNSGTHFVTDAASPSGSPSCLGDSLAETTLSEDTTDSVGSASPHGS
SEKSSSFSLSSTEVHMRPGYSHRVSLPTSPGILATSPYPETDSAFFEPSHLTSAADEGA
VQVSRRTISSNSFSPEVFLPVDVEKENAHFYVADMIISAMEKMKCNILSQQTESWSKE
VSGLLGSDQPDSEMTFDTNIKQESGSTSSYSGYEGCAVLQVSPVTETRTYHDVKEICKC
DVDEFVILELGFNDITETCSCSCSSSKSVTYEPDFNSAELLAKELYRVFQKCWILSVVN
SQLAGSLSAAGSIVVNEECVRKDFESSMNVVQEIKFSRIRGTEDWAPPRFQIIFNIHPP
LKRDLVVAQAQFFCAGCGTPVEPKFVKRLRYCEYLGKYFCDCCHSYAESCIPARILMMWD
FKKYYVSNFSKQLLDSIWHQPIFNLLSIGQSLYAKAKELDRVKEIQELFHIKKLLKTCR
FANSALKEFEQVPGHLTDELHLFSLEDLVRIKKGLLAPLLKDILKASLAHVAGCELCQGK
GFICEFCQNTTVIFPFQTATCRRCSACRACFHKQCFQSSECPRCARITARRKLLESVASA
AT
```
- 2 > Search for template
- 3 Search should yield a top hit corresponding to the Alphafold model of Pacer, and subsequent hits represent using the Rubicon RH domain as a template (6wcw).

Select the hit that aligns Pacer to the Rubicon structure (6wcw), and > build model. From here, the file can be downloaded as a PDB and used in downstream modelling steps.

Build Rab7 complex model

- 4
 - >Open Pymol
 - >open downloaded Pacer homology model

>fetch rubicon-rab7 dimer crystal structure by typing "fetch 6wcw" in the command line

5 >Align Rubicon crystal structure and Pacer homology model using the "align" command.

6 >Delete rubicon monomer, and expansion binding site between the pacer homology model and rab7. Focus on S72 of Rab7