

May 21, 2024

 $\odot$ 

Single-cell single-unit recordings in vitro



In 1 collection

DOI

dx.doi.org/10.17504/protocols.io.yxmvme269g3p/v1

Nicola Biagio Mercuri<sup>1</sup>

<sup>1</sup>Fondazione Santa Lucia IRCSS

ASAP Collaborative Rese...

Mercuri Lab



## Nicola Biagio Mercuri

Fondazione Santa Lucia IRCSS





DOI: dx.doi.org/10.17504/protocols.io.yxmvme269g3p/v1

**Protocol Citation:** Nicola Biagio Mercuri 2024. Single-cell single-unit recordings in vitro. **protocols.io** 

https://dx.doi.org/10.17504/protocols.io.yxmvme269g3p/v1

**License:** This is an open access protocol distributed under the terms of the **Creative Commons Attribution License**, which permits unrestricted use, distribution, and reproduction in any medium, provided the original author and source are credited

Protocol status: Working

Created: May 20, 2024

Last Modified: May 21, 2024

Protocol Integer ID: 100136

## **Abstract**

Single units in slices



## Single-cell single-unit recordings

- 1 The slice is placed in a submerged recording chamber in continuously flowing ACSF (34°C) saturated with 02/C02 gas mixture (95/5%).
- 1.1 ACSF composition (in mM): 126 NaCl, 2.5 KCl,1.2 MgCl<sub>2</sub>, 1.2 NaH2PO4, 2.4 CaCl2, 10 glucose and 25 NaHCO3.
- A glass microelectrode filled with ACSF (tip resistance 5–10  $M\Omega$ ) is slowly deepened into the slice, with voltage signals captured through an Axoclamp 2A amplifier using Clampex 10 software and digitized with a Digidata 1440 (Molecular Devices, LLC., 3860 N First Street San Jose, CA 95134 USA).
- When fast spontaneous transients are observed, the depth of the recording electrode is adjusted to obtain voltage signals as high as possible