



Multitrim V.2

Kenji Gerhardt¹, Kostas Konstantinidis¹

¹Georgia Institute of Technology

Version 2

Oct 22, 2020

1

Works for me

This protocol is published without a DOI.

kgerhardt



Kenji Gerhardt

ABSTRACT

Multitrim is an Illumina short read trimming pipeline which facilitates effectively and easily trimming either single end or paired end FASTQ data. Multitrim achieves high quality trimming results by automating the detection of Illumina adapter sequences and sequentially applying two independent read trimming tools with complimentary properties. The script additionally produces quality assessment reports for both the input reads and the post-trim reads, creates consistent naming conventions for results, and compresses the trimmed reads to save on space.

EXTERNAL LINK

<https://github.com/KGerhardt/multitrim>

ATTACHMENTS

[Multitrim How-To.pdf](#)

EXTERNAL LINK

<https://github.com/KGerhardt/multitrim>

PROTOCOL CITATION

Kenji Gerhardt, Kostas Konstantinidis 2020. Multitrim. **protocols.io**
<https://protocols.io/view/multitrim-bnsnmede>
Version created by Kenji Gerhardt



EXTERNAL LINK

<https://github.com/KGerhardt/multitrim>

KEYWORDS

trimming, read trimming, short read trimming

LICENSE

————— This is an open access protocol distributed under the terms of the [Creative Commons Attribution License](#), which permits unrestricted use, distribution, and reproduction in any medium, provided the original author and source are credited

CREATED

Oct 22, 2020

LAST MODIFIED

Oct 22, 2020

PROTOCOL INTEGER ID

43566

ATTACHMENTS

[Multitrim How-To.pdf](#)

ABSTRACT

Multitrim is an Illumina short read trimming pipeline which facilitates effectively and easily trimming either single

end or paired end FASTQ data. Multitrim achieves high quality trimming results by automating the detection of Illumina adapter sequences and sequentially applying two independent read trimming tools with complimentary properties. The script additionally produces quality assessment reports for both the input reads and the post-trim reads, creates consistent naming conventions for results, and compresses the trimmed reads to save on space.

- 1 All contents of this protocol are best viewed in either the attached manual [Multitrim_User_Manual.pdf](#), or by going to the [Multitrim user manual google doc](#). You can also follow the instructions on this page to achieve the same results.

⚡

- 2 Install the correct version of Anaconda or Miniconda for Python 3.6+ for your system, if it is not already present.

Note: Miniconda will take up less space on your computer, and is the recommended method of preparing your computer to run Multitrim, but Anaconda will

Step 2 includes a Step case.

Windows OS

Mac OS

Linux

step case

Windows OS

If you are using Windows, please install [Ubuntu for Windows](#), then follow all Linux instructions for installing Multitrim from the Ubuntu terminal. You can open the Ubuntu terminal by typing "Ubuntu" in the search bar after installing it.

- 3 Copy and paste the following lines of code in your system's terminal to download and install Multitrim and its dependencies:

```
curl https://raw.githubusercontent.com/KGerhardt/multitrim/master/multitrim.yml > multitrim.yml
conda env create -f multitrim.yml
```

- 4 Activate the Multitrim environment by entering the following line of code:

```
conda activate multitrim
```

- 5 Test if the installation worked by simply typing "multitrim" in your terminal. Usage instructions will appear if multitrim installed successfully.

- 6 Example usage

Single end:

```
multitrim -u unpaired_reads.fastq.gz -o output_directory --max
```

Paired end:

```
multitrim -1 forward_reads.fastq.gz -2 reverse_reads.fastq.gz -o output_directory --max
```