




Sep 23, 2022

fastANI analysis protocol

Jamie Harrison¹, David J Studholme¹¹University of Exeter1 *Works for me* Share

This protocol is published without a DOI.

 Jamie Harrison

ABSTRACT

this is the protocol to conduct ani analysis between groups of genomes using fastANI and produce the heatmap figure in R using the pheatmap package

PROTOCOL CITATION

Jamie Harrison, David J Studholme 2022. fastANI analysis protocol.
protocols.io
<https://protocols.io/view/fastani-analysis-protocol-cgritv4e>



LICENSE

————— This is an open access protocol distributed under the terms of the [Creative Commons Attribution License](https://creativecommons.org/licenses/by/4.0/), which permits unrestricted use, distribution, and reproduction in any medium, provided the original author and source are credited

CREATED

Sep 16, 2022

LAST MODIFIED

Sep 23, 2022

PROTOCOL INTEGER ID

70154

1 Create directory structure and link files

create directories

1.1

For this there needs to be two files, one listing query genomes and one listing reference genomes, each with a single filename per line. Suggested names for these files = query_list.txt, reference_list.txt

1.2 mkdir analysis query_genomes reference_genomes

Create directories

mkdir analysis query_genomes, reference_genomes

create dirs for each of analysis, query genomes and reference genomes

1.3 move to query dir

move to reference genomes dir

cd ../reference_genomes

change dir to reference_genomes dir

1.4

Copy reference_list.txt

cp ZZZZZZZZ/reference_list.txt .

Copy reference_list.txt to reference_genomes dir, where ZZZZZZZZ is location of reference_list.txt

1.5

link reference genomes to reference_genomes dir

```
while read i; do ln -s YYYYYYYY/${i} .;done <  
reference_list.txt
```

loop through reference_list.txt and link each reference genomes to reference_genomes dir. YYYYYYYY is the location of the genome fasta files

1.6 check soft links and remove bad links

check softlinks and remove any that don't work

```
find . -xtype l | xargs rm
```

check softlinks and remove any that don't work

1.7

create query genome list

```
ls *fasta > query_list.txt
```

1.8 move to reference dir

move to reference genomes dir

```
cd ../reference_genomes
```

change dir to reference_genomes dir

1.9

Copy reference_list.txt

cp ZZZZZZZZ/reference_list.txt .

Copy reference_list.txt to reference_genomes dir, where ZZZZZZZZ is location of reference_list.txt

1.10

link reference genomes to reference_genomes dir

**while read i; do ln -s YYYYYYYY/\${i} .;done <
reference_list.txt**

loop through reference_list.txt and link each reference genomes to reference_genomes dir. YYYYYYYY is the location of the genome fasta files

1.11

check softlinks and remove any that don't work

find . -xtype l | xargs rm

check softlinks and remove any that don't work

1.12

create query genome list

ls *fasta > query_list.txt

1.13

move to analysis dir

cd ../analysis

move to directory to be used for the analysis step

1.14

softlink all necessary files to analysis directory

ln -s ../reference_genomes/ref_list.txt .

ln -s ../reference_genomes/*fasta .

ln -s ../query_genomes/query_list.txt .

ln -s ../query_genomes/query_list.txt .

softlink all necessary files to the analysis directory to be used in the fastANI analysis

2

Perform fastANI analysis

fastANI --rl reflist.txt --ql querylist.txt --matrix -o fastANI_out

perform the fastANI analysis of the query genomes vs the reference genomes

-rl specifies reference list of genomes

-ql specifies query genome list

-matrix outputs a bottom half triangular matrix of results

-o specifies output file prefix

this step can also be submitted to job queue on HPC cluster.

3

reformat fastANI output

git clone https://github.com/jh288/fastANI_reformatter.git

the output of fastANI is not in a suitable format to produce figure but this is addressed with a simple script available from github

3.1

reformat fastANI output for figure prep

**fastANI_reformatter.pl fastANI_out >
fastANI_out_reformat.tab**

reformat fastANI output for use in the R package pheatmap to create the figure

4

produce heatmap figure in R

4.1

edit matrix tab file

**sed 's/.fasta//g' fastANI_out_reformat.tab >
fastANI_out_reformat_ed.tab**

sed -i 's/_/ /g' fastANI_out_reformat_ed.tab

remove ".fasta" and substitute spaces for underscores in taxa names

4.2

produce heatmap in R

##load libraries

library("pheatmap")

library("RColorBrewer")

##load matrix into dataframe

**b1<-read.delim("fastANI_out_reformat_ed.tab", header =T,
row.names=1, check.names=F)**

##set output parameters

**png("fastANI_out_reformat_ed.png", height=1500,
width=750)**

###run pheatmap

**pheatmap(t(as.matrix(b1)), color = brewer.pal(n = 7,
name = "Blues"), display_numbers=T, number_format =
"%0.2f", number_color="black")**

dev.off()

r code to produce heatmap of fastANI results.