

Sep 08, 2020

High-throughput SARS-CoV-2 RNA extraction from nasopharyngeal swabs using repurposed 3D printers.

Koen Vandelannoote¹

¹University of Melbourne

1 Works for me dx.doi.org/10.17504/protocols.io.bkynkxve

XPRIZE Rapid Covid Testing | Koen Vandelannoote

Koen Vandelannoote

ABSTRACT

Here, we describe a semi-automated workflow for paramagnetic bead-based extraction of SARS-CoV-2 RNA from human upper respiratory samples that uses low-cost repurposed *Creality3D* Ender-3 3D-printers and readily accessible reagents. The protocol described here is for the use of four instruments in parallel, each processing 24 samples, 96 samples per batch.

ATTACHMENTS

20200908_Ender_VX- RNA_ex_v10.gcode 500_extraction_template.xl

DOI

dx.doi.org/10.17504/protocols.io.bkynkxve

PROTOCOL CITATION

 $Koen\ Vandelannoote\ 2020.\ High-throughput\ SARS-CoV-2\ RNA\ extraction\ from\ nasopharyngeal\ swabs\ using\ repurposed\ 3D\ printers..\ \textbf{protocols.io}$

https://dx.doi.org/10.17504/protocols.io.bkynkxve

KEYWORDS

Ender VX-500, RNA extraction, 3D printer, SARS-CoV-2, nasopharyngeal swabs, COVID-19

LICENSE

This is an open access protocol distributed under the terms of the Creative Commons Attribution License, which permits unrestricted use, distribution, and reproduction in any medium, provided the original author and source are credited

CREATED

Sep 07, 2020

LAST MODIFIED

Sep 08, 2020

PROTOCOL INTEGER ID

41710

MATERIALS TEXT

REAGENTS:

Lysis buffer ([M]6 Molarity (M) Guanidinium thiocyanate , [M]150 Milimolar (mM) Tris-Cl pH8,
 [M]30 Milimolar (mM) EDTA pH8 , [M]90 Milimolar (mM) DTT , 3% (v/v) Triton X-100).

iprotocols.io

09/08/2020

Citation: Koen Vandelannoote (09/08/2020). High-throughput SARS-CoV-2 RNA extractionÃÂ from nasopharyngeal swabs using repurposed 3D printers.. https://dx.doi.org/10.17504/protocols.io.bkynkxve

■ SPRI bead mix prepared for RNA binding as described in https://openwetware.org/wiki/SPRI_bead_mix



This SPRI bead mix is a drop-in substitute for RNAClean XP beads (Beckman Coulter) at about 1/100 of the cost.

- 100% Ethanol
- 80% Ethanol solution
- Nuclease free water (NFW)

PLASTIC CONSUMABLES:

• 96-well plates with V-shaped wells (Greiner – Ref. 651201)



It is highly recommended to work with the specified 96-well plates. The use of alternative plates requires careful modifications to the Ender VX-500 "print protocol".

• 8-tube PCR strips (SSIbio - Ref. 3247-00)



It is highly recommended to work with the specified strip tubes. The use of alternative strips requires careful modifications to the Ender VX-500 "print protocol".

• 96 deep-well plates (Axygen product number P-DW-11-C-S)

SAFETY WARNINGS

Nasopharyngeal swab samples that may contain respiratory viruses should be handled in a Class II BSC. Standard PC2 laboratory personal protective equipment is required. This includes a long sleeved laboratory gown, gloves and safety glasses. Additionally, a face mask should be worn.

The lysis buffer contains guanidine thiocyanate which may produce hazardous gases (including hydrogen cyanide and chlorine) when combined with bleach (sodium hypochlorite) and/or strong acids.


Ethanol is a highly flammable liquid.

BEFORE STARTING

This protocol provides directions for the use of a 3D Printer RNA extraction apparatus we named the "Ender VX-500". The platform essentially consists of a *Creality3D Ender-3* printer repurposed by installing three different custom designed interlocking attachments on the printer's extruder mounting mechanism.

protocols.io


09/08/2020



These models can be obtained from https://www.thingiverse.com/koen_vdl/designs

A 3D print "job" can be executed on the printers which will emulate the movements required to make the magnetic combs on the mounted attachments run a paramagnetic bead-based RNA extraction protocol.

Here we describe how we can efficiently process 91 nasopharyngeal swab samples in parallel on 4 Ender VX-500 machines. The following is a graphical overview of the extraction precidure.



Pre-process sample information

1

Scan the barcodes of 91 nasopharyngeal swabs using a barcode scanner and the "20200908_Ender_VX-500_extraction_template.xlsx" spreadsheet.

- Populate the "SampleID" column of the "Sample log" sheet
- Randomly include a negative extraction control for every set of 24 swabs in the sheet.
- Randomly include a PCR no-template-control (NTC) control in the sheet.



The spreadsheet will automatically parse 5 plate dispensing charts that can be printed for convenience:

• 4 charts represent the plate layouts of the 4 Ender VX-500 extraction runs (of 24 samples each).

Citation: Koen Vandelannoote (09/08/2020). High-throughput SARS-CoV-2 RNA extractionÃÂ from nasopharyngeal swabs using repurposed 3D printers.. https://dx.doi.org/10.17504/protocols.io.bkynkxve

- 1 chart represents the plate layout of the 96-well plate on which the eluates of the 4 extraction runs will be combined.
- <u></u>

The "20200908_Ender_VX-500_extraction_template.xlsx" spreadsheet can be found as an attachement under the abstract tab.

Pre-dispense the samples into a deep-well 96 well plate

2 Transfer 100 uL of swab transport medium into a deep-well 96 well plate in a Class II BSC using the plate layout charts as a guide.

Prepare four Ender VX-500 machines for extraction

- 3 Attach three 8-tube PCR strips onto the "Tube holder".
 - **B**
- The caps of the strip fit tightly into the openings on the "Tube holder".
- Only hold the strips by the caps and make sure not to touch the outside of the tubes.
- 4 Seat the "Tube holder" into the "Adaptor".
- 5 Lock the "Tube holder" in place by inserting the provided Allan hex wrench. This will ensure the "Tube holder" is always inserted in the same position.
- 6 Place three "Magnetic bars" in the openings of the "Tube holder".

Prepare four 96-well plates for extraction

- 7 Add 18.5 μl Lysis buffer to columns 1, 5 and 9 of a 96-well plates with V-shaped wells using a multichannel pipette.
 - Resuspend any salted out guanidine thiocyanate crystals before dispensing the buffer. Incubate § 65 °C for © 00:10:00
- 8 Add 380 μl NFW to columns 4, 8 and 12 using a multichannel pipette.
- 9 Add
 150 μl [M]80 % (v/v) Ethanol to columns 2, 3, 6, 7, 10 and 11 using a multichannel pipette.



- The ethanol concentration will quickly lower in the air flow of the BSC.
- Always use a freshly made up Ethanol solution.
- 10 Transfer / pipet-mix **37 μl** of nasopharyngeal swab transport medium from the deep-well plate into columns 1, 5 and 9 using using a multichannel pipette and the relevant plate dispensing chart
- 11 Incubate the plate δ Room temperature for \bigcirc 00:01:00.
- 12 Transfer / pipet-mix 30 μl SPRI bead mix into columns 1, 5 and 9 using a multichannel pipette.
 - Shake the SPRI bead mix before use (the beads settle quickly).
- 13 Transfer / pipet-mix 285.5 μl [M] 100 % (v/v) Ethanol to columns 1, 5 and 9 using a multichannel pipette.
- 14 Incubate the plate § Room temperature for © 00:05:00.
 - The prepared plates need to be extracted on the Ender VX-500 machines immediately after this incubation step

Extract 4 plates on 4 Ender VX-500 machines

- 15 Insert the four 96-well plates onto four Ender VX-500 machines prepared for extraction
 - Ensure the microplates are correctly oriented by checking the position of the A1 marker.
- 16 Power on the Ender VX-500 machines.
- 17 Use the knob on the Ender VX-500 to start the extraction by selecting "Print from TF" and selecting "RNA_ex_v10.gcode".
 - The "RNA_ex_v10.gcode" print job which emulates the RNA extraction can be found as an attachment under the abstract tab.

- 18 The Ender VX-500 will:
 - Collect bead-RNA complex from the lysate (© 00:05:00)
 - Wash 1: vortex (© 00:01:00) & collect bead-RNA complex (© 00:01:30)
 - Wash 2: vortex (**⊙ 00:01:00**) & collect bead-RNA complex (**⊙ 00:01:30**)
 - Air dry (**© 00:05:00**)
 - Elute: vortex (**00:01:00**) & collect beads (**00:01:00**)
 - Raise the magnetic bars out of the eluates



After © 00:20:00 the machine will beep to indicate the run completed successfully.

- 19 Remove the 96-well plates from the Ender VX-500 machines.
- 20 Power off the Ender VX-500 machines.
- Place the 96-well plates on a 96 well magnetic rack and use a multichannel pipette to transfer **30 μl** of eluate onto a fresh 96-well plate that will combine the eluates of the 4 extraction runs.



■30 µl of eluate is sacrificed to prevent any bead SPRI bead carryover.

Machine clean-up

- 22 Carefully remove the "Tube holder" from the EnderVX-500 "Adaptor ".
- Use paper tissues to release the three 8-tube PCR strips from the "Tube holder" and decontaminate the attachment in a bath containing a 1% sodium hypochlorite solution for min **© 00:10:00**.