

3GPP TS 36.213 V15.3.0 (2018-09)

Technical Specification

3rd Generation Partnership Project; Technical Specification Group Radio Access Network; Evolved Universal Terrestrial Radio Access (E-UTRA); Physical layer procedures (Release 15)



Keywords

E-UTRA, radio, layer 1

3GPP

Postal address

3GPP support office address

650 Route des Lucioles – Sophia Antipolis
Valbonne – France
Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Internet

<http://www.3gpp.org>

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© 2018, 3GPP Organizational Partners (ARIB, ATIS, CCSA, ETSI, TSDSI, TTA, TTC).
All rights reserved.

UMTS™ is a Trade Mark of ETSI registered for the benefit of its members
3GPP™ is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners
LTE™ is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners
GSM® and the GSM logo are registered and owned by the GSM Association

Contents

Foreword.....	8
1 Scope.....	9
2 References.....	9
3 Symbols and abbreviations.....	10
3.1 Symbols.....	10
3.2 Abbreviations.....	10
4 Synchronization procedures.....	12
4.1 Cell search.....	12
4.2 Timing synchronization.....	12
4.2.1 Radio link monitoring.....	12
4.2.2 Inter-cell synchronization.....	12
4.2.3 Transmission timing adjustments.....	12
4.3 Timing for Secondary Cell Activation / Deactivation.....	14
5 Power control.....	15
5.1 Uplink power control.....	15
5.1.1 Physical uplink shared channel.....	15
5.1.1.1 UE behaviour.....	16
5.1.1.2 Power headroom.....	30
5.1.2 Physical uplink control channel.....	33
5.1.2.1 UE behaviour.....	34
5.1.3 Sounding Reference Symbol (SRS).....	39
5.1.3.1 UE behaviour.....	39
5.1.3.2 Power headroom for Type3 report.....	41
5.1.4 Power allocation for EUTRA dual connectivity.....	42
5.1.4.1 Dual connectivity power control Mode 1.....	42
5.1.4.2 Dual connectivity power control Mode 2.....	50
5.1.5 Power allocation for PUCCH-SCell.....	54
5.2 Downlink power allocation.....	55
5.2.1 eNodeB Relative Narrowband TX Power (RNTP) restrictions.....	57
6 Random access procedure.....	59
6.1 Physical non-synchronized random access procedure.....	59
6.1.1 Timing.....	60
6.2 Random Access Response Grant.....	61
7 Physical downlink shared channel related procedures.....	66
7.1 UE procedure for receiving the physical downlink shared channel.....	67
7.1.1 Single-antenna port scheme.....	85
7.1.2 Transmit diversity scheme.....	85
7.1.3 Large delay CDD scheme.....	85
7.1.4 Closed-loop spatial multiplexing scheme.....	85
7.1.5 Multi-user MIMO scheme.....	86
7.1.5A Dual layer scheme.....	86
7.1.5B Up to 8 layer transmission scheme.....	86
7.1.6 Resource allocation.....	86
7.1.6.1 Resource allocation type 0.....	88
7.1.6.2 Resource allocation type 1.....	89
7.1.6.3 Resource allocation type 2.....	90
7.1.6.4 PDSCH starting position.....	93
7.1.6.4A PDSCH starting position for BL/CE UEs.....	95
7.1.6.5 Physical Resource Block (PRB) bundling.....	95
7.1.7 Modulation order and transport block size determination.....	97
7.1.7.1 Modulation order and redundancy version determination.....	99
7.1.7.2 Transport block size determination.....	105
7.1.7.2.1 Transport blocks not mapped to two or more layer spatial multiplexing.....	109
7.1.7.2.2 Transport blocks mapped to two-layer spatial multiplexing.....	118

7.1.7.2.3	Transport blocks mapped for DCI Format 1C and DCI Format 6-2.....	118
7.1.7.2.4	Transport blocks mapped to three-layer spatial multiplexing.....	119
7.1.7.2.5	Transport blocks mapped to four-layer spatial multiplexing.....	119
7.1.7.2.6	Transport blocks mapped for BL/CE UEs configured with CEModeB and PDSCH bandwidth up to 1.4MHz.....	120
7.1.7.2.7	Transport blocks mapped for BL/CE UEs <i>SystemInformationBlockType1-BR</i>	121
7.1.7.2.8	Transport blocks mapped for UEs configured with <i>ce-pdsch-maxBandwidth-config</i> value of 5 MHz or with <i>pdsch-MaxBandwidth-SC-MTCH</i> value of 24 PRBs.....	121
7.1.7.3	Redundancy Version determination for Format 1C.....	121
7.1.8	Storing soft channel bits.....	122
7.1.9	PDSCH resource mapping parameters.....	122
7.1.10	Antenna ports quasi co-location for PDSCH.....	124
7.1.11	PDSCH subframe assignment for BL/CE UE.....	125
7.2	UE procedure for reporting Channel State Information (CSI).....	127
7.2.1	Aperiodic CSI Reporting using PUSCH.....	137
7.2.2	Periodic CSI Reporting using PUCCH.....	162
7.2.3	Channel Quality Indicator (CQI) definition.....	202
7.2.4	Precoding Matrix Indicator (PMI) definition.....	215
7.2.5	Channel-State Information – Reference Signal (CSI-RS) definition.....	243
7.2.6	Channel-State Information – Interference Measurement (CSI-IM) Resource definition.....	245
7.2.7	Zero Power CSI-RS Resource definition.....	245
7.2.8	CSI-RS Activation / Deactivation.....	245
7.3	UE procedure for reporting HARQ-ACK.....	246
7.3.1	FDD HARQ-ACK reporting procedure.....	248
7.3.2	TDD HARQ-ACK reporting procedure.....	253
7.3.2.1	TDD HARQ-ACK reporting procedure for same UL/DL configuration.....	253
7.3.2.2	TDD HARQ-ACK reporting procedure for different UL/DL configurations.....	268
7.3.3	FDD-TDD HARQ-ACK reporting procedure for primary cell frame structure type 1.....	276
7.3.4	FDD-TDD HARQ-ACK reporting procedure for primary cell frame structure type 2.....	277
8	Physical uplink shared channel related procedures.....	279
8.0	UE procedure for transmitting the physical uplink shared channel.....	279
8.0.1	Single-antenna port scheme.....	303
8.0.2	Closed-loop spatial multiplexing scheme.....	303
8.1	Resource allocation for PDCCH/EPDCCH/SPDCCH with uplink DCI format.....	304
8.1.1	Uplink resource allocation type 0.....	304
8.1.2	Uplink resource allocation type 1.....	305
8.1.3	Uplink resource allocation type 2.....	305
8.1.4	Uplink resource allocation type 3.....	306
8.1.5	Uplink resource allocation type 4.....	307
8.1.5.1	UL Resource Block Groups.....	307
8.1.6	Uplink resource allocation type 5.....	308
8.2	UE sounding procedure.....	310
8.3	UE HARQ-ACK procedure.....	321
8.3A	Autonomous uplink feedback procedure.....	323
8.4	UE PUSCH hopping procedure.....	323
8.4.1	Type 1 PUSCH hopping.....	324
8.4.2	Type 2 PUSCH hopping.....	324
8.5	UE Reference Symbol (RS) procedure.....	325
8.6	Modulation order, redundancy version and transport block size determination.....	326
8.6.1	Modulation order and redundancy version determination.....	326
8.6.2	Transport block size determination.....	334
8.6.3	Control information MCS offset determination.....	340
8.7	UE transmit antenna selection.....	344
8.8	Transmission timing adjustments.....	344
9	Physical downlink control channel procedures.....	344
9.1	UE procedure for determining physical downlink control channel assignment.....	345
9.1.1	PDCCH assignment procedure.....	345
9.1.2	PHICH assignment procedure.....	349
9.1.3	Control Format Indicator (CFI) assignment procedure.....	352
9.1.4	EPDCCH assignment procedure.....	353

9.1.4.1	EPDCCH starting position.....	360
9.1.4.2	Antenna ports quasi co-location for EPDCCH.....	360
9.1.4.3	Resource mapping parameters for EPDCCH.....	361
9.1.4.4	PRB-pair indication for EPDCCH.....	361
9.1.5	MPDCCH assignment procedure.....	362
9.1.5.1	MPDCCH starting position.....	368
9.1.5.2	Antenna ports quasi co-location for MPDCCH.....	369
9.1.6	SPDCCH assignment procedure.....	369
9.1.6.1	Resource mapping parameters for SPDCCH.....	370
9.1.6.2	PRB-pair indication for SPDCCH.....	370
9.1.6.3	Physical Resource Block (PRB) bundling for DMRS-based SPDCCH.....	371
9.1.6.4	Antenna ports quasi co-location for DMRS-based SPDCCH.....	371
9.2	PDCCH/EPDCCH/MPDCCH/SPDCCH validation for semi-persistent scheduling.....	373
9.2A	PDCCH/EPDCCH validation for autonomous uplink transmissions.....	375
9.3	PDCCH/EPDCCH/MPDCCH/SPDCCH control information procedure.....	376
10	Physical uplink control channel procedures.....	377
10.1	UE procedure for determining physical uplink control channel assignment.....	378
10.1.1	PUCCH format information.....	383
10.1.2	FDD HARQ-ACK feedback procedures.....	389
10.1.2.1	FDD HARQ-ACK procedure for one configured serving cell.....	389
10.1.2.2	FDD HARQ-ACK procedures for more than one configured serving cell.....	393
10.1.2.2.1	PUCCH format 1b with channel selection HARQ-ACK procedure.....	393
10.1.2.2.2	PUCCH format 3 HARQ-ACK procedure.....	397
10.1.2.2.3	PUCCH format 4 HARQ-ACK procedure.....	399
10.1.2.2.4	PUCCH format 5 HARQ-ACK procedure.....	402
10.1.3	TDD HARQ-ACK feedback procedures.....	403
10.1.3.1	TDD HARQ-ACK procedure for one configured serving cell.....	405
10.1.3.2	TDD HARQ-ACK procedure for more than one configured serving cell.....	419
10.1.3.2.1	PUCCH format 1b with channel selection HARQ-ACK procedure.....	419
10.1.3.2.2	PUCCH format 3 HARQ-ACK procedure.....	435
10.1.3.2.3	PUCCH format 4 HARQ-ACK procedure.....	442
10.1.3.2.4	PUCCH format 5 HARQ-ACK procedure.....	459
10.1.3A	FDD-TDD HARQ-ACK feedback procedures for primary cell frame structure type 2.....	459
10.1.4	HARQ-ACK Repetition procedure.....	461
10.1.5	Scheduling Request (SR) procedure.....	462
10.2	Uplink HARQ-ACK timing.....	464
11	Physical Multicast Channel (PMCH) related procedures.....	468
11.1	UE procedure for receiving the PMCH.....	468
11.2	UE procedure for receiving MCCH and system information change notification.....	469
12	Assumptions independent of physical channel.....	469
13	Uplink/Downlink configuration determination procedure for Frame Structure Type 2.....	469
13.1	UE procedure for determining eIMTA-uplink/downlink configuration.....	470
13A	Subframe configuration for Frame Structure Type 3.....	471
14	UE procedures related to Sidelink.....	474
14.1	Physical Sidelink Shared Channel related procedures.....	475
14.1.1	UE procedure for transmitting the PSSCH.....	475
14.1.1.1	UE procedure for determining subframes for transmitting PSSCH for sidelink transmission mode 1.....	477
14.1.1.1.1	Determination of subframe indicator bitmap.....	477
14.1.1.2	UE procedure for determining resource blocks for transmitting PSSCH for sidelink transmission mode 1.....	480
14.1.1.2.1	PSSCH resource allocation for sidelink transmission mode 1.....	480
14.1.1.2.2	PSSCH frequency hopping for sidelink transmission mode 1.....	481
14.1.1.3	UE procedure for determining subframes for transmitting PSSCH for sidelink transmission mode 2.....	481
14.1.1.4	UE procedure for determining resource blocks for transmitting PSSCH for sidelink transmission mode 2.....	482

14.1.1.4A	UE procedure for determining subframes and resource blocks for transmitting PSSCH for sidelink transmission mode 3.....	482
14.1.1.4B	UE procedure for determining subframes and resource blocks for transmitting PSSCH and reserving resources for sidelink transmission mode 4.....	483
14.1.1.4C	UE procedure for determining subframes and resource blocks for PSSCH transmission associated with an SCI format 1.....	483
14.1.1.5	UE procedure for PSSCH power control.....	485
14.1.1.6	UE procedure for determining the subset of resources to be reported to higher layers in PSSCH resource selection in sidelink transmission mode 4.....	486
14.1.1.7	Conditions for selecting resources when the number of HARQ transmissions is two in sidelink transmission mode 4.....	489
14.1.2	UE procedure for receiving the PSSCH.....	489
14.1.3	UE procedure for determining resource block pool and subframe pool for sidelink transmission mode 2.....	489
14.1.5	UE procedure for determining resource block pool and subframe pool for sidelink transmission mode 3 and 4.....	490
14.2	Physical Sidelink Control Channel related procedures.....	491
14.2.1	UE procedure for transmitting the PSCCH.....	491
14.2.1.1	UE procedure for determining subframes and resource blocks for transmitting PSCCH for sidelink transmission mode 1.....	494
14.2.1.2	UE procedure for determining subframes and resource blocks for transmitting PSCCH for sidelink transmission mode 2.....	495
14.2.1.3	UE procedure for PSCCH power control.....	495
14.2.2	UE procedure for receiving the PSCCH.....	496
14.2.3	UE procedure for determining resource block pool and subframe pool for PSCCH.....	496
14.2.4	UE procedure for determining resource block pool for PSCCH in sidelink transmission mode 3 and 4.....	497
15	Void.....	500
16	UE Procedures related to narrowband IoT.....	501
16.1	Synchronization procedures.....	501
16.1.1	Cell search.....	501
16.1.2	Timing synchronization.....	501
16.2	Power control.....	501
16.2.1	Uplink power control.....	501
16.2.1.1	Narrowband physical uplink shared channel.....	501
16.2.1.1.1	UE behaviour.....	501
16.2.1.1.2	Power headroom.....	502
16.2.1.2	SR.....	502
16.2.1.2.1	UE behaviour.....	502
16.2.2	Downlink power allocation.....	503
16.3	Random access procedure.....	503
16.3.1	Physical non-synchronized random access procedure.....	503
16.3.2	Timing.....	504
16.3.3	Narrowband random access response grant.....	505
16.4	Narrowband physical downlink shared channel related procedures.....	507
16.4.1	UE procedure for receiving the narrowband physical downlink shared channel.....	507
16.4.1.1	Single-antenna port scheme.....	510
16.4.1.2	Transmit diversity scheme.....	510
16.4.1.3	Resource allocation.....	510
16.4.1.4	NPDSCH starting position.....	513
16.4.1.5	Modulation order and transport block size determination.....	514
16.4.1.5.1	Transport blocks not mapped for <i>SystemInformationBlockType1-NB</i>	514
16.4.1.5.2	Transport blocks mapped for <i>SystemInformationBlockType1-NB</i>	515
16.4.2	UE procedure for reporting ACK/NACK.....	515
16.5	Narrowband physical uplink shared channel related procedures.....	516
16.5.1	UE procedure for transmitting format 1 narrowband physical uplink shared channel.....	516
16.5.1.1	Resource allocation.....	518
16.5.1.2	Modulation order, redundancy version and transport block size determination.....	519
16.5.2	UE procedure for NPUSCH retransmission.....	521
16.5.3	UE procedure for transmitting SR.....	521

16.6	Narrowband physical downlink control channel related procedures.....	521
16.6.1	NPDCCH starting position.....	526
16.6.2	NPDCCH control information procedure.....	527
16.6.3	NPDCCH validation for semi-persistent scheduling.....	527
16.7	Assumptions independent of physical channel related to narrowband IoT.....	527
16.8	UE procedure for acquiring cell-specific reference signal sequence and raster offset.....	527
16.9	UE procedure for receiving narrowband wake up signal.....	528
17	Wake-up signal related procedures for BL/CE UE.....	529
Annex A (informative): Change history.....		530