Code Metrics

С		Interfac	Interface metrics		trics
class	Cyclic	Dcy	Dcy*	□ □ Dpt	Dpt*
x.operators.OperationOnExceptionResumeNextViaObservableTest.TestObse	. 0	4	7	1	1
x.operators.OperationTimeout.Timeout	216	14	1610	1	398
x.operators.OperationSingle	216	10	1610	1	398
x.operators.OperationSkip.Skip.ItemObserver	216	3	1610	1	398
x.operators.OperationTakeUntil.OtherObservable	216	8	1610	1	398
x.operators.OperationTimeout.TimeoutSelector	216	13	1610	1	398
x.schedulers.TestScheduler.CompareActionsByTime	0	1	7	1	33
x.schedulers.TestScheduler.InnerTestScheduler	1	5	13	1	32
x.android.observables.AndroidObservable	0	4	1631	1	1
x.observers.SynchronizedObserverTest.CompletionThread	0	2	3	1	1
x.operators.OperationConditionals	0	12	1625	1	2
x.operators.OperationSkipWhile.SkipWhile.SkipWhileObserver	216	4	1610	1	398
x.operators.OperationSample.SampleWithObservable.ResultManager.Sampler	216	3	1610	1	398
x.apache.http.consumers.ResponseConsumerBasic	0	8	1615	1	3

SWEN-261 Introduction to Software Engineering

Department of Software Engineering Rochester Institute of Technology



A metric is not just a number.

- A metric is a quantitative function that calculates some characteristic and produces a numeric measurement which will be used to make a decision.
- For software product development, metrics fall into three broad categories
 - Process measurements of the software process that apply across projects
 - Project measurements of one project team's activities
 - Product measurements of the resulting software product

Software product metrics fall into multiple categories that look at different characteristics.

- Complexity
 - Lines of Code is the most familiar
 - Cyclomatic Complexity
- Coupling and Dependency
 - Robert Martin Package Metrics
- Counting/averaging lots of things that can be counted/measured
 - Average lines per method
 - Average parameters per method
 - Average number of methods per class
- Some metrics will apply at multiple levels, such as project, package, class, or method

Software Engineering
Rochester Institute

Even though you can count something, it does not necessarily count for anything.

- A metric is only as good as the decisions that it will be used to make.
- Measuring something without it having a solid connection to possibly improving what you are doing is a waste of time and resources.
- Target values for measurements should be set based on a record of past measurements and resulting performance.
 - Measurement not in some range

 some project quality was poorer
- Initially, measurements need to be made to find the correlations.

A metric target is not absolute.

- A measurement falling outside of a target range is not an absolute indictment.
- Measurements that do not fall in the target range indicate a place for additional scrutiny.
 - For product metrics, they indicate possible "code smells".
 - Places to consider for refactoring, redesign, or reimplementation



These are some of the more popular metrics for object-oriented software systems.

- Cyclomatic complexity
 - Count of execution paths through a method
- Chidamber and Kemerer
 - Coupling between object classes
 - Lack of cohesion in methods
- Martin Package Metrics
 - Fan-out coupling classes need something outside package
 - Fan-in coupling classes outside package use something inside package
 - Instability ratio of fan-out to fan-out + fan-in
 - Abstractness ratio of abstract classes and interfaces to total number in package

