AGENT EVOLUTION · NOTEBOOK 5 OF 8

Version 5 — Routing: Internal Data or the Web

A guide to `version5_agent_pinecone_sql_validation_tavily.ipynb`: how the agent decides between internal data, public web sources or both, what `web_search` does, and how to keep the two kinds of evidence apart.

PA

Tutor: Prudhvi Akella
Lead Data & AI Engineer · 13+ years in data engineering and AI architecture

Stack: LangChain `create_agent` · Bedrock chat model · OpenAI embeddings · Pinecone · PostgreSQL · Tavily

Tools: `lookup_schema` · `lookup_examples` · `lookup_common` · `validate_query` · `run_query` · `web_search`

1. What changes from Version 4
2. The end-to-end workflow
3. Routing: three kinds of question
4. Inside `web_search`
5. Domain filters
6. What the model gets back
7. The loop with six tools
8. One call, step by step
9. Keeping evidence apart
10. The prompt for Versions 5–7
11. Web content is untrusted text
12. Checking a web answer
13. The limitation, and what Version 6 changes
14. Key takeaways

1 What changes from Version 4




Figure 1. Version 5 adds a second kind of evidence: public web pages.

	Version 4	Version 5
Evidence sources	PostgreSQL + knowledge base	+ the public web
New tool	—	`web_search(query, include_domains, exclude_domains, max_results)`
New skill	—	**routing**: internal, web, or both

Prompt	SQL workflow	+ TOOL-SELECTION RULES and web evidence rules
SOURCE section	SQL that ran	SQL, web titles and URLs, labelled separately
Tools	5	6

2 The end-to-end workflow




Figure 2. Version 5 end to end. The model picks a route per question.

Every earlier version had one route: internal data. Version 5 adds a decision at the start. The model reads the question and asks itself which evidence it needs, then calls only those tools.

The rule that holds the routes together: **web search never replaces PostgreSQL for internal data**, and **a web-only question needs no SQL**.

3 Routing: three kinds of question




Figure 3. The routing decision the prompt describes.

Question	Route	Expected tools
What percentage of our orders were cancelled?	Internal	lookups → `validate_query` → `run_query`; **no** `web_search`
What is a typical cancellation rate in online retail? Use only statista.com or census.gov.	Web	`web_search` with `include_domains`; **no** SQL
How does our cancellation rate compare with the industry average?	Both	SQL tools **and** `web_search`; sources labelled apart
What does "average order value" usually mean?	Neither / KB	a direct answer, or `lookup_common` for our definition

The notebook runs the first three as its routing test. For each, read the trace and check which tools were called. Extra tools mean wasted passes; missing tools mean a weaker answer.

> The routing words matter. "**Our** orders" points to internal data. "**Typical** rate in **online retail**" points to the web. "**Compare** ... with the **industry**" needs both. The prompt teaches these cues; the model applies them.

4 Inside `web_search`




Figure 4. Three steps. Every failure is returned as an `{"error": …}` dict, never raised.

This is the schema the model sees for `web_search`, as LangChain builds it from the function:

Parameter	Type	Meaning
`query`	string, **required**	what to search for
`include_domains`	list of strings or null	only return results from these sites
`exclude_domains`	list of strings or null	never return results from these sites
`max_results`	integer, default 5	clamped to 1–10 by the tool

The docstring is sent as the description, including its `Args:` block and the line “This tool does not query internal databases”. That line is part of routing: it tells the model what this tool cannot do.

- **Clamping:** a request for 50 results becomes 10; a request for 0 becomes 1. The model cannot pull an unlimited amount of web text into the conversation.
- **Search depth is fixed at `"basic"`**, the faster and cheaper Tavily mode.
- **No key, no crash.** Without `TAVILY_API_KEY` the tool returns `{"error": "Tavily is not configured…"}`. The agent still works for internal questions.

5 Domain filters




Figure 5. Real input and output of the domain clean-up in the notebook's code.

Models often pass full URLs where a domain is expected. The tool cleans every entry before sending it, so the filter works whatever form the model used. A test run showed exactly this: the model passed `https://www.statista.com/x` and Tavily received `www.statista.com`.

User says	Model should send

“Use only statista.com or census.gov”	`include_domains=["statista.com", "census.gov"]`
“Don't use Reddit”	`exclude_domains=["reddit.com"]`
nothing about sources	no filters — the prompt says “do not invent arbitrary domain restrictions”

> The clean-up keeps a `www.` prefix if the model sends one. To be safe, ask for bare domains (`statista.com`) in your own questions, as in the examples above.

6 What the model gets back




Figure 6. The dict becomes a JSON string inside the `ToolMessage`. Field values are illustrative.

`web_search` is the first tool in the series that returns a **dict** instead of a string. The model cannot read Python objects, so LangChain turns the dict into JSON text when it builds the `ToolMessage`. This was checked on the notebook's agent: the message content is a `str` that starts with `{"results": …`.

Field	Used by the model for
`title`	naming the source in SOURCE
`url`	the citation — must be copied exactly, never invented
`content`	a short extract of the page: the actual evidence
`score`	how relevant Tavily judged the result

> **The model sees extracts, not whole pages.** `content` is a short piece of each page. A claim in the answer must be supported by that text, not by what the model assumes the rest of the page says.

7 The loop with six tools




Figure 7. Still four graph nodes. The pass list is the message order from a test run of the notebook's agent.

The graph is the same as in every version since Version 2. What grows is the work per question. A “both” question touches every kind of tool.

Route	Typical passes	Tools used
Web only	2	`web_search` → answer
Internal, clean	4	lookup → validate → run → answer
Both, clean	5	lookup → web → validate → run → answer
Both, one SQL repair	6	as Figure 7

> The model may also ask for `web_search` and a lookup in the **same** reply. The `tools` node then runs both in one step, which saves a pass. Whether it does depends on the model, not on our code.

8 One call, step by step

```
result["messages"] == [
  HumanMessage("How does our order cancellation rate compare with the industry average?"),

  AIMessage(tool_calls=[lookup_schema(term="order status cancelled")]),
  ToolMessage("RESULT 1 | id=col-orders-status | ...", name="lookup_schema"),

  AIMessage(tool_calls=[web_search(query="average ecommerce order cancellation rate")]),
  ToolMessage('{"results": [{"title": "...", "url": "https://...", "content": "...",
              "score": 0.81}, ...]}', name="web_search"),

  AIMessage(tool_calls=[validate_query(sql="SELECT ... COUNT(*) FILTER (WHERE status =
'cancelled') ...")]),
  ToolMessage("VALIDATION PASSED: ...", name="validate_query"),

  AIMessage(tool_calls=[run_query(sql="SELECT ... COUNT(*) FILTER (WHERE status = 'cancelled')
...")]),
  ToolMessage("cancelled | total | rate\n7 | 140 | 5.0\n(1 rows.)", name="run_query"),

  AIMessage("ANSWER: Our rate is 5.0%. Public sources put a typical rate at ... ")
]
```

Figure 8. Message list for a “both” question, shortened. SQL, values and sources are illustrative.

The order between web and SQL does not matter. What matters is that both kinds of evidence are in the message list before the final answer, each in its own `ToolMessage` with its own `name`. That is what lets the answer, and anyone reading the trace, tell them apart.

9 Keeping evidence apart




Figure 9. The shape of a good “both” answer. Bracketed parts are placeholders.

The prompt's evidence rules, in plain terms:

Rule	Why
Label which facts came from PostgreSQL and which from the web.	Readers trust the two very differently. Our numbers are exact; a public figure is someone else's estimate.
Treat web results as external evidence, never as facts about our business.	A page about “online retail” says nothing about our orders.

Never invent titles, URLs, dates or citations.	A made-up URL looks exactly like a real one. Only URLs returned by `web_search` may appear.
Distinguish facts from interpretation.	“Source says 4%” is a fact; “so we are doing badly” is a judgement.
Say when sources are weak or conflict; do not call the search exhaustive.	Five search results are a sample, not the whole web.

Compare like with like. Our rate and a public benchmark are often measured differently: different years, regions, or definitions of “cancelled”. The CAVEAT section is where those mismatches belong.

10 The prompt for Versions 5–7




Figure 10. The Version 5 prompt. Red blocks are new for web search.

Version 5 introduces the prompt that Versions 6 and 7 keep **unchanged**. That is deliberate: the next two lessons add middleware, and keeping the prompt fixed means any change in behaviour comes from the code, not from new wording.

Block	Key lines
TOOL-SELECTION RULES	“Use web_search when the question requires current or external information...” · “Use both PostgreSQL and web_search when the user asks to compare internal performance with external information.” · “Do not use web search as a substitute for querying internal business data.” · “Do not call every tool automatically.”
Domain rules	“When the user specifies allowed websites, pass them through include_domains... Do not invent arbitrary domain restrictions.”
EVIDENCE AND SAFETY	“For web-based claims, cite or list the source URLs returned by Tavily...” · “label which information came from PostgreSQL and which came from web sources.”
OUTPUT FORMAT	ANSWER · DENOMINATOR · SOURCE · CAVEAT, with “Do not force SQL-specific sections onto a web-only answer.”

11 Web content is untrusted text




Figure 11. Anything on a web page enters the model's context. Example page text is illustrative.

Until Version 5, every piece of text the model read came from our own systems: our prompt, our knowledge base, our database. `web_search` is the first tool that brings in text written by **strangers**.

That text lands in the same message list as everything else. If a page contains something that looks like an instruction, the model reads it. This is called **prompt injection**. The agent cannot change data (every SQL path is read-only), but a page could still try to push the model into a wrong or misleading answer.

- **The prompt frames web results as evidence:** "Treat web results as external evidence, not as facts about the user's internal business."
- **Our numbers come only from SQL.** "Do not use web search as a substitute for querying internal business data." A web page cannot change what `run_query` returns.
- **Domain allow-lists** (`include_domains`) limit results to sources you trust.
- **The trace shows everything** the model read, so an odd answer can be traced to the page that caused it.

> These reduce the risk; they do not remove it. For sensitive uses, restrict web search to trusted domains, and review web-based answers before acting on them.

12 Checking a web answer

Check	How, in the trace
Every URL is real	each URL in SOURCE appears in a `web_search` observation
Every web claim is supported	the figure or fact appears in that result's `content`
Domain filters were respected	the `web_search` call carries the user's `include_domains` / `exclude_domains`
Internal numbers came from SQL	they appear in a `run_query` observation, not a web result
The route was right	no SQL for a web-only question; no web search for an internal one
Mismatches are flagged	CAVEAT mentions differences in year, region or definition

13 The limitation, and what Version 6 changes




Figure 12. Each version adds capability, and more model passes per question.

Six tools give the agent many ways to keep going. Nothing in Version 5 limits how many times it calls them. In particular:

- **It can run SQL again and again,** each time trying a slightly different query, with no stopping point.
- **Every pass resends the whole message list,** including large web and SQL results. Cost and time grow with each loop.
- **The prompt cannot enforce a limit.** Telling the model “run at most 3 queries” is a request it may not follow.

	Version 5	Version 6
Limit on SQL executions	none	at most 3 `run_query` calls per run
Where the limit lives	—	**middleware** code that wraps every tool call
Tools / prompt	6 / Version 5 prompt	unchanged / unchanged
Agent state	messages	messages + `sql_call_count`

14 Key takeaways

1. **Routing comes first.** The model decides per question: internal data, the web, or both.
2. **Web search never replaces SQL for our data,** and a web-only question needs no SQL.
3. `web_search` **has one required parameter** (`query`) and three optional ones; `max_results` is clamped to 1–10.
4. **Clean what the model sends.** Full URLs become domains before reaching Tavily.
5. **Pass only the user's domain filters;** invent none.
6. **A dict result becomes JSON text** in the `ToolMessage` ; the model reads title, url, content and score.
7. **Keep evidence apart.** Label PostgreSQL and web sources separately; copy URLs exactly.
8. **Web text is untrusted.** It enters the model's context like any other text; treat it as data, not instructions.
9. **The prompt is fixed from here to Version 7,** so the next lessons change only code.
10. **More tools mean more passes,** and Version 5 has no limit on them.

> **Next — Version 6:** the first middleware. `SQLBudgetMiddleware` wraps every tool call, counts `run_query` executions in agent state, and blocks the fourth before it reaches the database.