

SQL QUERIES

```
mysql> CREATE DATABASE sales_db;
Query OK, 1 row affected (0.05 sec)

mysql> USE sales_db;
Database changed
mysql> CREATE TABLE orders (
  ->     Order_ID INT,
  ->     Customer_ID INT,
  ->     Revenue DECIMAL(10,2)
  -> );
Query OK, 0 rows affected (0.06 sec)

mysql> INSERT INTO orders (Order_ID, Customer_ID, Revenue)
  -> VALUES
  -> (1, 101, 5000),
  -> (2, 102, 3000),
  -> (3, 101, 7000),
  -> (4, 103, 2000),
  -> (5, 101, 4000),
  -> (6, 102, 6000);
Query OK, 6 rows affected (0.06 sec)
Records: 6  Duplicates: 0  Warnings: 0

mysql>
mysql> SELECT Customer_ID, SUM(Revenue)
  -> FROM orders
  -> GROUP BY Customer_ID
  -> ORDER BY SUM(Revenue) DESC;
```

```
mysql> INSERT INTO orders (Order_ID, Customer_ID, Revenue)
-> VALUES
-> (1, 101, 5000),
-> (2, 102, 3000),
-> (3, 101, 7000),
-> (4, 103, 2000),
-> (5, 101, 4000),
-> (6, 102, 6000);
```

Query OK, 6 rows affected (0.06 sec)
Records: 6 Duplicates: 0 Warnings: 0

```
mysql>
mysql> SELECT Customer_ID, SUM(Revenue)
-> FROM orders
-> GROUP BY Customer_ID
-> ORDER BY SUM(Revenue) DESC;
```

Customer_ID	SUM(Revenue)
101	16000.00
102	9000.00
103	2000.00

3 rows in set (0.03 sec)

```
mysql> SELECT Customer_ID, COUNT(Order_ID)
-> FROM orders
-> GROUP BY Customer_ID
-> HAVING COUNT(Order_ID) > 1;
```

Customer_ID	COUNT(Order_ID)
101	3
102	2

2 rows in set (0.03 sec)

```
mysql> SELECT Customer_ID, SUM(Revenue) FROM orders GROUP BY Customer_ID ORDER BY SUM(Revenue) DESC;
```

Customer_ID	SUM(Revenue)
101	16000.00
102	9000.00
103	2000.00

3 rows in set (0.03 sec)

```
mysql> SELECT Customer_ID, COUNT(Order_ID)
-> FROM orders
-> GROUP BY Customer_ID
-> HAVING COUNT(Order_ID) > 1;
```

Customer_ID	COUNT(Order_ID)
101	3
102	2

2 rows in set (0.03 sec)

```
mysql> SELECT Customer_ID, SUM(Revenue) FROM orders GROUP BY Customer_ID ORDER BY SUM(Revenue) DESC;
```

Customer_ID	SUM(Revenue)
101	16000.00
102	9000.00
103	2000.00

3 rows in set (0.00 sec)