

OpenStack Swift Object Storage

Sachin*

April 19, 2017

1 Theory

- Swift allows users to store unstructured data(objects) with canonical names containing *three* part:
 - `/account`: Think *account* as a storage location and NOT user's account. *account* stores meta-data of that account, plus list of all containers in that account. *account* is analogous to `/home` directory which may hold multiple users.
 - `/account/container`: Think of container as a root directory of user(analogous to `/home/<USER>/`). Account can have many containers with no limit.
 - `/account/container/object`: This is actual file. User may start storing a single file(files are stored in container as an object), or hierarchical data like `/photos/alaska/magic-bus/me.jpg` as an object. Swift stores multiple copies of single object across physical locations to ensure the data reliability and availability.
- Remember that, user do not have to know the actual location of the data. In-fact he never knows. User always access the data in the form of `/account/container/object`.

2 Handy commands

- *My settings*:
 - Swift server address: `saio:8080`
 - AuthURL: `http://saio:8080/auth/v1.0`
 - PublicURL/StorageURL: `http://saio:8080/v1/AUTH_wasteland`
 - account: `wasteland`
 - container: `keys`
 - object: `mykey.pem`
- If you have access to Swift server, Public-URL/StorageURL, Auth-Token, & account can be fetched using following command,

```
swift stat -v
#           StorageURL: http://saio:8080/v1/AUTH_wasteland
#           Auth Token: AUTH_tk968b0ae7947640be874af6cd897a2b1e
#           Account: AUTH_wasteland
#           Containers: 0
#           Objects: 0
#           Bytes: 0
# Containers in policy "default": 1
# Objects in policy "default": 0
# Bytes in policy "default": 0
#           Accept-Ranges: bytes
#           X-Timestamp: 1463138224.81309
#           X-Trans-Id: tx1fe3ecbeb9f04fdc92287-005735e92c
#           Content-Type: text/plain; charset=utf-8
```

*psachin@redhat.com

- New user can be added as follows,

```
# --- /etc/swift/proxy-server.conf ---
[filter:tempauth]
use = egg:swift#tempauth
# user_ACCOUNT_USER = PASSWORD [GROUP] <storage URL:8080>
user_wasteland_psachin = psachin .admin .reseller_admin

[app:proxy-server]
use = egg:swift#proxy
allow_account_management = true
account_autocreate = true
# --- File ends here ---

# Restart servers and Proxy
swift-init account restart
swift-init container restart
swift-init object restart
swift-init proxy restart
```

- Managing container and object using `swift` command

Set following environmental variables

```
# --- ~/.profile ---
export ST_AUTH=http://saio:8080/auth/v1.0
export ST_USER=wasteland:psachin
export ST_KEY=psachin
# --- File ends here ---
```

Source the file before executing any command

```
source ~/.profile
```

If swift is enabled using packstack no configuration is needed. You can actually start from here.

```
# --- Create container: 'keys' ---
swift post keys
# Verify/list containers
swift list
# --- Upload an object to container ---
# Create a file
echo "746c1c636cebe7a888fd77688dbfc252" > mykey.pem
# Upload object-'mykey.pem' to container-'keys'
swift upload keys mykey.pem
# Verify the object
swift list keys
# --- Download object ---
swift download keys mykey.pem
# Download object with different name
swift download keys mykey.pem -o mykey2.pem
```

- Another way to access swift container/object is to provide username & password.

```
# swift -U <ACCOUNT>:<USER> -K <PASSWORD> COMMAND
swift -U wasteland:psachin -K psachin stat -v
#
#           StorageURL: http://saio:8080/v1/AUTH_wasteland
#           Auth Token: AUTH_tkf551ef98eb1e442b9efcef1261d87c64
#           Account: AUTH_wasteland
#           Containers: 1
#           Objects: 0
#           Bytes: 0
# Containers in policy "default": 1
# Objects in policy "default": 0
```

```

#       Bytes in policy "default": 0
#       Accept-Ranges: bytes
#       X-Timestamp: 1463292608.77517
#       X-Trans-Id: txc8bc7ba0659b497fb170f-00573b0ff4
#       Content-Type: text/plain; charset=utf-8

# Upload an object
# swift -U <ACCOUNT>:<USER> -K <PASSWORD> upload <CONTAINER> <file/object>
swift -U wasteland:psachin -K psachin upload keys mykey.pem

```

- Managing container and object using APIs(curl command)

```

# --- Get token ---
# Set authURL and publicURL
export authURL="http://saio:8080/auth/v1.0/"
export publicURL="http://saio:8080/v1/AUTH_wasteland"

curl -v \
    -H "X-Auth-User: wasteland:psachin" \
    -H "X-Auth-Key: psachin" \
    $authURL

# *   Trying 192.168.8.80...
# *   Connected to 192.168.8.80 (192.168.8.80) port 8080 (#0)
# > GET /auth/v1.0/ HTTP/1.1
# > Host: 192.168.8.80:8080
# > User-Agent: curl/7.43.0
# > Accept: */*
# > X-Auth-User: wasteland:psachin
# > X-Auth-Key: psachin
# >
# < HTTP/1.1 200 OK
# < X-Storage-Url: http://192.168.8.80:8080/v1/AUTH_wasteland
# < X-Auth-Token-Expires: 82975
# < X-Auth-Token: AUTH_tk968b0ae7947640be874af6cd897a2b1e
# < Content-Type: text/html; charset=UTF-8
# < X-Storage-Token: AUTH_tk968b0ae7947640be874af6cd897a2b1e
# < Content-Length: 0
# < X-Trans-Id: tx9c1bef9065754dd9b68ec-005735c49d
# < Date: Fri, 13 May 2016 12:12:13 GMT
# <
# * Connection #0 to host 192.168.8.80 left intact

export token="AUTH_tk968b0ae7947640be874af6cd897a2b1e"

# Verify account access
curl -v \
    -H "X-Storage-Token: $token" \
    $publicURL

# *   Trying 192.168.8.80...
# *   Connected to 192.168.8.80 (192.168.8.80) port 8080 (#0)
# > GET /v1/AUTH_wasteland HTTP/1.1
# > Host: 192.168.8.80:8080
# > User-Agent: curl/7.43.0
# > Accept: */*
# > X-Storage-Token: AUTH_tk968b0ae7947640be874af6cd897a2b1e
# >
# < HTTP/1.1 204 No Content
# < Content-Length: 0
# < Accept-Ranges: bytes

```

```

# < X-Account-Object-Count: 0
# < X-Account-Storage-Policy-Default-Bytes-Used: 0
# < X-Account-Storage-Policy-Default-Object-Count: 0
# < X-Timestamp: 1463138224.81309
# < X-Account-Bytes-Used: 0
# < X-Account-Container-Count: 0
# < Content-Type: text/plain; charset=utf-8
# < X-Account-Storage-Policy-Default-Container-Count: 0
# < X-Trans-Id: tx95142c218202459399c88-005735cac1
# < Date: Fri, 13 May 2016 12:38:25 GMT
# <
# * Connection #0 to host 192.168.8.80 left intact

# --- Create a container: 'keys' ---
curl -v \
    -H "X-Storage-Token: $token" \
    -X PUT $publicURL/keys

# * Trying 192.168.8.80...
# * Connected to 192.168.8.80 (192.168.8.80) port 8080 (#0)
# > PUT /v1/AUTH_wasteland/keys HTTP/1.1
# > Host: 192.168.8.80:8080
# > User-Agent: curl/7.43.0
# > Accept: */*
# > X-Storage-Token: AUTH_tk968b0ae7947640be874af6cd897a2b1e
# >
# < HTTP/1.1 201 Created
# < Content-Length: 0
# < Content-Type: text/html; charset=UTF-8
# < X-Trans-Id: tx39b7aee463b64127adfe2-005735cb92
# < Date: Fri, 13 May 2016 12:41:54 GMT
# <
# * Connection #0 to host 192.168.8.80 left intact

# Verify container
curl -v \
    -H "X-Storage-Token: $token" \
    -X GET $publicURL/keys

# * Trying 192.168.8.80...
# * Connected to 192.168.8.80 (192.168.8.80) port 8080 (#0)
# > GET /v1/AUTH_wasteland/keys HTTP/1.1
# > Host: 192.168.8.80:8080
# > User-Agent: curl/7.43.0
# > Accept: */*
# > X-Storage-Token: AUTH_tk968b0ae7947640be874af6cd897a2b1e
# >
# < HTTP/1.1 204 No Content
# < Content-Length: 0
# < X-Container-Object-Count: 0
# < Accept-Ranges: bytes
# < X-Storage-Policy: default
# < X-Container-Bytes-Used: 0
# < X-Timestamp: 1463138224.83257
# < Content-Type: text/html; charset=UTF-8
# < X-Trans-Id: tx05408e3d41c246ea930f5-005735cc21
# < Date: Fri, 13 May 2016 12:44:17 GMT
# <
# * Connection #0 to host 192.168.8.80 left intact

```

```

# --- Upload object to container ---
# Create a file
echo "746c1c636cebe7a888fd77688dbfc252" > mykey.pem

# Upload object-'mykey.pem' to container-'keys'
curl -v \
    -H "X-Storage-Token: $token" \
    -X PUT $publicURL/keys/mykey.pem -T mykey.pem

# * Trying 192.168.8.80...
# * Connected to 192.168.8.80 (192.168.8.80) port 8080 (#0)
# > PUT /v1/AUTH_wasteland/keys/mykey.pem HTTP/1.1
# > Host: 192.168.8.80:8080
# > User-Agent: curl/7.43.0
# > Accept: */*
# > X-Storage-Token: AUTH_tk968b0ae7947640be874af6cd897a2b1e
# > Content-Length: 43
# > Expect: 100-continue
# >
# < HTTP/1.1 100 Continue
# * We are completely uploaded and fine
# < HTTP/1.1 201 Created
# < Last-Modified: Fri, 13 May 2016 12:53:00 GMT
# < Content-Length: 0
# < Etag: 640ebd176639fb6ef9a3227770ee7b17
# < Content-Type: text/html; charset=UTF-8
# < X-Trans-Id: tx33923d6fbfe4523b4451-005735ce2b
# < Date: Fri, 13 May 2016 12:52:59 GMT
# <
# * Connection #0 to host 192.168.8.80 left intact

# Download an object
curl -v \
    -H "X-Storage-Token: $token" \
    -X GET $publicURL/keys/mykey.pem > mykey.pem

# * Trying 192.168.8.80...
# % Total    % Received % Xferd  Average Speed   Time    Time     Time  Current
#                                 Dload  Upload   Total   Spent    Left   Speed
#
#      0      0     0     0     0     0     0     0     0  --:--:-- --:--:-- --:--:--  0* \
#
# Connected to 192.168.8.80 (192.168.8.80) port 8080 (#0)
# > GET /v1/AUTH_wasteland/keys/mykey.pem HTTP/1.1
# > Host: 192.168.8.80:8080
# > User-Agent: curl/7.43.0
# > Accept: */*
# > X-Storage-Token: AUTH_tk968b0ae7947640be874af6cd897a2b1e
# >
# < HTTP/1.1 200 OK
# < Content-Length: 43
# < Accept-Ranges: bytes
# < Last-Modified: Fri, 13 May 2016 12:53:00 GMT
# < Etag: 640ebd176639fb6ef9a3227770ee7b17
# < X-Timestamp: 1463143979.89953
# < Content-Type: application/octet-stream
# < X-Trans-Id: tx6b14a272331b4bc6937db-005735cef1
# < Date: Fri, 13 May 2016 12:56:17 GMT
# <
# { [43 bytes data]
# 100  43 100  43  0  0  2748  0  --:--:-- --:--:-- --:--:-- 2866
# * Connection #0 to host 192.168.8.80 left intact

```

- Get statistics

```
# Auth related information
swift auth
# export OS_STORAGE_URL=http://saio:8080/v1/AUTH_wasteland
# export OS_AUTH_TOKEN=AUTH_tkf551ef98eb1e442b9efcef1261d87c64

swift auth -v
# export ST_AUTH=http://saio:8080/auth/v1.0
# export ST_USER=wasteland:psachin
# export ST_KEY=psachin

# To obtain Storage URL and Auth-Token
swift stat -v

# Get statistics of container and/or object
swift stat [container]
swift stat [container] [object]

# Retrive capability of proxy
swift capabilities
# Core: swift
# Options:
#   account_autocreate: True
#   account_listing_limit: 10000
#   allow_account_management: True
#   container_listing_limit: 10000
#   extra_header_count: 0
#   max_account_name_length: 256
#   max_container_name_length: 256
#   max_file_size: 5368709122
#   max_header_size: 8192
#   max_meta_count: 90
#   max_meta_name_length: 128
#   max_meta_overall_size: 4096
#   max_meta_value_length: 256
#   max_object_name_length: 1024
#   policies: [{u'default': True, u'name': u'default', u'aliases': u'default'}]
#   strict_cors_mode: True
#   version: 2.7.1.dev83
# Additional middleware: bulk_delete
# Options:
#   max_deletes_per_request: 10000
#   max_failed_deletes: 1000
# Additional middleware: bulk_upload
# Options:
#   max_containers_per_extraction: 10000
#   max_failed_extractions: 1000
# Additional middleware: container_sync
# Options:
#   realms: {u'TEST': {u'clusters': {u'SAIO': {u'current': True}}}}
# Additional middleware: slo
# Options:
#   max_manifest_segments: 1000
#   max_manifest_size: 2097152
#   min_segment_size: 1
# Additional middleware: staticweb
# Additional middleware: tempauth
# Options:
#   account_acls: True
```

```
# Additional middleware: tempurl
# Options:
#   incoming_allow_headers: []
#   incoming_remove_headers: [u'x-timestamp']
#   methods: [u'GET', u'HEAD', u'PUT', u'POST', u'DELETE']
#   outgoing_allow_headers: [u'x-object-meta-public-*']
#   outgoing_remove_headers: [u'x-object-meta-*']
```

```
# List container's details(Similar to 'ls -lh')
```

```
swift list --lh [container]
```

- Object versioning

When an object is overwritten, it's older version is lost, but there is a way we can store older version(s) of an object, no matter how many times it was overwritten.

To enable object versioning, set `allow_versions` option to `true` in container configuration file.

```
# --- /etc/swift/container-server.conf ---
```

```
[app:container-server]
```

```
allow_versions = true
```

```
# --- File ends here ---
```

```
# --- Create containers ---
```

```
# Create 'archive' container to hold 'current' container's object versions
```

```
swift post archive
```

```
# Now create 'current' container with header 'X-Versions-Location'
```

```
# pointing to 'archive'
```

```
swift post current -H "X-Versions-Location: archive"
```

```
# --- Other similar ways(Optional) ---
```

```
# May also define content length at the time of creating a container
```

```
swift post archive -H "content-length: 0"
```

```
swift post current -H "content-length: 0" -H "X-Versions-Location: archive"
```

```
# And also specify Read ACL(World readable) during container creation
```

```
swift post -r ".r:*" archive -H "content-length: 0"
```

```
swift post -r ".r:*" current -H "content-length: 0" -H "X-Versions-Location: archive"
```

```
# --- xxx ---
```

– <https://www.youtube.com/watch?v=ru2iMJvUZjI>

- Managing account quota

– Note: Write request to metadata entry is only permitted to reseller. Make sure you(in this case `test` user) have `reseller_admin` rights.

```
# /etc/swift/proxy-server.conf
```

```
[filter:tempauth]
```

```
use = egg:swift#tempauth
```

```
user_admin_admin = admin .admin .reseller_admin
```

```
user_test_tester = testing .admin .reseller_admin
```

```
user_test2_tester2 = testing2 .admin
```

```
user_test_tester3 = testing3
```

– Set account quotas

```
# 10K bytes
```

```
swift post -m quota-bytes:13000
```

```
# OR
```

```
swift post -H "X-Account-Meta-Quota-Bytes:13000"
```

```
# 3 objects. Note: This is NOT implemented yet(swift version: 2.12.0)
```

```
swift post -m quota-count:3
```

```

# OR
swift post -H "X-Account-Meta-Quota-Count:3"

swift stat -v
#           StorageURL: http://saio:8080/v1/AUTH_test
#           Auth Token: AUTH_tk665649077fc74fca88eebd7274de17f4
#           Account: AUTH_test
#           Containers: 1
#           Objects: 1
#           Bytes: 83412
# Containers in policy "gold": 1
# Objects in policy "gold": 1
# Bytes in policy "gold": 83412
# Meta Quota-Bytes: 13000
# Meta Quota-Count: 3
# X-Trans-Id: tx491cefe71fa848199480c-00586a834c
# X-Openstack-Request-Id: tx491cefe71fa848199480c-00586a834c
# X-Timestamp: 1483034243.85889
# Content-Type: text/plain; charset=utf-8
# Accept-Ranges: bytes

# Remove quota
swift post -m quota-count:
# OR
swift post -H "X-Account-Meta-Quota-Count:"

```

- Managing container's quota

```

# Limit maximum of 3 objects in container 'keys'
swift post -m quota-count:3 keys
# OR
swift post -H "X-Container-Meta-Quota-Count: 3" keys

# Max size of an object should be not more than 512 bytes in container 'keys'
swift post -m quota-count:512 keys
# OR
swift post -H "X-Container-Meta-Quota-Bytes: 512" keys

swift stat -v keys
#           URL: http://saio:8080/v1/AUTH_test/keys
#           Auth Token: AUTH_tk665649077fc74fca88eebd7274de17f4
#           Account: AUTH_test
#           Container: keys
#           Objects: 1
#           Bytes: 83412
#           Read ACL:
#           Write ACL:
#           Sync To:
#           Sync Key:
#           Meta Quota-Count: 3
#           Meta Quota-Bytes: 512
#           Last-Modified: Mon, 02 Jan 2017 16:42:27 GMT
#           Accept-Ranges: bytes
#           X-Storage-Policy: gold
#           X-Timestamp: 1483362272.23768
#           X-Trans-Id: tx9387af8e677745d18ffe3-00586a82fb
# X-Openstack-Request-Id: tx9387af8e677745d18ffe3-00586a82fb
#           Content-Type: text/plain; charset=utf-8

```



```
# Remove container quota
swift post -m quota-count: keys
# OR
swift post -H "X-Container-Meta-Quota-Bytes:" keys
```

3 Builder files

- Acts as a database
- Python pickle

```
1 import pickle
2 print(pickle.load(open('object.builder')))
```

- Ring builder command

```
# Account server runs on port 6002
swift-ring-builder add account.builder <region><zone>-<IP>:6002/<device><weight>
# Container server runs on port 6001
swift-ring-builder add container.builder <region><zone>-<IP>:6001/<device><weight>
# and the Object server runs on port 6000
swift-ring-builder add object.builder <region><zone>-<IP>:6000/<device><weight>
swift-ring-builder add object-N.builder <region><zone>-<IP>:6000/<device><weight>
```

- Region: Geographical location
- Zone: within region isolation
- Weight: Relative number of partition a drive will have
 - 1TB ~ Weight of 100.0
 - 2TB ~ Weight of 200.0..

4 Swift Ring

- Data structure
- Describes your cluster
- One ring each for account, container, & object

```
# swift-ring-builder account.builder create <PartitionPower> <Replicas> <MinPartHrs>
```

```
cd /etc/swift/
swift-ring-builder account.builder create 10 3 1
swift-ring-builder container.builder create 10 3 1
swift-ring-builder object.builder create 10 3 1
```

- How to decide value of Partition Power?

Assume that I have a system with 4 drives right now, but the maximum drives I can go up-to is 10.

```
# Partition Power
2^part_power > (Nos. of drives you think you will have at-scale) * 100

# I may have 10 drives in future
2^part_power > 10 * 100
2^part_power > 1000
2^10 > 1000
1024 > 1000 # 2^10 = 1024 just goes above 1000, which is perfect.
```

- Calculate Partition Power(Python snippet)

```

1 # Use python3 interpreter
2 from math import log2, ceil
3 print(ceil(log2(10 * 100))) # 10 <- Partition Power

```

- Partition in Swift

```
/srv/2/node/sdb2/objects/171/a56/2ae7be8de859228d6575cc9fe5518a56/1479968148.23926.data
```

```

/srv/2/node/sdb2/objects/171 # partition number
/srv/2/node/sdb2/objects/171/a56 # last 3 chars from hashed objectname
/srv/2/node/sdb2/objects/171/a56/2ae7be8de859228d6575cc9fe5518a56/ # hashed objectname
/srv/2/node/sdb2/objects/171/a56/2ae7be8de859228d6575cc9fe5518a56/1479968148 # timestamp

```

- Swift partition table

	Replica # 1	Replica # 2	Replica #3
Partition # 0	Device # 0	Device # 3	Device # 2
Partition # 1	Device # 1	Device # 2	Device # 0
Partition # 2	Device # 4	Device # 1	Device # 3

```

[vagrant@saio ~]$ swift-get-nodes /etc/swift/object.ring.gz test hoota CHANGEL0G

Account      test
Container    hoota
Object       CHANGEL0G

Partition    932
Hash         e90ec799284002b7f85ce1149841bbd0

Server:Port Device 127.0.0.1:6040 sdb4
Server:Port Device 127.0.0.1:6030 sdb3
Server:Port Device 127.0.0.1:6010 sdb1
Server:Port Device 127.0.0.1:6020 sdb2 [Handoff]

curl -g -I -XHEAD "http://127.0.0.1:6040/sdb4/932/test/hoota/CHANGEL0G"
curl -g -I -XHEAD "http://127.0.0.1:6030/sdb3/932/test/hoota/CHANGEL0G"
curl -g -I -XHEAD "http://127.0.0.1:6010/sdb1/932/test/hoota/CHANGEL0G"
curl -g -I -XHEAD "http://127.0.0.1:6020/sdb2/932/test/hoota/CHANGEL0G" # [Handoff]

Use your own device location of servers:
such as "export DEVICE=/srv/node"
ssh 127.0.0.1 "ls -lah ${DEVICE:-/srv/node*}/sdb4/objects/932/bd0/e90ec799284002b7f85ce1149841bbd0"
ssh 127.0.0.1 "ls -lah ${DEVICE:-/srv/node*}/sdb3/objects/932/bd0/e90ec799284002b7f85ce1149841bbd0"
ssh 127.0.0.1 "ls -lah ${DEVICE:-/srv/node*}/sdb1/objects/932/bd0/e90ec799284002b7f85ce1149841bbd0"
ssh 127.0.0.1 "ls -lah ${DEVICE:-/srv/node*}/sdb2/objects/932/bd0/e90ec799284002b7f85ce1149841bbd0" # [Handoff]

note: '/srv/node*' is used as default value of 'devices', the real value is set in the config file on each storage node.

```

5 Additional notes

Swift consistency processes:

- *Auditor*: Will walk through the storage nodes, read the data and the checksum, ensure the checksum matched with the database checksum. If the checksum didn't match, the data is moved to the Quarantine.
- *Replicator*: The replicator, will also scan each drive and ensures that the replicas of data is stored where is supposed to live. If it does not finds the data in that place(may be the data, due to corruption was moved to Quarantine), it will push the data to that place.
- Storage policies
 - Decide where you want to store data
 - * Between swift clusters
 - * Subset of hardware
 - Erasure coding(Data availability policies)
 - * Based in frequency of access
 - * Example:

```

swift post -H "X-Storage-Policy: gold" container_gold
swift post -H "X-Storage-Policy: silver" container_silver
swift post -H "X-Storage-Policy: ec42" container_ec42

swift upload container_gold cirros-0.3.4-x86_64-disk.img
swift upload container_silver cirros-0.3.4-x86_64-disk.img
swift upload container_ec42 cirros-0.3.4-x86_64-disk.img

```

- Erasure Codes

- When building a ring for Erasure codes, number of replicas are replaced with number of fragments

```
swift-ring-builder object.builder create 10 6 1
```

where $4 + 2 = 6$

4 data fragments 2 parity data

So that the system can sustain 4 disk failures before the data is treated to be lost

- Erasure coding is implemented in Swift as storage policies

```

# /etc/swift/swift.conf
[storage-policy:2]
name = ec42
policy_type = erasure_coding
ec_type = liberasurecode_rs_vand
ec_num_data_fragments = 4
ec_num_parity_fragments = 2

```

- <https://www.youtube.com/watch?v=kH3DXMKIEr8>
- <https://www.youtube.com/watch?v=GDNK1S4FJBQ>

- ACLs

- Container ACL

```

# World readable
swift post -r ".r:*" photos

# Allow .welcome.com but deny .noisy.com
swift post -r ".r:*.welcome.com,.r:-noisy.com" photos

# Enable object listing within a container
swift post -r ".r:*,.rlistings" photos

# ---xxx---
# We created tenant(project1) and created account user1 and user2 as
# member. We applied ACL for container1, container2 to make only user1
# can access container1 and user2 can access container2. But user1 can
# access container1 and container2, user2 can access both. We want
# configure ACL for container to limit each user only can access his
# container

swift post --read-acl "<project1-id>:<user1-id>" container1
swift post --read-acl "<project1-id>:<user2-id>" container2

```

- Hashing

- Swift hashing function

```

1 # Use python3 interpreter
2 # Swift hashing is based on MD5
3 # hash(path) = md5(path + per-cluster suffix)
4
5 # Python snippet to know on which drive the object will be stored,
6 # assuming I have 4 drives
7 from hashlib import md5

```

```

8
9 m = md5()
10 m.update("/account/container/object") # Hypothetical path
11 digest = m.hexdigest()
12 print(digest)
13
14 # hex to int
15 hex2int = int(digest, 16)
16 print(hex2int)
17 # digest % (number of drives) = Drive number
18 print(hex2int % 4) # 2

```

- Account access

– Using Python interpreter

```

>>> import swift.common.memcached as mc
>>> mc = mc.MemcacheRing(['127.0.01:11211'])
>>> mc.get('AUTH_/user/test:tester')
u'AUTH_tk8e047f9a96cc48759319b7781ddeb992'
>>> mc.get('AUTH_/token/AUTH_tk8e047f9a96cc48759319b7781ddeb992')
[1481115804.307723, u'test,test:tester,AUTH_test']

```

– Shell

```

swift stat -v
#                               StorageURL: http://saio:8080/v1/AUTH_test
#                               Auth Token: AUTH_tk8e047f9a96cc48759319b7781ddeb992
#                               Account: AUTH_test
#                               Containers: 27
#                               Objects: 22
#                               Bytes: 13328148
# Containers in policy "ec42": 12
# Objects in policy "ec42": 11
# Bytes in policy "ec42": 13288056
# Containers in policy "silver": 1
# Objects in policy "silver": 0
# Bytes in policy "silver": 0
# Containers in policy "gold": 14
# Objects in policy "gold": 11
# Bytes in policy "gold": 40092
#                               X-Trans-Id: txb4f4f6812c514fce91f15-005846ebc6
#                               X-Timestamp: 1480517025.85633
#                               Content-Type: text/plain; charset=utf-8
#                               Accept-Ranges: bytes

```

6 Object expirer

- Start object expirer server

```
swift-init object-expirer start
```

- Schedule deletion of object after user deletes the file

```
swift delete container_gold cirros-0.3.4-x86_64-disk.img -H "X-Delete-After: 120"
```

7 Temporary URL

- This allows to share a temporary URL for an object for particular period of time.

```

# Upload object
swift upload container1 cat.jpg

```

```

swift list container1 --lh
# 125K 2017-03-27 13:44:48          image/jpeg cat.jpg
# 125K

swift stat container1 -v
#
#           URL: http://192.168.11.33:8080/v1/AUTH_account1/container1
#
#       Auth Token: AUTH_tk9cb82129b5b34fc5876e75e9d0bc3b60
#
#           Account: AUTH_account1
#
#       Container: container1
#
#           Objects: 1
#
#           Bytes: 129006
#
#       Read ACL: account1:aone
#
#       Write ACL:
#
#       Sync To:
#
#       Sync Key:
#
#   Accept-Ranges: bytes
#
#   X-Trans-Id: tx0bb106d0d2164133b7b13-0058d9193f
#
# X-Storage-Policy: gold
#
#   Last-Modified: Mon, 27 Mar 2017 13:44:49 GMT
#
#   X-Timestamp: 1487354738.54612
#
#   Content-Type: text/plain; charset=utf-8
#
# X-Openstack-Request-Id: tx0bb106d0d2164133b7b13-0058d9193f

# Create key
swift post -m "Temp-URL-Key:mykey"

# Generate temp URL which is valid for 30 mins
swift tempurl GET 1800 http://192.168.11.33:8080/v1/AUTH_account1/container1/cat.jpg mykey
# http://192.168.11.33:8080/v1/AUTH_account1/container1/cat.jpg?\
# temp_url_sig=e34606590ec6f0a18e1df52d32d7ec5da74dadd5&temp_url_expires=1490624622

# Download the object
curl "http://192.168.11.33:8080/v1/AUTH_account1/container1/cat.jpg?\
temp_url_sig=ff0b580b29b6bacaad0de658b30d2837fed4fb87&temp_url_expires=1490624309" > catty.jpg

```

8 Swift handoff partitions

- How is a handoff partition flagged versus a partition that is marked to be moved during a rebalance?

Answer (notmyname): "handoff" is only a thing defined by the results of the call to `get_more_nodes()`. it's not a concept that means anything with regards to rebalancing. ie it's not "flagged" or anything. handoffs are just an ordered walk through the ring

- How should one think of handoff devices?

Answer (mattoliverau): A hand off device is a non primary node for a certain partition in the ring. Things are placed to hand off nodes when either

- there wasn't enough primary nodes to keep it durable.
- when write affinity has been set and you want to get your object durability written to a closer region or zone
- on a ring rebalance

When looking for an object (GET) swift will check all primary nodes for the object and then some of the hand off nodes.

But in essence once on a handoff node, we have durability which is the most important. but if the primaries are busy or down you may not get your object back until swift corrects it self

The replicators will look at the objects they have, and if its a partition they're a hand off for, because they received it cause other primaries where down, or a rebalance suddenly has now suddenly made them a handoff node for a partition, they will replicate it out to the primary nodes and then if successful, delete it.

handoff nodes + eventual consistency helps swift keep its awesome durability

- is it (handoff node) meant to be a temporary holding place?

Answer (mattoliverau): Yeah

9 Swift on OpenStack(RHOSP-8)

- undercloud

Verify swift authentication using below command

```
[stack@undercloud ~]$ source stackrc
```

```
[stack@undercloud ~]$ swift list
```

```
[stack@undercloud ~]$ swift stat -v
```

```
#      StorageURL: http://192.0.2.1:8080/v1/AUTH_447097d6f2844cdf9d5d0fa7b8529046
#      Auth Token: e117add154fc429f92fba2a00fdbaaaf0
#      Account: AUTH_447097d6f2844cdf9d5d0fa7b8529046
#      Containers: 0
#      Objects: 0
#      Bytes: 0
# X-Put-Timestamp: 1481719100.59059
# X-Timestamp: 1481719100.59059
# X-Trans-Id: tx2aa20b0ed084bfc8a059-0058513d3c
# Content-Type: text/plain; charset=utf-8
```

```
[stack@undercloud ~]$ swift auth -v
```

```
export OS_IDENTITY_API_VERSION=2.0
export OS_AUTH_VERSION=2.0
export OS_AUTH_URL=http://192.0.2.1:5000/v2.0
export OS_PASSWORD=Redhat01
export OS_TENANT_NAME=admin
export OS_USERNAME=admin
```

Password is derived from puppet configs

```
[stack@undercloud:/etc]# grep -r Redhat01 *
```

```
puppet/hieradata/puppet-stack-config.yaml:heat::keystone::domain::keystone_password: Redhat01
puppet/hieradata/puppet-stack-config.yaml:keystone::roles::admin::password: Redhat01
puppet/hieradata/puppet-stack-config.yaml:admin_password: Redhat01
```

You will find IP address in /etc/ironic/ironic.conf

```
...
my_ip=192.0.2.1
...
```

Access swift using curl

- Get **admin** account UUID

```
[stack@undercloud]$ openstack project list
```

```
+-----+-----+
| ID                | Name    |
+-----+-----+
| 447097d6f2844cdf9d5d0fa7b8529046 | admin   |
| 31f55360edff4a1d81670daf65d720a2 | service |
+-----+-----+
```

- Get token

```
[stack@undercloud]# openstack token issue
```

```
+-----+-----+
| Field      | Value                                     |
+-----+-----+
```

```
+-----+
| expires | 2016-12-14T17:05:37Z |
| id      | 2de6e7295e1b481a9c12b264ace5284c |
| project_id | 447097d6f2844cdf9d5d0fa7b8529046 |
| user_id  | b62e1dfc83e5479db4c258b31ebb57bb |
+-----+
```

- User admin token and UUID to access swift

```
[stack@undercloud]# curl -v -H "X-Storage-Token: 2de6e7295e1b481a9c12b264ace5284c" \
http://192.0.2.1:8080/v1/AUTH_447097d6f2844cdf9d5d0fa7b8529046
* About to connect() to 192.0.2.1 port 8080 (#0)
* Trying 192.0.2.1...
* Connected to 192.0.2.1 (192.0.2.1) port 8080 (#0)
> GET /v1/AUTH_447097d6f2844cdf9d5d0fa7b8529046 HTTP/1.1
> User-Agent: curl/7.29.0
> Host: 192.0.2.1:8080
> Accept: */*
> X-Storage-Token: 2de6e7295e1b481a9c12b264ace5284c
>
< HTTP/1.1 204 No Content
< Content-Type: text/plain; charset=utf-8
< X-Account-Object-Count: 0
< X-Timestamp: 1481720818.51417
< X-Account-Bytes-Used: 0
< X-Account-Container-Count: 0
< X-Put-Timestamp: 1481720818.51417
< Content-Length: 0
< X-Trans-Id: tx2aac9d2dbbe443f3aa758-00585143f2
< Date: Wed, 14 Dec 2016 13:06:58 GMT
<
* Connection #0 to host 192.0.2.1 left intact
```

- TODO: overcloud

```
[stack@undercloud ~]$ source overcloudrc
[stack@undercloud ~]$ swift auth -v
export OS_IDENTITY_API_VERSION=2.0
export OS_AUTH_VERSION=2.0
export OS_AUTH_URL=http://10.0.0.4:5000/v2.0
export OS_PASSWORD=tdr8WZh7vFkDzFdQpDxdzFrft
export OS_TENANT_NAME=admin
export OS_USERNAME=admin
```

10 Todo

- Container sync: Sync container(with same name) to other cluster
 - http://docs.openstack.org/developer/swift/overview_container_sync.html

11 Links

- <https://github.com/psachin/bootcamp>
- HTML version of this¹ doc is available at:
 - <https://github.com/psachin/bootcamp/blob/master/swift-notes.org>
- Slides: <https://redhat.slides.com/psachin/rhosp-swift-2016>
- SAIO on Fedora: <https://github.com/psachin/fedora-saio>

¹Made with Love, L^AT_EX, & GNU Emacs

- https://github.com/gholt/ring/blob/master/BASIC_HASH_RING.md
- http://docs.openstack.org/developer/swift/ring_background.html