

Literature Survey

Kinesis: A Fraud-Resistant, Self-Sustaining Play-to-Earn and Move-to-Earn Web3 Ecosystem

Title	Technology	Dataset (Used)	Evaluation Metrics	Result	Gaps (Drawbacks)
SoK: Play-to-Earn Projects <i>Yu, Zhang, Chen, Fang (2022), arXiv:2211.01000</i>	Systematic study of P2E blockchain games; tokenomics and governance model analysis	None — systematisation of existing platforms (e.g. StepN, Axie Infinity); no empirical dataset	Not applicable — qualitative systematisation of knowledge (SoK), no quantitative evaluation	Identifies recurring tokenomics failure patterns (irregular issuance, treasury mismanagement) across surveyed P2E platforms	No concrete mechanism proposed to prevent identified failures; no empirical validation of any solution
Evaluating and Managing Tokenomics for NFTs in Game-Based Blockchain Networks <i>Kim, Kim, Park (2023), arXiv:2306.13672</i>	AMM (automated-market-maker) based reward-adjustment mechanism for token/NFT inflation control	None — theoretical model illustrated with worked numerical examples only	Not applicable — analytical/mathematical illustration, no empirical benchmark or dataset	Shows algebraically that adjusting swap ratios / rarity weighting can control unscheduled token-supply growth	No real-world or empirical validation; does not address user-activity verification or fraud detection
Blockchain for Fraud Detection in Financial Transactions <i>Chaitanya Anil, Onkar Popat, Samyak Gautamrao, Shinkar (2026), Springer ICCCT 2025, LNNS vol. 1674</i>	Solidity smart contracts; on-chain risk-scoring model	Not specified in the published abstract (implied own transaction testbed)	Risk-score parameters: transaction size, frequency, velocity, geographic location, KYC status	Real-time, on-chain flagging of high-risk transactions without centralized oversight	Relies solely on on-chain transaction metadata; no off-chain/behavioural signal fusion; quantitative accuracy figures not publicly detailed
A Machine Learning Based Smartphone App for GPS Spoofing Detection <i>Campos et al. (2020), Springer SecureComm 2020, LNICST vol. 336</i>	Supervised ML: Random Forest, SVM, KNN; Android application	Real GPS signals plus spoofed signals generated via LimeSDR SDR using NASA CDDIS ephemeris data	Classification accuracy	Up to 99.5% spoofing-detection accuracy using lightweight, on-device features	Detection limited to GPS signal-level spoofing; no fusion with other mobile sensors or on-chain context
Hyperledger Fabric Blockchain for Securing the Edge Internet of Things <i>Honar Pajooh, Rashid, Alam, Demidenko (2021), Sensors 21(2), 359</i>	Permissioned Hyperledger Fabric network; layered edge-IoT identity/authentication architecture	Real hardware testbed — Raspberry Pi devices and VMware virtual desktops running live Fabric nodes	Transaction throughput, latency, resource (CPU/memory) consumption, network usage	Demonstrates the platform is feasible and “promising” for securing resource-constrained IoT edge devices (qualitative result; exact figures not extracted for this table)	Focused on device-level IoT authentication and data provenance only; does not address application-layer fraud such as spoofed activity or reward manipulation
Evaluating DAO Sustainability and Longevity Through On-Chain Governance Metrics <i>Meneguzzo, Schifanella, Gatteschi, Destefanis (2025), arXiv:2504.11341</i>	Multi-chain on-chain data retrieval pipeline; KPI (Key Performance Indicator) scoring framework	Real on-chain data from 50 active DAOs across Ethereum, Polygon, Arbitrum (6,930 proposals; 317,317 voting addresses)	Participation rate, treasury size, proposal approval rate, decentralisation score; Shapiro–Wilk, Levene’s, ANOVA/Kruskal–Wallis tests	Reveals persistently low voter participation and high proposer-power concentration across most sampled DAOs	Covers governance/financial sustainability only; does not address fraud detection or physical-activity verification
A Location Validation Technique to Mitigate GPS Spoofing Attacks in IEEE 802.11p Fleet Networks <i>Samaddar, Easwaran (2024), arXiv:2410.13031, IEEE ITSC 2024</i>	Location-validation algorithm for IEEE 802.11p vehicular communication networks	Generated/simulated GPS-spoofing datasets for an electric-vehicle fleet scenario	Detection efficacy on generated attack datasets (specific accuracy figures not detailed in the available abstract)	Reports that the proposed location-validation technique effectively mitigates the modelled GPS spoofing attacks	Vehicular fleet context, not pedestrian/mobile; not evaluated against blockchain-based reward or token systems