

Enterprise Blockchain Case Studies

TypeScript repository demonstrating enterprise blockchain patterns.

Focus areas

- Operational case studies (traceability, privacy, credentials, settlement)
- Protocol adapters (Fabric, Besu, Corda)
- Off-chain cryptography (MPC, HSM, post-quantum)

Repository Structure

Folder	Contents
modules/	Domain logic, protocol adapters, integration clients
examples/	20 runnable scenarios
contracts/	Solidity (Foundry), Fabric chaincode (TS), Corda (Kotlin)
docs/	Architecture guides, ADRs, this deck
skills/	AI skill files for assisted development
tests/	Property-based tests (fast-check)


Case Studies

Scenario	Domain Problem	Protocol Fit
Food recall	Trace contaminated lots across supply chain	Fabric (channel isolation)
Order sharing	Selective disclosure to bank/logistics/regulator	Besu (privacy groups)
Staffing clearance	Verify credentials before clinical assignment	Corda (point-to-point)
Aid reconciliation	Multi-agency voucher settlement	Besu (shared state)

Platform Selection

Decision tree for protocol choice:


- Data integrity only → **KSI / Guardtime**
- Public anchoring → **Bitcoin / Ethereum**
- Bilateral flows → **Corda**
- EVM ecosystem → **Besu**
- Channel isolation → **Fabric**



Fabric: Endorsement Flow

1. Client submits proposal
2. Endorsing peers simulate chaincode
3. Client collects endorsements
4. Orderer batches into block
5. All peers validate and commit


Use case: **Food recall traceability**



Privacy Patterns

Platform	Mechanism
Fabric	Private data collections, transient data
Besu	Privacy groups, restricted contract state
Corda	Need-to-know state distribution


Use case: Consortium order sharing



Corda: Flow Protocol

1. Issuer builds `CredentialState`
2. Contract verifies locally
3. `CollectSignaturesFlow` gathers counterparty signatures
4. Notary checks uniqueness
5. `FinalityFlow` distributes to participants


Use case: **Hospital staffing clearance**



Settlement Controls

- Agency registers and allocates funds
- Beneficiary redeems at POS
- Contract enforces budget limits
- Cross-agency duplicate detection

Use case: **Aid voucher reconciliation**




MPC: Additive Secret Sharing

Parties split inputs into additive shares:

$$\text{secret} = \text{share}_1 + \text{share}_2 + \text{share}_3 \pmod{p}$$

Computation happens on shares; result reconstructed.

Examples: `mpc-sealed-bid-auction`, `mpc-joint-risk-analysis`



MPC: Threshold Schemes

Shamir Secret Sharing (k-of-n)


- Polynomial interpolation over finite field
- Any k shares reconstruct; k-1 reveal nothing
- Used for key custody and quorum authorization

Example: `quantum-resistant-key-sharing` — 3-of-5 threshold + hash-ladder anchoring

HSM: Envelope Encryption

1. Generate ephemeral DEK (256-bit)
2. Encrypt payload with DEK (AES-GCM)
3. Wrap DEK with KEK inside HSM
4. Store `ciphertext + wrappedDEK`
5. Only HSM can unwrap

Private keys never leave hardware boundary.



HSM Examples

Example	Pattern
hsm-transaction-signing	EC P-256 ECDSA with audit digest
hsm-key-ceremony	3-of-5 Shamir + HSM-signed root certificate
hsm-envelope-encryption	DEK/KEK for on-ledger document confidentiality

Post-Quantum Cryptography

NIST Standards (August 2024)

Standard	Algorithm	Wire Sizes
FIPS 203	ML-KEM-768	pk: 1184 B, ct: 1088 B, ss: 32 B
FIPS 204	ML-DSA-65	pk: 1952 B, sig: 3309 B

Replaces RSA/ECDH (key exchange) and ECDSA (signatures).

ML-KEM Key Encapsulation

Lattice-based KEM (FIPS 203)

1. Recipient generates `(pk, sk)`
2. Sender: `(ciphertext, sharedSecret) = encapsulate(pk)`
3. Recipient: `sharedSecret = decapsulate(sk, ciphertext)`

Parameter sets: ML-KEM-512, ML-KEM-768, ML-KEM-1024

Example: `kyber-kem-key-exchange`

Hybrid KEM

X25519 + ML-KEM-768

```
combinedSecret = HKDF(x25519Secret || mlkemSecret)
```

- Defense-in-depth: secure if either primitive holds
- Recommended for transition period
- Backward compatible with classical peers

Example: hybrid-kem-settlement

Quantum-Safe Payment Flow

Phase	Primitive
Key ceremony	Hybrid KEM (X25519 + ML-KEM-768)
Sign instruction	ML-DSA-65 (FIPS 204)
Encrypt payload	AES-256-GCM with hybrid key
Authorize settlement	3-of-3 MPC threshold

Example: quantum-safe-payment

Consensus Comparison

Protocol	Consensus	Finality
Fabric	Raft / BFT	Immediate
Besu	QBFT / IBFT 2.0	Immediate
Corda	Notary (single/clustered)	Immediate

All provide deterministic finality (no forks).



Architecture Layers


Layer	Responsibility	Location
Domain	Business rules, entities	modules/{domain}/
Protocol	Platform-specific tx shapes	modules/protocols/
Integration	SDK bindings, retry, errors	modules/integrations/
Config	Endpoints, credentials	examples/config/

Besu Integration

Stack: Solidity + ethers.js + privacy groups

Repository assets:

- `contracts/solidity/src/` — Foundry project
- `modules/integrations/besu-client/` — tx builders
- `modules/protocols/besu/` — privacy group calls



Besu Dev Mode Configuration

Docker Compose Settings

Setting	Value
Image	hyperledger/besu:24.12.2
Network mode	--network=dev (PoA mining)
Chain ID	1337
Block time	~1 second (dev mode)
Validator-0 port	8545
Validator-1 port	8546

Health check: TCP socket on RPC port (10s interval)

Besu Command-Line Arguments

command:

- `--network=dev` # Dev mode with auto-mining
- `--rpc-http-enabled` # Enable JSON-RPC HTTP
- `--rpc-http-host=0.0.0.0` # Bind to all interfaces
- `--rpc-http-cors-origins=http://localhost`
- `--host-allowlist=localhost,127.0.0.1`
- `--miner-enabled` # Enable block production
- `--miner-coinbase=0x0000000000000000000000000000000000000000000000000000000000000000`

Security: `no-new-privileges`, resource limits (1 CPU, 1GB)

Besu Quick Start

```
# Start Besu validators
docker compose up -d besu-validator-0 besu-validator-1

# Wait for health checks (~20s)
docker compose ps

# Verify JSON-RPC
curl -X POST http://localhost:8545 \
  -H "Content-Type: application/json" \
  -d '{"jsonrpc":"2.0","method":"eth_blockNumber","params":[],"id":1}'


# Run E2E tests (15 tests against live nodes)
npm run test:e2e
```

Fabric Integration

Stack: TypeScript chaincode + Gateway SDK

Repository assets:

- `contracts/fabric/` — FoodTraceContract
- `modules/integrations/fabric-gateway/` — proposal builders
- `modules/protocols/fabric/` — invoke/query shapes



Corda Integration

Stack: Kotlin CorDapp + REST gateway

Repository assets:

- `contracts/corda/` — ProviderClearanceContract/Flow/State
- `modules/integrations/corda-gateway/` — HTTP request builders
- `modules/protocols/corda/` — flow invocation shapes

TypeScript handles the integration boundary, not CorDapp runtime.

Quick Start

```
npm install          # install dependencies
npm run verify       # format + lint + typecheck + test + examples
make up              # start Docker Compose stack
make smoke           # run smoke tests
```

All examples run offline with mocked SDK boundaries.

Infrastructure

Local Development Stack

Service	Port	Purpose
Besu validator-0	8545	Primary JSON-RPC
Besu validator-1	8546	Secondary validator
Fabric peer	7051	gRPC
OTEL Collector	4318	Trace/metric ingestion
Jaeger	16686	Distributed trace UI
Prometheus	9090	Metrics collection

Security: CIS Docker Benchmark (resource limits, no-new-privileges)

Observability

OpenTelemetry Integration

```
import { withSpan, createMeter } from "@enterprise-blockchain/shared";

const result = await withSpan("submitTransaction", async (span) => {
  span.setAttribute("channel", "food-trace");
  return gateway.submit(proposal);
});
```

- Automatic context propagation across services
- Traces exported to Jaeger, metrics to Prometheus
- Circuit breaker and retry instrumented

Example Commands

Category	Commands
Case studies	<code>example:food-recall</code> , <code>example:order-sharing</code> , <code>example:staffing-clearance</code> , <code>example:aid-reconciliation</code>
Protocol	<code>example:fabric-projection</code> , <code>example:besu-projection</code> , <code>example:corda-projection</code>
Integration	<code>example:fabric-gateway</code> , <code>example:besu-ethers</code> , <code>example:corda-rest</code>
MPC	<code>example:mpc-auction</code> , <code>example:mpc-risk-analysis</code> , <code>example:quantum-key-sharing</code>
HSM	<code>example:hsm-tx-signing</code> , <code>example:hsm-key-ceremony</code> , <code>example:hsm-envelope-encryption</code>
PQC	<code>example:kyber-kem</code> , <code>example:hybrid-kem</code> , <code>example:quantum-safe-payment</code>

Property-Based Testing

fast-check for Cryptographic Invariants

Module	Properties Tested
HSM	Envelope round-trip, ECDSA sign/verify
Kyber	ML-KEM encapsulate/decapsulate, implicit reject
MPC	Field arithmetic, Shamir k-of-n reconstruction

```
npm test # run all tests
npm test -- tests/hsm.property.test.ts
```

Navigation

Goal	Start
Run a scenario	<code>examples/</code>
Read domain logic	<code>modules/{domain}/src/</code>
See protocol shapes	<code>modules/protocols/</code>
Study integration patterns	<code>modules/integrations/</code>
Review architecture	<code>docs/architecture/</code>
Set up Besu locally	<code>docs/architecture/besu-setup.md</code>
Run infrastructure	<code>make up && make smoke</code>
Run E2E tests	<code>npm run test:e2e</code>

Summary

- **4** case studies (traceability, privacy, credentials, settlement)
- **3** protocol adapters (Fabric, Besu, Corda)
- **3** integration clients (Gateway, ethers, REST)
- **9** cryptographic examples (3 MPC + 3 HSM + 3 PQC)
- **OpenTelemetry** observability with Jaeger and Prometheus
- **Property tests** for cryptographic correctness
- **E2E tests** with live Besu nodes (15 tests)

All pass `npm run verify` and run offline. E2E tests run with `npm run test:e2e`.