

Advanced Algorithms for Optimization

LINFO2266

Introduction

Prof: Pierre Schaus
TAs: Alice Burlats, Amaury Guichard



Knapsack Problem

The set of items: I

Variables $x_i \in \{0,1\}$, 1 iff item i selected

Objective: Maximize $\sum_{i \in I} v_i \cdot x_i$


Maximize value of
selected items

Constraints: $\sum_{i \in I} w_i \cdot x_i \leq C$

Under capacity
constraint

Solving Knapsack: Brute-force

- Try every possible solutions
 - n items, 2^n solutions
 - $n = 50$, 1 ms to test one solution, > 30.000 years



Knapsack: Recursive Bruteforce

- Assume $I = \{1, \dots, n\}$
- Notation $O(k, j)$ = optimal objective with capacity k and items $\{1, \dots, j\}$:

$$\begin{array}{ll} \text{maximize} & \sum_{i \in \{1, \dots, j\}} v_i x_i \\ \text{subject to} & \sum_{i \in \{1, \dots, j\}} w_i x_i \leq k \end{array}$$

- We are interested in $O(C, n)$

Knapsack Recursive Bruteforce

- To solve $O(k, j)$, should we select item j (if $w_j \leq k$)?
 - If we don't select it the best solution is $O(k, j-1)$
 - If we select it the best solution $v_j + O(k - w_j, j - 1)$


Take the best 🤔

- Recurrence equations:


$$O(k, j) = \begin{cases} 0 & \text{if } j = 0 \\ \max(O(k, j - 1), v_j + O(k - w_j, j - 1)) & \text{if } w_j \leq k \\ O(k, j - 1) & \text{otherwise} \end{cases}$$

Bellman Recurrence Equations


Pure brute force: backtrack if capa < 0



Some States are equivalent: DP idea don't recompute them



Store the state and retrieve them



A (hash)map is needed

- For the knapsack we can also use a table since the capacity is fixed
- We need two dimensions:
 - Index (of item in the search tree)
 - Capacity left

Knapsack DP: Implem with Table

(v,w)	-	1,2	6,3	18,5	22,6	28,7
k	0	1	2	3	4	5
0	0	0	0	0	0	0
1	0	0	0	0	0	0
2	0	1	1	1	1	1
3	0	1	6	6	6	6
4	0	1	6	6	6	6
5	0	1	7	18	18	18
6	0	1	7	18	22	22
7	0	1	7	19	22	28
8	0	1	7	24	23	28
9	0	1	7	24	28	29
10	0	1	7	25	28	34
11	0	1	7	25	40	40

What is the time complexity?
How to retrieve the solution?

Optimal Value

- See code KnapsackTable

Knapsack DP: Implem with Table

- Time and Space Complexity: $\Theta(C.n)$

- Is this polynomial ?

suggestion: divide C and w_i 's by their greatest common divisor

- No! Because $\log(C)$ bits are necessary to represent C , the complexity is thus exponential wrt to the input size.
- We say it is *pseudo-polynomial*:
 - Can be considered as roughly polynomial for small value of C
 - But quickly becomes expensive to compute for large values of C
- *Hint: For large C , you can scale down (approximation)*

Knapsack is Weakly NP-Hard

An **NP-complete** (or **NP-hard**) problem is **weakly NP-complete** (or weakly NP-hard), if there is an algorithm for the problem whose running time is polynomial in the dimension of the problem and the magnitudes of the data involved (provided these are given as integers), rather than the base-two logarithms of their magnitudes.

http://en.wikipedia.org/wiki/Weakly_NP-complete


Not every NP-complete are weakly NP-complete. TSP is NP-complete in the strong sense, bin-packing as well.

- Alternatively we can use a standard hash-table for the MAP using


```
HashMap<Pair<Integer,Integer>, Integer> cache;
```



Index



Residual
capacity



Objective
Value

- See code KnapsackHash.java

Knapsack DP: Implem with cache

- Time and Space
- Complexity: ~~$\Theta(C.n)$~~ $O(C.n)$

Only 30/72 cells
are stored in the
cache

(v,w)	-	1,2	6,3	18,5	22,6	28,7
k	0	1	2	3	4	5
0	0	0	0	0	0	0
1	0	0	0	0	0	0
2	0	1	1	1	1	1
3	0	1	6	6	6	6
4	0	1	6	6	6	6
5	0	1	7	18	18	18
6	0	1	7	18	22	22
7	0	1	7	19	22	28
8	0	1	7	24	23	28
9	0	1	7	24	28	29
10	0	1	7	25	28	34
11	0	1	7	25	40	40

Optimization of a Range Partitioning

Problem Statement

Given

(1) an arrangement $S=[s_1, \dots, s_n]$ of nonnegative numbers

(2) an integer k ,

The objective is to partition S into k or fewer ranges, to minimize the maximum sum over all the ranges without reordering the numbers.

Example:

$S = [1, 2, 3, 4, 5, 6, 7, 8, 9]$ and $k = 3$.

An optimal partition into contiguous ranges is

$[1, 2, 3, 4, 5], [6, 7], [8, 9]$

with the largest one having a sum of **17**.

Just to make sure ;-) ?

$S = [1, 2, 6, 3, 1, 4, 5, 6, 7, 8, 5]$ and $k = 4$.

Optimal value?

- 13

- 9

- 10

- 15

- 12

Exercise

- Formulate this problem as a dynamic program. Write recurrence equations (don't forget the base-cases)

Choose the correct recurrence equation

Let $O(i, l)$ with $i \in [1..n]$, $l \in [2..k]$ denote the optimal value of the problem on the prefix sequence $[s_1, \dots, s_i]$ using at most l partitions. $O(i, l) =$

1 : $\max (O(i-1, l), O(i-1, l-1) + s_i)$

2 : $\min (O(i-1, l), O(i-1, l-1) + s_i)$

3 : $\max_{j \in [1..i-1]} \min ((s_{j+1} + s_{j+2} + \dots + s_i), O(j, l-1))$


4 : $\min_{j \in [1..i-1]} \max ((s_{j+1} + s_{j+2} + \dots + s_i), O(j, l-1))$

5 : $\min_{j \in [1..i-1]} \max ((s_{i+1} + s_{i+2} + \dots + s_j), O(j, l-1))$



Explanation

$[s_1, \dots, s_j, s_{j+1}, \dots, s_i, \dots, s_n]$



Max is necessary in case the last partition $[s_{j+1}, \dots, s_i]$ is the heaviest one

$$O(i, l) = \min_{j \in [1..i-1]} \max((s_{j+1} + s_{j+2} + \dots + s_i), O(j, l-1))$$

Base case

- The base case is the one with one partition:
 - $O(i,1) = s_1 + \dots + s_i$
- And the one with the sequence of length 1
 - $O(1,l) = s_1 \quad \forall l \in [1..k]$.
- We should not forget to characterize the optimal solution :
 - * **The optimal solution is $O(n, k)$**

Table-Based Implementation

- $O(5,2) = \min(\max(10,5), \text{max}(6,4+5), \text{max}(3,(3+4+5), \text{max}(1,(2+3+4+5)))$
- $O(5,2) = \min(10,9,12,14) = 9$

k/s	1	2	3	4	5	6	7	8	9
1	1	3	6	10	15	21	28	36	45
2	1				?				
3	1								

$$O(i, l) = \min_{j \in [1..i-1]} \max((s_{j+1} + s_{j+2} + \dots + s_i), O(j, l-1))$$

Time-Complexity Analysis


$$O(i, l) = \min_{j \in [1..i-1]} \max((s_{j+1} + s_{j+2} + \dots + s_i), O(j, l - 1))$$

- Time complexity to fill in the table ?
- Can we go faster to compute $s_{j+1} + s_{j+2} + \dots + s_i$?

Is it possible to make a generic Dynamic Solver ?

Yes!

- Because every dynamic program can be reduced to a shortest (minimization) or (longest) path problem in a Directed Acyclic (Layered) Graph (DAG).




Longest path problem in a general graph is an NP-Hard problem but not in a DAG

DAG for the (Bounded) Knapsack

- Compact encoding of the solution space
- Longest path = optimal solution

cap	15	val	wgt	qty
		2	4	1
		3	6	1
		6	4	2
		6	2	2
		1	5	1




Optimal set of items:
2x item 3 and 2x item 4

Optimal value: 24

Longest path in a DAG: solved with DP

- Because every dynamic program can be reduced to a shortest (minimization) or (longest) path problem in a Directed Acyclic (Layered) Graph (DAG).




Let $L(i)$ the longest path from i to the tail node t .
Can you give the DP recurrence equation ?

$$L(i) = \max_{j \in \text{succ}(i)} \text{cost}(i, j) + L(j)$$

Finding the longest path

- Linear time bottom-up




$$L(i) = \max_{j \in \text{succ}(i)} \text{cost}(i, j) + L(j)$$

The framework we propose

- Is composed of three classes:
 - State (= nodes of the DAG)
 - Transition = Edges (directed) of the DAG
 - The Model is able to generate successor states from a state and also identify the root r and the sink t
- A global Hash Table is used during the solving process

Best objective value for the state

`HashMap<State, Double> table;`



- Therefore State's must be *hashable*

State.java

```
abstract class State {  
  
    abstract int hash();  
  
    abstract boolean isEqual(State state);  
  
    @Override  
    public int hashCode() {  
        return this.hash();  
    }  
  
    @Override  
    public boolean equals(Object o) {  
        if (o instanceof State) {  
            State state = (State) o;  
            return isEqual(state);  
        }  
        return false;  
    }  
}
```

KnapsackState.java

```
public class KnapsackState extends State {

    int item, capacity;

    public KnapsackState(int index, int capacity) {
        this.item = index;
        this.capacity = capacity;
    }

    @Override
    int hash() {
        return Objects.hash(item, capacity);
    }

    @Override
    boolean isEqual(State s) {
        if (s instanceof KnapsackState) {
            KnapsackState state = (KnapsackState) s;
            return item == state.item && capacity == state.capacity;
        }
        return false;
    }
}
```


Useful Method

- Objects.hash

hash (2, 5)

hash

```
public static int hash(Object... values)
```

Generates a hash code for a sequence of input values. The hash code is generated as if all the input values were placed into an array, and that array were hashed by calling `Arrays.hashCode(Object[])`.

This method is useful for implementing `Object.hashCode()` on objects containing multiple fields. For example, if an object that has three fields, x, y, and z, one could write:

```
@Override public int hashCode() {  
    return Objects.hash(x, y, z);  
}
```

Warning: When a single object reference is supplied, the returned value does not equal the hash code of that object reference. This value can be computed by calling `hashCode(Object)`.

Parameters:

values - the values to be hashed

Returns:

a hash value of the sequence of input values

See Also:

`Arrays.hashCode(Object[])`, `List.hashCode()`

Transition.java (nothing to implement here)

```
class Transition<S extends State> {

    private S successor;
    private int decision;
    private double value;

    public Transition(S successor, int decision, double value) {
        this.successor = successor;
        this.decision = decision;
        this.value = value;
    }

    public S getSuccessor() {
        return successor;
    }

    public int getDecision() {
        return decision;
    }

    public double getValue() {
        return value;
    }
}
```

Model

```
abstract class Model<S extends State> {  
  
    abstract boolean isBaseCase(S state);  
  
    abstract double getBaseCaseValue(S state);  
  
    abstract S getRootState();  
  
    abstract List<Transition<S>> getTransitions(S state);  
  
    abstract boolean isMaximization();  
}
```


Knapsack(Model).java

```
public class Knapsack extends Model<KnapsackState> {
    KnapsackInstance instance;
    KnapsackState root;
    @Override
    boolean isBaseCase(KnapsackState state) { return state.item == instance.n || state.capacity == 0; }
    @Override
    double getBaseCaseValue(KnapsackState state) { return 0; }
    @Override
    List<Transition<KnapsackState>> getTransitions(KnapsackState state) {
        List<Transition<KnapsackState>> transitions = new LinkedList<>();
        // do not take the item
        transitions.add(new Transition<KnapsackState>(
            new KnapsackState(state.item + 1, state.capacity), 0, 0));
        // take the item if remaining capacity allows
        if (instance.weight[state.item] <= state.capacity) {
            transitions.add(new Transition<KnapsackState>(
                new KnapsackState(state.item + 1, state.capacity - instance.weight[state.item]), 1, instance.value[state.item]));
        }
        return transitions;
    }
    @Override
    KnapsackState getRootState() { return root; }
    @Override
    boolean isMaximization() { return true; }
}
```

Index	0	1	2	3	4
Value	1	6	18	22	28
Weight	2	3	5	6	7

DynamicProgramming.java

```
public class DynamicProgramming<S extends State> {  
  
    Model<S> model;           // the dynamic programming model to solve  
    HashMap<State, Double> table; // table to store the best value found for each state  
  
    public DynamicProgramming(Model<S> model) {  
        this.model = model;  
        this.table = new HashMap<>();  
    }  
    public Solution getSolution() {  
        // TODO compute the solution for the root state of the model  
    }  
}
```

Solution.java

```
public class Solution {  
  
    private double value;  
    private List<Integer> decisions;  
  
    public Solution(double value, List<Integer> decisions) {  
        this.value = value;  
        this.decisions = decisions;  
    }  
  
    public double getValue() {  
        return value;  
    }  
  
    public List<Integer> getDecisions() {  
        return decisions;  
    }  
  
    public boolean isValid() {  
        return true;  
    }  
  
}
```



How to recompute the solution from the table

```
HashMap<State, Double> table;
```


- Start from the root
- Generate the successor of the root and follow the one that has the same objective value minus the cost of the transition.
- Continue like this until you reach a terminal state.
- By following this path, you retrieve greedily the decisions leading to the best solution.

The solving ...

Retrieving the longest path



Your Project: Solve the TSP with DP (Hint on the state)



Dynamic Programming

LINFO2266

Pierre Schaus

