

Equipment Datasheet — 100-E-102

Heat Exchanger | CDU Unit

Document ID	DS-100-E-102
Equipment Tag	100-E-102
Equipment Name	Heat Exchanger
Process Unit	Crude Distillation Unit (100)
Manufacturer	Emerson Process Management
Install Date	2000-07-02
Design Pressure	8.8 barg
Design Temperature	136.2 degC
Material of Construction	Carbon Steel
Criticality Rating	Medium
Governing SOP	SOP-100-003
Governing Safety Procedure	SP-002

1. Equipment Description

100-E-102 is a Heat Exchanger installed in the Crude Distillation Unit (CDU) at PRPC. It was supplied by Emerson Process Management and commissioned on 2000-07-02. The equipment is classified as Medium criticality within the unit's reliability programme.

2. Design Basis

Design pressure is rated at 8.8 barg with a design temperature of 136.2 degC. Primary material of construction is Carbon Steel, selected for compatibility with process fluid composition and corrosion allowance requirements specific to CDU service.

3. Operating & Safety References

Operation of 100-E-102 is governed by procedure SOP-100-003 (Fired Heater Safe Startup Procedure). Isolation and personnel safety during maintenance follow SP-002 (Hot Work Permit and Fire Watch).

4. Maintenance Philosophy

100-E-102 is included in the CDU rotating/static equipment reliability programme with scheduled preventive maintenance and risk-based inspection (RBI) intervals determined by criticality rating (Medium).