

Equipment Datasheet — 100-F-104

Fired Heater | CDU Unit

Document ID	DS-100-F-104
Equipment Tag	100-F-104
Equipment Name	Fired Heater
Process Unit	Crude Distillation Unit (100)
Manufacturer	Triveni Turbines
Install Date	1998-03-23
Design Pressure	78.1 barg
Design Temperature	162.3 degC
Material of Construction	Duplex Stainless Steel
Criticality Rating	High
Governing SOP	SOP-100-001
Governing Safety Procedure	SP-009

1. Equipment Description

100-F-104 is a Fired Heater installed in the Crude Distillation Unit (CDU) at PRPC. It was supplied by Triveni Turbines and commissioned on 1998-03-23. The equipment is classified as High criticality within the unit's reliability programme.

2. Design Basis

Design pressure is rated at 78.1 barg with a design temperature of 162.3 degC. Primary material of construction is Duplex Stainless Steel, selected for compatibility with process fluid composition and corrosion allowance requirements specific to CDU service.

3. Operating & Safety References

Operation of 100-F-104 is governed by procedure SOP-100-001 (Crude Charge Pump Startup and Shutdown). Isolation and personnel safety during maintenance follow SP-009 (Crane and Heavy Lift Operations).

4. Maintenance Philosophy

100-F-104 is included in the CDU rotating/static equipment reliability programme with scheduled preventive maintenance and risk-based inspection (RBI) intervals determined by criticality rating (High).