

Equipment Datasheet — 100-PSV-110

Column Relief Valve | CDU Unit

Document ID	DS-100-PSV-110
Equipment Tag	100-PSV-110
Equipment Name	Column Relief Valve
Process Unit	Crude Distillation Unit (100)
Manufacturer	Godrej & Boyce
Install Date	2015-04-06
Design Pressure	85.1 barg
Design Temperature	158.8 degC
Material of Construction	Cast Iron
Criticality Rating	Low
Governing SOP	SOP-100-002
Governing Safety Procedure	SP-005

1. Equipment Description

100-PSV-110 is a Column Relief Valve installed in the Crude Distillation Unit (CDU) at PRPC. It was supplied by Godrej & Boyce and commissioned on 2015-04-06. The equipment is classified as Low criticality within the unit's reliability programme.

2. Design Basis

Design pressure is rated at 85.1 barg with a design temperature of 158.8 degC. Primary material of construction is Cast Iron, selected for compatibility with process fluid composition and corrosion allowance requirements specific to CDU service.

3. Operating & Safety References

Operation of 100-PSV-110 is governed by procedure SOP-100-002 (Atmospheric Distillation Column Operation). Isolation and personnel safety during maintenance follow SP-005 (Working at Height on Structures and Columns).

4. Maintenance Philosophy

100-PSV-110 is included in the CDU rotating/static equipment reliability programme with scheduled preventive maintenance and risk-based inspection (RBI) intervals determined by criticality rating (Low).