

Equipment Datasheet — 200-C-202

Recycle Gas Compressor | HCU Unit

Document ID	DS-200-C-202
Equipment Tag	200-C-202
Equipment Name	Recycle Gas Compressor
Process Unit	Hydrocracker Unit (200)
Manufacturer	L&T Valves
Install Date	2010-02-07
Design Pressure	164.7 barg
Design Temperature	289.6 degC
Material of Construction	Stainless Steel 316L
Criticality Rating	Medium
Governing SOP	SOP-200-004
Governing Safety Procedure	SP-004

1. Equipment Description

200-C-202 is a Recycle Gas Compressor installed in the Hydrocracker Unit (HCU) at PRPC. It was supplied by L&T; Valves and commissioned on 2010-02-07. The equipment is classified as Medium criticality within the unit's reliability programme.

2. Design Basis

Design pressure is rated at 164.7 barg with a design temperature of 289.6 degC. Primary material of construction is Stainless Steel 316L, selected for compatibility with process fluid composition and corrosion allowance requirements specific to HCU service.

3. Operating & Safety References

Operation of 200-C-202 is governed by procedure SOP-200-004 (Hydrocracker Reactor Loading and Catalyst Activation). Isolation and personnel safety during maintenance follow SP-004 (H2S Detection and Emergency Response).

4. Maintenance Philosophy

200-C-202 is included in the HCU rotating/static equipment reliability programme with scheduled preventive maintenance and risk-based inspection (RBI) intervals determined by criticality rating (Medium).