

Equipment Datasheet — 200-E-204

Feed/Effluent Exchanger | HCU Unit

Document ID	DS-200-E-204
Equipment Tag	200-E-204
Equipment Name	Feed/Effluent Exchanger
Process Unit	Hydrocracker Unit (200)
Manufacturer	L&T Valves
Install Date	2015-12-19
Design Pressure	79.1 barg
Design Temperature	296.8 degC
Material of Construction	Stainless Steel 316L
Criticality Rating	High
Governing SOP	SOP-200-006
Governing Safety Procedure	SP-004

1. Equipment Description

200-E-204 is a Feed/Effluent Exchanger installed in the Hydrocracker Unit (HCU) at PRPC. It was supplied by L&T; Valves and commissioned on 2015-12-19. The equipment is classified as High criticality within the unit's reliability programme.

2. Design Basis

Design pressure is rated at 79.1 barg with a design temperature of 296.8 degC. Primary material of construction is Stainless Steel 316L, selected for compatibility with process fluid composition and corrosion allowance requirements specific to HCU service.

3. Operating & Safety References

Operation of 200-E-204 is governed by procedure SOP-200-006 (High Pressure Separator Level Control). Isolation and personnel safety during maintenance follow SP-004 (H2S Detection and Emergency Response).

4. Maintenance Philosophy

200-E-204 is included in the HCU rotating/static equipment reliability programme with scheduled preventive maintenance and risk-based inspection (RBI) intervals determined by criticality rating (High).