

Equipment Datasheet — 200-R-201

Hydrocracking Reactor | HCU Unit

Document ID	DS-200-R-201
Equipment Tag	200-R-201
Equipment Name	Hydrocracking Reactor
Process Unit	Hydrocracker Unit (200)
Manufacturer	Fluor Daniel India
Install Date	2005-06-27
Design Pressure	139.1 barg
Design Temperature	64.6 degC
Material of Construction	Duplex Stainless Steel
Criticality Rating	Low
Governing SOP	SOP-200-006
Governing Safety Procedure	SP-008

1. Equipment Description

200-R-201 is a Hydrocracking Reactor installed in the Hydrocracker Unit (HCU) at PRPC. It was supplied by Fluor Daniel India and commissioned on 2005-06-27. The equipment is classified as Low criticality within the unit's reliability programme.

2. Design Basis

Design pressure is rated at 139.1 barg with a design temperature of 64.6 degC. Primary material of construction is Duplex Stainless Steel, selected for compatibility with process fluid composition and corrosion allowance requirements specific to HCU service.

3. Operating & Safety References

Operation of 200-R-201 is governed by procedure SOP-200-006 (High Pressure Separator Level Control). Isolation and personnel safety during maintenance follow SP-008 (Chemical Handling and Spill Response - ETP).

4. Maintenance Philosophy

200-R-201 is included in the HCU rotating/static equipment reliability programme with scheduled preventive maintenance and risk-based inspection (RBI) intervals determined by criticality rating (Low).