

Equipment Datasheet — 300-C-310

Nitrogen Generation Compressor | UTIL Unit

Document ID	DS-300-C-310
Equipment Tag	300-C-310
Equipment Name	Nitrogen Generation Compressor
Process Unit	Utilities & Offsites (300)
Manufacturer	Fluor Daniel India
Install Date	2019-11-04
Design Pressure	14.2 barg
Design Temperature	360.4 degC
Material of Construction	Carbon Steel
Criticality Rating	Low
Governing SOP	SOP-300-008
Governing Safety Procedure	SP-006

1. Equipment Description

300-C-310 is a Nitrogen Generation Compressor installed in the Utilities & Offsites (UTIL) at PRPC. It was supplied by Fluor Daniel India and commissioned on 2019-11-04. The equipment is classified as Low criticality within the unit's reliability programme.

2. Design Basis

Design pressure is rated at 14.2 barg with a design temperature of 360.4 degC. Primary material of construction is Carbon Steel, selected for compatibility with process fluid composition and corrosion allowance requirements specific to UTIL service.

3. Operating & Safety References

Operation of 300-C-310 is governed by procedure SOP-300-008 (Steam Turbine Generator Synchronization). Isolation and personnel safety during maintenance follow SP-006 (Pressure Safety Valve Isolation and Testing).

4. Maintenance Philosophy

300-C-310 is included in the UTIL rotating/static equipment reliability programme with scheduled preventive maintenance and risk-based inspection (RBI) intervals determined by criticality rating (Low).