

Equipment Datasheet — 400-PSV-407

Tank Vent Relief Valve | TF Unit

Document ID	DS-400-PSV-407
Equipment Tag	400-PSV-407
Equipment Name	Tank Vent Relief Valve
Process Unit	Tank Farm / Storage (400)
Manufacturer	Kirloskar Brothers Ltd
Install Date	2003-09-03
Design Pressure	153.8 barg
Design Temperature	70.1 degC
Material of Construction	Stainless Steel 316L
Criticality Rating	High
Governing SOP	SOP-400-010
Governing Safety Procedure	SP-008

1. Equipment Description

400-PSV-407 is a Tank Vent Relief Valve installed in the Tank Farm / Storage (TF) at PRPC. It was supplied by Kirloskar Brothers Ltd and commissioned on 2003-09-03. The equipment is classified as High criticality within the unit's reliability programme.

2. Design Basis

Design pressure is rated at 153.8 barg with a design temperature of 70.1 degC. Primary material of construction is Stainless Steel 316L, selected for compatibility with process fluid composition and corrosion allowance requirements specific to TF service.

3. Operating & Safety References

Operation of 400-PSV-407 is governed by procedure SOP-400-010 (Tank Gauging and Inventory Reconciliation). Isolation and personnel safety during maintenance follow SP-008 (Chemical Handling and Spill Response - ETP).

4. Maintenance Philosophy

400-PSV-407 is included in the TF rotating/static equipment reliability programme with scheduled preventive maintenance and risk-based inspection (RBI) intervals determined by criticality rating (High).