

## Equipment Datasheet — 400-T-401

Crude Storage Tank | TF Unit

|                            |                           |
|----------------------------|---------------------------|
| Document ID                | DS-400-T-401              |
| Equipment Tag              | 400-T-401                 |
| Equipment Name             | Crude Storage Tank        |
| Process Unit               | Tank Farm / Storage (400) |
| Manufacturer               | Forbes Marshall           |
| Install Date               | 2005-04-18                |
| Design Pressure            | 82.7 barg                 |
| Design Temperature         | 225.6 degC                |
| Material of Construction   | Stainless Steel 316L      |
| Criticality Rating         | High                      |
| Governing SOP              | SOP-400-012               |
| Governing Safety Procedure | SP-005                    |

### 1. Equipment Description

400-T-401 is a Crude Storage Tank installed in the Tank Farm / Storage (TF) at PRPC. It was supplied by Forbes Marshall and commissioned on 2005-04-18. The equipment is classified as High criticality within the unit's reliability programme.

### 2. Design Basis

Design pressure is rated at 82.7 barg with a design temperature of 225.6 degC. Primary material of construction is Stainless Steel 316L, selected for compatibility with process fluid composition and corrosion allowance requirements specific to TF service.

### 3. Operating & Safety References

Operation of 400-T-401 is governed by procedure SOP-400-012 (LPG Bullet Pressure Monitoring). Isolation and personnel safety during maintenance follow SP-005 (Working at Height on Structures and Columns).

### 4. Maintenance Philosophy

400-T-401 is included in the TF rotating/static equipment reliability programme with scheduled preventive maintenance and risk-based inspection (RBI) intervals determined by criticality rating (High).