

Equipment Datasheet — 400-T-403

Diesel Storage Tank | TF Unit

Document ID	DS-400-T-403
Equipment Tag	400-T-403
Equipment Name	Diesel Storage Tank
Process Unit	Tank Farm / Storage (400)
Manufacturer	Thermax Ltd
Install Date	2005-07-16
Design Pressure	88.5 barg
Design Temperature	420.4 degC
Material of Construction	Stainless Steel 316L
Criticality Rating	Low
Governing SOP	SOP-400-010
Governing Safety Procedure	SP-010

1. Equipment Description

400-T-403 is a Diesel Storage Tank installed in the Tank Farm / Storage (TF) at PRPC. It was supplied by Thermax Ltd and commissioned on 2005-07-16. The equipment is classified as Low criticality within the unit's reliability programme.

2. Design Basis

Design pressure is rated at 88.5 barg with a design temperature of 420.4 degC. Primary material of construction is Stainless Steel 316L, selected for compatibility with process fluid composition and corrosion allowance requirements specific to TF service.

3. Operating & Safety References

Operation of 400-T-403 is governed by procedure SOP-400-010 (Tank Gauging and Inventory Reconciliation). Isolation and personnel safety during maintenance follow SP-010 (Fire and Gas Detection System Testing).

4. Maintenance Philosophy

400-T-403 is included in the TF rotating/static equipment reliability programme with scheduled preventive maintenance and risk-based inspection (RBI) intervals determined by criticality rating (Low).