

Equipment Datasheet — 400-T-404

LPG Bullet | TF Unit

Document ID	DS-400-T-404
Equipment Tag	400-T-404
Equipment Name	LPG Bullet
Process Unit	Tank Farm / Storage (400)
Manufacturer	Kirloskar Brothers Ltd
Install Date	2010-07-09
Design Pressure	167.0 barg
Design Temperature	385.5 degC
Material of Construction	Cast Iron
Criticality Rating	High
Governing SOP	SOP-400-012
Governing Safety Procedure	SP-001

1. Equipment Description

400-T-404 is a LPG Bullet installed in the Tank Farm / Storage (TF) at PRPC. It was supplied by Kirloskar Brothers Ltd and commissioned on 2010-07-09. The equipment is classified as High criticality within the unit's reliability programme.

2. Design Basis

Design pressure is rated at 167.0 barg with a design temperature of 385.5 degC. Primary material of construction is Cast Iron, selected for compatibility with process fluid composition and corrosion allowance requirements specific to TF service.

3. Operating & Safety References

Operation of 400-T-404 is governed by procedure SOP-400-012 (LPG Bullet Pressure Monitoring). Isolation and personnel safety during maintenance follow SP-001 (Lockout-Tagout (LOTO) for Rotating Equipment).

4. Maintenance Philosophy

400-T-404 is included in the TF rotating/static equipment reliability programme with scheduled preventive maintenance and risk-based inspection (RBI) intervals determined by criticality rating (High).