

Equipment Datasheet — 400-T-408

Slop Oil Tank | TF Unit

Document ID	DS-400-T-408
Equipment Tag	400-T-408
Equipment Name	Slop Oil Tank
Process Unit	Tank Farm / Storage (400)
Manufacturer	BHEL
Install Date	2010-10-08
Design Pressure	105.7 barg
Design Temperature	57.5 degC
Material of Construction	Cast Iron
Criticality Rating	High
Governing SOP	SOP-400-012
Governing Safety Procedure	SP-008

1. Equipment Description

400-T-408 is a Slop Oil Tank installed in the Tank Farm / Storage (TF) at PRPC. It was supplied by BHEL and commissioned on 2010-10-08. The equipment is classified as High criticality within the unit's reliability programme.

2. Design Basis

Design pressure is rated at 105.7 barg with a design temperature of 57.5 degC. Primary material of construction is Cast Iron, selected for compatibility with process fluid composition and corrosion allowance requirements specific to TF service.

3. Operating & Safety References

Operation of 400-T-408 is governed by procedure SOP-400-012 (LPG Bullet Pressure Monitoring). Isolation and personnel safety during maintenance follow SP-008 (Chemical Handling and Spill Response - ETP).

4. Maintenance Philosophy

400-T-408 is included in the TF rotating/static equipment reliability programme with scheduled preventive maintenance and risk-based inspection (RBI) intervals determined by criticality rating (High).