

Equipment Datasheet — 500-AGT-501

Flocculation Agitator | ETP Unit

Document ID	DS-500-AGT-501
Equipment Tag	500-AGT-501
Equipment Name	Flocculation Agitator
Process Unit	Effluent Treatment Plant (500)
Manufacturer	Emerson Process Management
Install Date	2012-10-04
Design Pressure	16.4 barg
Design Temperature	133.8 degC
Material of Construction	Duplex Stainless Steel
Criticality Rating	High
Governing SOP	SOP-500-015
Governing Safety Procedure	SP-008

1. Equipment Description

500-AGT-501 is a Flocculation Agitator installed in the Effluent Treatment Plant (ETP) at PRPC. It was supplied by Emerson Process Management and commissioned on 2012-10-04. The equipment is classified as High criticality within the unit's reliability programme.

2. Design Basis

Design pressure is rated at 16.4 barg with a design temperature of 133.8 degC. Primary material of construction is Duplex Stainless Steel, selected for compatibility with process fluid composition and corrosion allowance requirements specific to ETP service.

3. Operating & Safety References

Operation of 500-AGT-501 is governed by procedure SOP-500-015 (Sludge Dewatering and Disposal). Isolation and personnel safety during maintenance follow SP-008 (Chemical Handling and Spill Response - ETP).

4. Maintenance Philosophy

500-AGT-501 is included in the ETP rotating/static equipment reliability programme with scheduled preventive maintenance and risk-based inspection (RBI) intervals determined by criticality rating (High).