

Equipment Datasheet — 500-P-507

Dosing Pump - Chemical | ETP Unit

Document ID	DS-500-P-507
Equipment Tag	500-P-507
Equipment Name	Dosing Pump - Chemical
Process Unit	Effluent Treatment Plant (500)
Manufacturer	Godrej & Boyce
Install Date	2003-08-18
Design Pressure	128.1 barg
Design Temperature	286.8 degC
Material of Construction	Stainless Steel 316L
Criticality Rating	High
Governing SOP	SOP-500-014
Governing Safety Procedure	SP-008

1. Equipment Description

500-P-507 is a Dosing Pump - Chemical installed in the Effluent Treatment Plant (ETP) at PRPC. It was supplied by Godrej & Boyce and commissioned on 2003-08-18. The equipment is classified as High criticality within the unit's reliability programme.

2. Design Basis

Design pressure is rated at 128.1 barg with a design temperature of 286.8 degC. Primary material of construction is Stainless Steel 316L, selected for compatibility with process fluid composition and corrosion allowance requirements specific to ETP service.

3. Operating & Safety References

Operation of 500-P-507 is governed by procedure SOP-500-014 (Oil-Water Separator Skimming Procedure). Isolation and personnel safety during maintenance follow SP-008 (Chemical Handling and Spill Response - ETP).

4. Maintenance Philosophy

500-P-507 is included in the ETP rotating/static equipment reliability programme with scheduled preventive maintenance and risk-based inspection (RBI) intervals determined by criticality rating (High).