

Equipment Datasheet — 500-P-509

Backwash Pump | ETP Unit

Document ID	DS-500-P-509
Equipment Tag	500-P-509
Equipment Name	Backwash Pump
Process Unit	Effluent Treatment Plant (500)
Manufacturer	Cameron (Schlumberger)
Install Date	1999-06-07
Design Pressure	123.9 barg
Design Temperature	333.5 degC
Material of Construction	Cast Iron
Criticality Rating	High
Governing SOP	SOP-500-015
Governing Safety Procedure	SP-001

1. Equipment Description

500-P-509 is a Backwash Pump installed in the Effluent Treatment Plant (ETP) at PRPC. It was supplied by Cameron (Schlumberger) and commissioned on 1999-06-07. The equipment is classified as High criticality within the unit's reliability programme.

2. Design Basis

Design pressure is rated at 123.9 barg with a design temperature of 333.5 degC. Primary material of construction is Cast Iron, selected for compatibility with process fluid composition and corrosion allowance requirements specific to ETP service.

3. Operating & Safety References

Operation of 500-P-509 is governed by procedure SOP-500-015 (Sludge Dewatering and Disposal). Isolation and personnel safety during maintenance follow SP-001 (Lockout-Tagout (LOTO) for Rotating Equipment).

4. Maintenance Philosophy

500-P-509 is included in the ETP rotating/static equipment reliability programme with scheduled preventive maintenance and risk-based inspection (RBI) intervals determined by criticality rating (High).