

Equipment Datasheet — 100-PSV-106

Pressure Safety Valve | CDU Unit

Document ID	DS-100-PSV-106
Equipment Tag	100-PSV-106
Equipment Name	Pressure Safety Valve
Process Unit	Crude Distillation Unit (100)
Manufacturer	Sulzer India
Install Date	2012-02-13
Design Pressure	17.4 barg
Design Temperature	169.0 degC
Material of Construction	Duplex Stainless Steel
Criticality Rating	Medium
Governing SOP	SOP-100-001
Governing Safety Procedure	SP-007

1. Equipment Description

100-PSV-106 is a Pressure Safety Valve installed in the Crude Distillation Unit (CDU) at PRPC. It was supplied by Sulzer India and commissioned on 2012-02-13. The equipment is classified as Medium criticality within the unit's reliability programme.

2. Design Basis

Design pressure is rated at 17.4 barg with a design temperature of 169.0 degC. Primary material of construction is Duplex Stainless Steel, selected for compatibility with process fluid composition and corrosion allowance requirements specific to CDU service.

3. Operating & Safety References

Operation of 100-PSV-106 is governed by procedure SOP-100-001 (Crude Charge Pump Startup and Shutdown). Isolation and personnel safety during maintenance follow SP-007 (Emergency Shutdown (ESD) Activation Protocol).

4. Maintenance Philosophy

100-PSV-106 is included in the CDU rotating/static equipment reliability programme with scheduled preventive maintenance and risk-based inspection (RBI) intervals determined by criticality rating (Medium).