

Equipment Datasheet — 200-F-206

Reactor Feed Heater | HCU Unit

Document ID	DS-200-F-206
Equipment Tag	200-F-206
Equipment Name	Reactor Feed Heater
Process Unit	Hydrocracker Unit (200)
Manufacturer	BHEL
Install Date	2017-07-13
Design Pressure	108.7 barg
Design Temperature	245.9 degC
Material of Construction	Cast Iron
Criticality Rating	High
Governing SOP	SOP-200-006
Governing Safety Procedure	SP-004

1. Equipment Description

200-F-206 is a Reactor Feed Heater installed in the Hydrocracker Unit (HCU) at PRPC. It was supplied by BHEL and commissioned on 2017-07-13. The equipment is classified as High criticality within the unit's reliability programme.

2. Design Basis

Design pressure is rated at 108.7 barg with a design temperature of 245.9 degC. Primary material of construction is Cast Iron, selected for compatibility with process fluid composition and corrosion allowance requirements specific to HCU service.

3. Operating & Safety References

Operation of 200-F-206 is governed by procedure SOP-200-006 (High Pressure Separator Level Control). Isolation and personnel safety during maintenance follow SP-004 (H2S Detection and Emergency Response).

4. Maintenance Philosophy

200-F-206 is included in the HCU rotating/static equipment reliability programme with scheduled preventive maintenance and risk-based inspection (RBI) intervals determined by criticality rating (High).