

Equipment Datasheet — 200-P-203

Charge Pump | HCU Unit

Document ID	DS-200-P-203
Equipment Tag	200-P-203
Equipment Name	Charge Pump
Process Unit	Hydrocracker Unit (200)
Manufacturer	Ingersoll Rand
Install Date	2018-07-21
Design Pressure	84.5 barg
Design Temperature	156.5 degC
Material of Construction	Cast Iron
Criticality Rating	High
Governing SOP	SOP-200-005
Governing Safety Procedure	SP-010

1. Equipment Description

200-P-203 is a Charge Pump installed in the Hydrocracker Unit (HCU) at PRPC. It was supplied by Ingersoll Rand and commissioned on 2018-07-21. The equipment is classified as High criticality within the unit's reliability programme.

2. Design Basis

Design pressure is rated at 84.5 barg with a design temperature of 156.5 degC. Primary material of construction is Cast Iron, selected for compatibility with process fluid composition and corrosion allowance requirements specific to HCU service.

3. Operating & Safety References

Operation of 200-P-203 is governed by procedure SOP-200-005 (Recycle Gas Compressor Operating Envelope). Isolation and personnel safety during maintenance follow SP-010 (Fire and Gas Detection System Testing).

4. Maintenance Philosophy

200-P-203 is included in the HCU rotating/static equipment reliability programme with scheduled preventive maintenance and risk-based inspection (RBI) intervals determined by criticality rating (High).