

Equipment Datasheet — 200-V-205

High Pressure Separator | HCU Unit

Document ID	DS-200-V-205
Equipment Tag	200-V-205
Equipment Name	High Pressure Separator
Process Unit	Hydrocracker Unit (200)
Manufacturer	Ingersoll Rand
Install Date	2014-02-25
Design Pressure	11.8 barg
Design Temperature	88.2 degC
Material of Construction	Low Alloy Steel (Cr-Mo)
Criticality Rating	Medium
Governing SOP	SOP-200-005
Governing Safety Procedure	SP-002

1. Equipment Description

200-V-205 is a High Pressure Separator installed in the Hydrocracker Unit (HCU) at PRPC. It was supplied by Ingersoll Rand and commissioned on 2014-02-25. The equipment is classified as Medium criticality within the unit's reliability programme.

2. Design Basis

Design pressure is rated at 11.8 barg with a design temperature of 88.2 degC. Primary material of construction is Low Alloy Steel (Cr-Mo), selected for compatibility with process fluid composition and corrosion allowance requirements specific to HCU service.

3. Operating & Safety References

Operation of 200-V-205 is governed by procedure SOP-200-005 (Recycle Gas Compressor Operating Envelope). Isolation and personnel safety during maintenance follow SP-002 (Hot Work Permit and Fire Watch).

4. Maintenance Philosophy

200-V-205 is included in the HCU rotating/static equipment reliability programme with scheduled preventive maintenance and risk-based inspection (RBI) intervals determined by criticality rating (Medium).