

Equipment Datasheet — 300-BLR-301

Package Boiler | UTIL Unit

Document ID	DS-300-BLR-301
Equipment Tag	300-BLR-301
Equipment Name	Package Boiler
Process Unit	Utilities & Offsites (300)
Manufacturer	Emerson Process Management
Install Date	1998-06-16
Design Pressure	6.9 barg
Design Temperature	448.8 degC
Material of Construction	Duplex Stainless Steel
Criticality Rating	Low
Governing SOP	SOP-300-009
Governing Safety Procedure	SP-010

1. Equipment Description

300-BLR-301 is a Package Boiler installed in the Utilities & Offsites (UTIL) at PRPC. It was supplied by Emerson Process Management and commissioned on 1998-06-16. The equipment is classified as Low criticality within the unit's reliability programme.

2. Design Basis

Design pressure is rated at 6.9 barg with a design temperature of 448.8 degC. Primary material of construction is Duplex Stainless Steel, selected for compatibility with process fluid composition and corrosion allowance requirements specific to UTIL service.

3. Operating & Safety References

Operation of 300-BLR-301 is governed by procedure SOP-300-009 (Cooling Tower Water Chemistry Control). Isolation and personnel safety during maintenance follow SP-010 (Fire and Gas Detection System Testing).

4. Maintenance Philosophy

300-BLR-301 is included in the UTIL rotating/static equipment reliability programme with scheduled preventive maintenance and risk-based inspection (RBI) intervals determined by criticality rating (Low).