

Equipment Datasheet — 300-CT-304

Induced Draft Cooling Tower | UTIL Unit

Document ID	DS-300-CT-304
Equipment Tag	300-CT-304
Equipment Name	Induced Draft Cooling Tower
Process Unit	Utilities & Offsites (300)
Manufacturer	Grundfos India
Install Date	2017-04-18
Design Pressure	136.8 barg
Design Temperature	343.5 degC
Material of Construction	Low Alloy Steel (Cr-Mo)
Criticality Rating	Medium
Governing SOP	SOP-300-009
Governing Safety Procedure	SP-005

1. Equipment Description

300-CT-304 is a Induced Draft Cooling Tower installed in the Utilities & Offsites (UTIL) at PRPC. It was supplied by Grundfos India and commissioned on 2017-04-18. The equipment is classified as Medium criticality within the unit's reliability programme.

2. Design Basis

Design pressure is rated at 136.8 barg with a design temperature of 343.5 degC. Primary material of construction is Low Alloy Steel (Cr-Mo), selected for compatibility with process fluid composition and corrosion allowance requirements specific to UTIL service.

3. Operating & Safety References

Operation of 300-CT-304 is governed by procedure SOP-300-009 (Cooling Tower Water Chemistry Control). Isolation and personnel safety during maintenance follow SP-005 (Working at Height on Structures and Columns).

4. Maintenance Philosophy

300-CT-304 is included in the UTIL rotating/static equipment reliability programme with scheduled preventive maintenance and risk-based inspection (RBI) intervals determined by criticality rating (Medium).