

Equipment Datasheet — 300-TUR-302

Steam Turbine Generator | UTIL Unit

Document ID	DS-300-TUR-302
Equipment Tag	300-TUR-302
Equipment Name	Steam Turbine Generator
Process Unit	Utilities & Offsites (300)
Manufacturer	Kirloskar Brothers Ltd
Install Date	2005-04-19
Design Pressure	170.6 barg
Design Temperature	77.7 degC
Material of Construction	Carbon Steel
Criticality Rating	Medium
Governing SOP	SOP-300-008
Governing Safety Procedure	SP-008

1. Equipment Description

300-TUR-302 is a Steam Turbine Generator installed in the Utilities & Offsites (UTIL) at PRPC. It was supplied by Kirloskar Brothers Ltd and commissioned on 2005-04-19. The equipment is classified as Medium criticality within the unit's reliability programme.

2. Design Basis

Design pressure is rated at 170.6 barg with a design temperature of 77.7 degC. Primary material of construction is Carbon Steel, selected for compatibility with process fluid composition and corrosion allowance requirements specific to UTIL service.

3. Operating & Safety References

Operation of 300-TUR-302 is governed by procedure SOP-300-008 (Steam Turbine Generator Synchronization). Isolation and personnel safety during maintenance follow SP-008 (Chemical Handling and Spill Response - ETP).

4. Maintenance Philosophy

300-TUR-302 is included in the UTIL rotating/static equipment reliability programme with scheduled preventive maintenance and risk-based inspection (RBI) intervals determined by criticality rating (Medium).