

Equipment Datasheet — 400-P-410

Blending Pump | TF Unit

Document ID	DS-400-P-410
Equipment Tag	400-P-410
Equipment Name	Blending Pump
Process Unit	Tank Farm / Storage (400)
Manufacturer	Fluor Daniel India
Install Date	2002-11-10
Design Pressure	84.2 barg
Design Temperature	448.8 degC
Material of Construction	Carbon Steel
Criticality Rating	Low
Governing SOP	SOP-400-012
Governing Safety Procedure	SP-007

1. Equipment Description

400-P-410 is a Blending Pump installed in the Tank Farm / Storage (TF) at PRPC. It was supplied by Fluor Daniel India and commissioned on 2002-11-10. The equipment is classified as Low criticality within the unit's reliability programme.

2. Design Basis

Design pressure is rated at 84.2 barg with a design temperature of 448.8 degC. Primary material of construction is Carbon Steel, selected for compatibility with process fluid composition and corrosion allowance requirements specific to TF service.

3. Operating & Safety References

Operation of 400-P-410 is governed by procedure SOP-400-012 (LPG Bullet Pressure Monitoring). Isolation and personnel safety during maintenance follow SP-007 (Emergency Shutdown (ESD) Activation Protocol).

4. Maintenance Philosophy

400-P-410 is included in the TF rotating/static equipment reliability programme with scheduled preventive maintenance and risk-based inspection (RBI) intervals determined by criticality rating (Low).