

Equipment Datasheet — 400-T-402

Naphtha Storage Tank | TF Unit

Document ID	DS-400-T-402
Equipment Tag	400-T-402
Equipment Name	Naphtha Storage Tank
Process Unit	Tank Farm / Storage (400)
Manufacturer	Ingersoll Rand
Install Date	2000-09-04
Design Pressure	12.4 barg
Design Temperature	479.7 degC
Material of Construction	Carbon Steel
Criticality Rating	Low
Governing SOP	SOP-400-010
Governing Safety Procedure	SP-002

1. Equipment Description

400-T-402 is a Naphtha Storage Tank installed in the Tank Farm / Storage (TF) at PRPC. It was supplied by Ingersoll Rand and commissioned on 2000-09-04. The equipment is classified as Low criticality within the unit's reliability programme.

2. Design Basis

Design pressure is rated at 12.4 barg with a design temperature of 479.7 degC. Primary material of construction is Carbon Steel, selected for compatibility with process fluid composition and corrosion allowance requirements specific to TF service.

3. Operating & Safety References

Operation of 400-T-402 is governed by procedure SOP-400-010 (Tank Gauging and Inventory Reconciliation). Isolation and personnel safety during maintenance follow SP-002 (Hot Work Permit and Fire Watch).

4. Maintenance Philosophy

400-T-402 is included in the TF rotating/static equipment reliability programme with scheduled preventive maintenance and risk-based inspection (RBI) intervals determined by criticality rating (Low).