

Equipment Datasheet — 400-T-409

ATF Storage Tank | TF Unit

Document ID	DS-400-T-409
Equipment Tag	400-T-409
Equipment Name	ATF Storage Tank
Process Unit	Tank Farm / Storage (400)
Manufacturer	Sulzer India
Install Date	2016-06-09
Design Pressure	39.6 barg
Design Temperature	355.1 degC
Material of Construction	Low Alloy Steel (Cr-Mo)
Criticality Rating	High
Governing SOP	SOP-400-011
Governing Safety Procedure	SP-003

1. Equipment Description

400-T-409 is a ATF Storage Tank installed in the Tank Farm / Storage (TF) at PRPC. It was supplied by Sulzer India and commissioned on 2016-06-09. The equipment is classified as High criticality within the unit's reliability programme.

2. Design Basis

Design pressure is rated at 39.6 barg with a design temperature of 355.1 degC. Primary material of construction is Low Alloy Steel (Cr-Mo), selected for compatibility with process fluid composition and corrosion allowance requirements specific to TF service.

3. Operating & Safety References

Operation of 400-T-409 is governed by procedure SOP-400-011 (Product Loading Arm Operation). Isolation and personnel safety during maintenance follow SP-003 (Confined Space Entry - Vessels and Tanks).

4. Maintenance Philosophy

400-T-409 is included in the TF rotating/static equipment reliability programme with scheduled preventive maintenance and risk-based inspection (RBI) intervals determined by criticality rating (High).