

Equipment Datasheet — 500-AGT-504

Aeration Tank Mixer | ETP Unit

Document ID	DS-500-AGT-504
Equipment Tag	500-AGT-504
Equipment Name	Aeration Tank Mixer
Process Unit	Effluent Treatment Plant (500)
Manufacturer	L&T Valves
Install Date	2002-02-04
Design Pressure	134.5 barg
Design Temperature	108.4 degC
Material of Construction	Stainless Steel 316L
Criticality Rating	High
Governing SOP	SOP-500-014
Governing Safety Procedure	SP-006

1. Equipment Description

500-AGT-504 is a Aeration Tank Mixer installed in the Effluent Treatment Plant (ETP) at PRPC. It was supplied by L&T; Valves and commissioned on 2002-02-04. The equipment is classified as High criticality within the unit's reliability programme.

2. Design Basis

Design pressure is rated at 134.5 barg with a design temperature of 108.4 degC. Primary material of construction is Stainless Steel 316L, selected for compatibility with process fluid composition and corrosion allowance requirements specific to ETP service.

3. Operating & Safety References

Operation of 500-AGT-504 is governed by procedure SOP-500-014 (Oil-Water Separator Skimming Procedure). Isolation and personnel safety during maintenance follow SP-006 (Pressure Safety Valve Isolation and Testing).

4. Maintenance Philosophy

500-AGT-504 is included in the ETP rotating/static equipment reliability programme with scheduled preventive maintenance and risk-based inspection (RBI) intervals determined by criticality rating (High).