

Equipment Datasheet — 500-V-503

Oil-Water Separator | ETP Unit

Document ID	DS-500-V-503
Equipment Tag	500-V-503
Equipment Name	Oil-Water Separator
Process Unit	Effluent Treatment Plant (500)
Manufacturer	Triveni Turbines
Install Date	2017-11-17
Design Pressure	4.9 barg
Design Temperature	399.5 degC
Material of Construction	Carbon Steel
Criticality Rating	High
Governing SOP	SOP-500-014
Governing Safety Procedure	SP-007

1. Equipment Description

500-V-503 is a Oil-Water Separator installed in the Effluent Treatment Plant (ETP) at PRPC. It was supplied by Triveni Turbines and commissioned on 2017-11-17. The equipment is classified as High criticality within the unit's reliability programme.

2. Design Basis

Design pressure is rated at 4.9 barg with a design temperature of 399.5 degC. Primary material of construction is Carbon Steel, selected for compatibility with process fluid composition and corrosion allowance requirements specific to ETP service.

3. Operating & Safety References

Operation of 500-V-503 is governed by procedure SOP-500-014 (Oil-Water Separator Skimming Procedure). Isolation and personnel safety during maintenance follow SP-007 (Emergency Shutdown (ESD) Activation Protocol).

4. Maintenance Philosophy

500-V-503 is included in the ETP rotating/static equipment reliability programme with scheduled preventive maintenance and risk-based inspection (RBI) intervals determined by criticality rating (High).