

# Computer Programming

Dr. Deepak B Phatak  
Dr. Supratik Chakraborty  
Department of Computer Science and Engineering  
IIT Bombay

Session: Using Arrays for solving computational problems

# Quick Recap

---



- C++ provides array data structure
- An array
  - is declared with a type and a size
  - elements of an array are accessed by using index expressions
  - value of index must be between 0 and size-1

# Quick Recap

---



- Iterative constructs can be easily used to examine and process all elements of an array, in some desired order
- A **for** loop is ideal to iterate on values of index  $i$ , from 0 to  $N-1$

```
for (i=0; i < N; i++){  
    // code to process array elements  
}
```

# Overview of This Lecture

---



- Using arrays to solve computational problems
  - Finding average and standard deviation of marks scored in quiz

# Problem: Calculating Marks Statistics



N students of a class have taken a quiz. Their marks are to be processed to calculate the average, and standard deviation. Assume that there are at most 600 students in the class.

## Analysis:

- We have seen how to solve the problem of finding the average of given numbers. We will use the same algorithm
  - Declare an array MARKS of size 600, type integer (?)
  - Read and store N marks in an array MARKS
  - Find the sum of all N marks, divide by N to get average ( $\mu$ )

# Standard Deviation

---



- We need to know how to calculate standard deviation
- Standard deviation is a statistical term. Its value describes how much various data values are spread around average value.
  - A large value indicates many data values are far away from average
  - A smaller value indicates most data values to be close to average.
- Useful in many practical situations

# Standard Deviation



If  $\mu$  is the average of N marks, standard Deviation ( $\sigma$ ) is defined in terms of our array elements, as:

$$\sigma = \text{sqrt} \left( \sum 1/N * (\text{MARKS}[i] - \mu)^2 \right),$$

(where the summation is over  $i = 0$  to  $N-1$ )

sqrt represents the square root of the quantity in parenthesis

- C++ provides a library, with many mathematical functions
- We must include a header file called `<cmath>` in our program, in order to use the sqrt, and other functions

# Program Design

---



- We use familiar algorithm to calculate average
  - Read and store N marks in an array MARKS
  - Iteratively find the sum, divide by N to get average  $\mu$
- Next we calculate standard deviation  $\sigma$ 
  - Set up another iteration over i, to scan all array elements again
    - Calculate the difference diff, between marks[i] and  $\mu$
    - Add the square of diff to the running sum
  - Divide the sum by N, and calculate square root, to get sigma



# Program to find statistics of marks scored



```
int main(){
    // program to find marks statistics
    int marks[600] , i, N;
    float sum, diff, mu, sigma;
    // read N elements of marks array
    cin >> N;
    for (i = 0; i < N; i = i + 1){
        cin >> marks[i];
    }
}
```

## Program ... ( average)

---



```
// Calculate average mu
sum = 0.0;
for (i =0; i < N; i = i +1){
    sum = sum + marks[i];
}
mu = sum/N;
```

## Program ... (standard deviation)



```
// Calculate standard deviation sigma
sum = 0.0;
for (i = 0; i < N; i = i + 1){
    diff = marks[i] - mu
    sum = sum + diff * diff;
}
sigma = sqrt (sum/N);
```

## Program ... (output results)



```
cout << "Statistics of quiz 1 marks of the class" << endl;
cout << "Number of students is: " << N << endl;
cout << "Average marks: " << mu << endl;
cout << "Standard Deviation of Marks: " << sigma << endl;
return 0;
}
```

# A few practical aspects of programming

---



- Users may commit mistakes while giving data
- What if the value of N is given as 1000?
  - How do we convey to users, that the limit is 600 marks?
- At least, our program should validate input
  - Check if value of N is out of bound
  - If so, give an error message, and exit with a value other than 0

# Practical programming ...

---



```
// validate input
if (N < 1 || N > 600){
    cout << "Invalid value of N: " << N << endl;
    return -1;
}
```

# Practical Programming

---



- For solving any problem, it is useful to
  - Write a small design document , outlining the algorithm
  - Indicate variables and arrays to be used
- While writing a program
  - Write program segments in logical order
  - Write explanatory comments
  - Use simple, and easy to understand constructs

# Summary

---



- We have learnt how to use arrays to solve simple computational problems
- In the next session, we will consider another problem