

# Computer Programming

Dr. Deepak B Phatak  
Dr. Supratik Chakraborty  
Department of Computer Science and Engineering  
IIT Bombay

Session: Introduction to Object-Oriented Programming -- Structures

# Quick Recap of Relevant Topics

---



- Basic ingredients for programming in C++
  - Data types, variables, constants, arrays
  - Sequential and conditional statements
  - Iterative constructs
  - Functions

# Overview of This Lecture

---



- Basic idea of object-oriented programming
- Introduction to structures in C++

# Acknowledgment

---



- Some examples in this lecture are from  
**An Introduction to Programming Through C++  
by Abhiram G. Ranade  
McGraw Hill Education 2014**
- All such examples indicated in slides with the citation  
**AGRBook**

# Designing A Complex Program [Ref. AGRBook]



- We want to design a book check out/return/claim management system of a small library
- How does the system work?
  - Every patron has a unique numerical id
  - Every book has an accession number
  - **Check out:** A patron can check out upto 3 books at any time
  - **Claim:** If X has not already checked out 3 books, she can claim a book checked out by Y

When Y returns the book, it is held for X and cannot be lent to others
  - **Return:** A patron can return a book checked out by her at any time

No late charges!

# Designing a Complex Program

## Should we jump into writing code?

- Keep adding variables/arrays and functions as and when needed

### For each book:

- Title and authors (char arrays)
- Price in Indian Rupees (double)
- Accession number (int)
- Check out status (bool)
- Claimant's id (int), if any

### For each patron:

- Name and address (char arrays)
- Unique id (int)
- Number of books checked out (int)
- Claimed book's accession number (int), if any

# Designing a Complex Program

## Should we jump into writing code?

- Keep adding variables and function as and when needed

### For each book:

- Title and authors (char arrays)
- Price in Indian Rupees (double)
- Accession number (int)
- Check out status (bool)
- Claimant's id (int), if any

### For each patron:

- Name and address (char array)
- Unique id (int)

1000 books implies 1000-sized arrays of

char array (book title)

char array (authors' names)

double (price)

int (accession number )

bool (check out status)

int (claimant id )

**Perhaps manageable, but not natural to split information about same book in six different arrays**

# Designing a Complex Program

**Must store information about a book at same index in all arrays**

title[5], authors[5], price[5],  
accNum[5],  
checkOutStatus[5],  
claimantId[5]

must refer to the same book

1000-sized arrays of  
char array (book title)  
char array (authors' names)  
double (price)  
int (accession number )  
bool (check out status)  
int (claimant id )

**How do we find claimant for the book with acc. number 123456?**

Find “index” such that accNum[index] is 123456  
Then access claimantId[index]

**Unnecessarily  
convoluted !!!**



## Is There A Better Way?

---

- Wouldn't it be nice if we could do the following?
  - Group all information about a book into a “book entity”
  - Have an array of these “book entities”

Once we search this array and find an entity whose accession number is 123456, we can read off the claimant information for this array element.

- Similarly, we could
  - Group all information about a patron into a “patron entity”
  - Have an array of these “patron entities”

# Structures in C++

- C++ provides **structures** to group a set of variables of possibly different data types together

```
struct Book {  
    char title[50];  
    char authors[500];  
    double price;  
    int accNum;  
    bool checkOutStatus;  
    int claimantId;  
};
```

C++ keyword

## Structures in C++

- C++ provides **structures** to group a set of variables of possibly different data types together

```
struct Book {  
    char title[50];  
    char authors[500];  
    double price;  
    int accNum;  
    bool checkOutStatus;  
    int claimantId;  
};
```

Structure type name  
(can be used like other data  
type names such as int, char)

## Structures in C++

- C++ provides **structures** to group a set of variables of possibly different data types together

```
struct Book {  
    char title[50];  
    char authors[500];  
    double price;  
    int accNum;  
    bool checkOutStatus;  
    int claimantId;  
};
```

Members of structure Book

Members of structure Book

## Structures in C++

- C++ provides **structures** to group a set of variables of possibly different data types together

```
struct Book {  
    char title[50];  
    char authors[500];  
    double price;  
    int accNum;  
    bool checkOutStatus;  
    int claimantId;  
};
```

Members can be arrays or variables of other data types (including **other** structures)

## Structures in C++

- C++ provides **structures** to group a set of variables of possibly different data types together

```
struct Book {  
    char title[50];  
    char authors[500];  
    double price;  
    int accNum;  
    bool checkOutStatus;  
    int claimantId;  
};
```

Member name

Member type

## Structures in C++

- C++ provides **structures** to group a set of variables of possibly different data types together

```
struct Book {  
    char title[50];  
    char authors[500];  
    double price;  
    int accNum;  
    bool checkOutStatus;  
    int claimantId;  
};
```

Declaring variables of type **Book**

**Book** myChoice, yourChoice;

Note similarity with declaring  
**int** myInt, yourInt;

Declaring an array of type **Book**

**Book** libraryShelf[1000];

Note similarity with declaring  
**int** rollNumbers[1000];

## Structures in C++

- C++ provides **structures** to group a set of variables of possibly different data types together

```
struct Book {  
    char title[50];  
    char authors[500];  
    double price;  
    int accNum;  
    bool checkOutStatus;  
    int claimantId;  
};
```

```
struct Patron {  
    char name[50];  
    char address[100];  
    int uniqueId;  
    int numBooksChkdOut;  
    int claimdBookAccNum;  
};
```



# Overall Design Philosophy

- Identify **entities** (physical or conceptual) involved in the working of the system
  - E.g., Books and Patrons
  - Entities also called **objects**
- Think of system functionality in terms of **operations on and interactions between objects**
  - E.g., Patron checking out a book, patron claiming a book
- **Abstract** away (hide) details not necessary for an operation
- Implement system modularly by focusing on entities, their interfaces and their interactions

**OBJECT-ORIENTED PROGRAMMING (in one slide)**

## Entity or Object

---

- Contains information specific to the object
  - “Fixed” information – usually doesn’t change as objects interact  
Name of patron, title of book, authors of book
  - “State” information – can change as objects interact  
Check out status of book, number of books checked out by patron
- Unambiguous, well-defined boundaries
  - Clear specification of what information is part of an object  
When a patron claims a book, where is the information stored?  
Claimant’s id is in “Book” object  
Claimed book’s accession number is in “Patron” object

# Interactions between Objects

---



- Ideally, every interaction between two objects should happen through well-defined interfaces of objects
  - Allows hiding unnecessary details of object from programmer

When a patron checks out a book by accession number, do we need to access book's title, author's name or price?
- Abstraction, data encapsulation: To be covered later in course

# Summary

---



- Motivation for object-oriented programming
- Introduction to structures as objects in C++

# Designing a Complex Program

## Should we jump into writing code?

- Keep adding variables and function as and when needed

### For each book:

- Title and authors (char arrays)
- Price in Indian Rupees (double)
- Accession number (int)
- Check out status (bool)
- Claimant's id (int), if any

1000 books implies

2000 character arrays (title, authors)

1000 double variables (price)

1000 int variables (acc. numbers)

1000 bool variables (check out status)

1000 int variables (claimant ids)

### For each patron:

- Name and address (char array)
- Unique id (int)
- Number of books checked out (int)
- Claimed book's accession number (int), if any

**Not quite manageable  
Recipe for disaster!**