Fruits into Baskets

∑ SR Score	1002
⊚ Link	https://www.educative.io/courses/grokking-the-coding-interview/Bn2KLlOR0lQ
□ Last Reviewed	@April 8, 2022
# Time	5
# Score	4
i≣ DS	arrays
i≣ Algo	sliding window
Stated	medium
○ Perceived	easy
List	REPEAT
Needs Review	
∑ C_Date	1
∑ C_Solution	2
∑ C_Time	500
◆ Frequency	

▼ Problem Statement

Problem Statement

You are visiting a farm to collect fruits. The farm has a single row of fruit trees. You will be given two baskets, and your goal is to pick as many fruits as possible to be placed in the given baskets.

You will be given an array of characters where each character represents a fruit tree. The farm has following restrictions:

- 1. Each basket can have only one type of fruit. There is no limit to how many fruit a basket can hold.
- 2. You can start with any tree, but you can't skip a tree once you have started.
- 3. You will pick exactly one fruit from every tree until you cannot, i.e., you will stop when you have to pick from a third fruit type.

Write a function to return the maximum number of fruits in both baskets.

Example 1:

```
Input: Fruit=['A', 'B', 'C', 'A', 'C']
Output: 3
Explanation: We can put 2 'C' in one basket and one 'A' in the other from the subarray ['C', 'A', 'C']

Example 2:

Input: Fruit=['A', 'B', 'C', 'B', 'B', 'C']
Output: 5
Explanation: We can put 3 'B' in one basket and two 'C' in the other basket.
This can be done if we start with the second letter: ['B', 'C', 'B', 'B', 'C']
```

▼ Intuition

- key is translating each part of the fruits & farms story to it's more boring LC parallel
- ▼ You are visiting a to collect fruits
 - jk!
- $\blacktriangledown \mbox{ The farm has a single row of fruit trees.}$
 - there is an array of characters
- lacktriangledown You will be given two baskets, and your goal is to pick as many fruits as possible to be placed in the given baskets.

Fruits into Baskets 1

- you will be given 2 "character slots", and your goal is to find the maximum # of characters as possible that fit within the 2 character slots
- lacksquare 1. Each basket can have only one type of fruit. There is no limit to how many fruit a basket can hold.
 - each character slot can only have one letter of the alphabet, but there is no limit to the # of that letter of the alphabet the slot can hold
- ▼ 2. You can start with any tree, but you can't skip a tree once you have started.
 - you can start with any letter, but cannot skip a letter once you've started
- \blacktriangledown 3. You will pick exactly one fruit from every tree until you cannot, i.e., you will stop when you have to pick from a third fruit type.
 - You will pick exactly one letter from each index in the array until you cannot, i.e. you will stop when you have to pick a third unique letter from the alphabet
- ▼ Write a function to return the maximum number of fruits in both baskets.
 - Write a function to return the maximum length substring containing 2 distinct characters

▼ Time & Space Considerations

- Time: $O(2n) \rightarrow O(n)$
 - \circ for loop to iterate thru all characters \rightarrow O(n)
 - \circ while loop inside for loop processes each letter in array 1 time $_{\rightarrow}$ O(n)
 - O(n+n) = O(2n) --> O(n)
- Space: $0(3) \rightarrow 0(1)$
 - \circ dictionary fruitTracker can hold a max of 3 elements (keys) since problem specifies we only get 2 "fruit baskets" (aka distinct characters), so size of dict is constant always

▼ Review Notes

- **▼** [3/5/22]
 - didn't have a clue, checked solution
- **▼** [4/8/22]
 - got code optimally in sub 5 min
 - key growth area from [3/5/22] is that you could find parallels between the farm + fruits story and the actual LC problem it's asking you

▼ Tracking

Scores

<u>Aa</u> Attempt #	 □ Date	# Time	# Score
2	@April 8, 2022	5	5
1	@March 5, 2022	1	1
<u>Untitled</u>			

▼ Solutions

Fruits into Baskets 2

```
fruitCounts[fruit] = fruitCounts.get(fruit, 0) + 1
while len(fruitCounts) > 2:
    leftFruit = fruits[windowStart]
    fruitCounts[leftFruit] -= 1
    if fruitCounts[leftFruit] == 0:
        det fruitCounts[leftFruit]
    windowStart += 1
    maxFruits = max(maxFruits, windowEnd - windowStart + 1)

return maxFruits

def main():
    print("Maximum number of fruits: " + str(fruits_into_baskets(['A', 'B', 'C', 'A', 'C'])))
    print("Maximum number of fruits: " + str(fruits_into_baskets(['A', 'B', 'C', 'B', 'B', 'C'])))

main()
```

▼ Resources

Fruits into Baskets (medium) - Grokking the Coding Interview: Patterns for Coding Questions

3 → []

thttps://www.educative.io/courses/grokking-the-coding-interview/Bn2KLlOR0lQ

Longest Substring with maximum K Distinct Characters (medium) - Grokking the Coding Interview: Patterns for Co

thttps://www.educative.io/courses/grokking-the-coding-interview/YQQwQMWLx80

▼ GitHub



Fruits into Baskets 3