Thermodynamics paper

Thermodynamics paper

Name:

Instructions:

Please do not attempt to copy or discuss the contents of this paper with any of your classmates during the course of this paper. Any such attempt, or even the action of glancing over someone else's work will be viewed as a violation of Georgia Tech's Honor Code, and this will result in a zero-point grade. Additionally, you are not permitted to use any electronic device during the course of this paper, aside from a standard calculator. You are permitted to use the restrooms, however, prior to leaving the lecture theatre, you are required to leave your cellular device(s) with the instructor. You may collect these once you return. As discussed, you are permitted to use two sides of a single 8.5" x 11" sheet of paper for formulas, notes, or derivations that you may find useful. There is no restriction on what your notes may comprise. Please do not turn in any scratch paper, and ensure your submitted answers do indeed answer the question that is being asked. Carefully read each question as the ask may be slightly different from questions you have practiced before. The numerical value after each question, e.g., [5] denotes the number of marks assigned to that question. Finally, please write down all your answers on **this** provided sheet, along with your derivations and calculations that you want graded.

Problem 1

Air flows steadily and isothermally at $27°\ C$ along a horizontal pipe of constant crosssectional area 100 cm^2. At point A the pressure is $3\ bar$ and the mean velocity is $160\ m/s$. At point B the pressure is $2\ bar$.

a. Calculate the velocity at point B, assuming air is an ideal gas [4].

b. Find the heat-transfer per kg of air between the two points [5].

c. Assuming the flow is from A to B, calculate the increase in specific entropy due to irreversibility. Suggest a physical cause for the irreversibility, and comment on the validity of the assumption that the flow is from A to B. Use an R value of 287 $J/(kg \cdot K)$ [5].

b. Water flows through an insulated pump. On the assumption that the flow is reversible, use the steady-flow energy equation along with the equation $\Delta h = \frac{\Delta p}{\rho}$ to show that the pump power is given by

$$\dot{W}_p = \frac{\dot{m}}{\rho}\left[(p_2 - p_1) + \frac{1}{2}\rho\left(v_2^2 - v_1^2\right)\right]$$

where $\dot{m}$ is the mass flow rate, p_1 and v_1 are the pressure and velocity at the inlet, and p_2 and v_2 are the pressure and velocity at the outlet. You may neglect changes in potential energy. [5]

Problem 2

c. Why will the flow not be reversible in practice? [2]

a. Use the first law of thermodynamics, in the form $dq = du + pdv$ to show that for a reversible adiabatic process, the incremental change in specific enthalpy is $dh = vdp$. Hence show that when an incompressible fluid undergoes a reversible adiabatic process, the total change in specific enthalpy is given by the expression below $\Delta h = \frac{\Delta p}{\rho}$.
[5]