laserdata

Prepared for **Cribl**

SIEM outage buffering for Cribl Stream, on LaserData.

A down SIEM's events wait in one shared Apache Iggy log, not on Worker disks. **Every other Destination keeps receiving in milliseconds, and the SIEM gets fresh events first when it is back.** It sits behind a Webhook Destination, so nothing else has to move.

One SIEM down, the rest on time,
as the log sees it.
Now multiply by every Worker.



14:00:00.000	dest.down	splunk_lb · offsets held at 9,214,530
14:02:13.411	delivered	cribl_lake · fw-030112 · seq 48,211 · +9 ms
14:04:00.000	dest.up	splunk_lb · 1,680,000 waiting in the log
14:04:00.218	delivered	splunk_lb · dc-010044 · fresh, +8 ms
14:07:20.000	drained	splunk_lb · from offset 9,214,530 · 0 lost

From the creators of APACHE IGGY

15×
faster P99 latency
than Apache Kafka

4×
higher throughput
than Apache Kafka

60–70%
lower infrastructure cost
compute, storage and network

Apache Iggy vs Apache Kafka, LaserData testing. Results vary by workload.

What you shared	**On Cribl.Cloud, a Destination's queue is 1 GB per Worker Process,** on disk, and data flow blocks when it fills (Cribl Stream docs). Riding out ~14 hours of Splunk downtime took ~21 TB of Worker SSD in Cribl's own sizing post.
Where it fits	**The SIEM outage lane:** one Route's security events written once, keyed by host. The SIEM, Cribl Lake and a new SIEM each read from their own offsets; fresh events first on recovery. Stream keeps its Sources, Routes and Pipelines.
Next	**AI agents** act on the same lane, with session, context, memory and replay from Laser SDK.
Underneath	**One durable event log.** LaserData, powered by Apache Iggy.

Try it in 15 minutes. Let the numbers decide.

A ready-made kit for Cribl: **a Worker Node writing a Route's events once**, Cribl Lake and SIEM Destinations on their own offsets, a SIEM outage with a fresh-first drain, a new SIEM backfilling, and a Webhook Destination receiver. It prints every Destination's p99, events waiting and events lost every second.

Open the Cribl kit and write-up →

Then a 2–4 week evaluation on a shadowed Route beside your Destinations, priced per billion events. **No advantage, no migration.**

kranti@laserdata.com laserdata.com

© 2026 LaserData, Inc. Apache, Apache Iggy and the Iggy logo are trademarks of The Apache Software Foundation; their use does not imply endorsement by the ASF. The Cribl name identifies the intended reader only; no affiliation is implied. Facts are from Cribl Stream documentation (Persistent Queues and Webhook Destination, version 4.20) and the Cribl blog post "How Does Persistent Queuing Work Inside Cribl Stream?" (2023). Destination names follow Cribl Stream's; host names, offsets, counts and timestamps are illustrative.