

[17:33:00] 🔍 [BT-SCAN] Configuring scan: duration=30s, role=GHOST, filter=NONE (check tactical names for both BRIDGE and GHOST)

[17:33:00] 🔍 [BT-SCAN] Received 5 scan result(s), updating discovery context...

[17:33:00] 🔍 [DEBUG] RAW SCAN DATA:

[17:33:00] MAC: :::::AF:43

[17:33:00] localName: 'EMPTY'

[17:33:00] platformName: 'EMPTY'

[17:33:00] effectiveName: 'EMPTY'

[17:33:00] serviceUUIDs: [bf27730d-860a-4e09-889c-2d8b6a9e0fe7]

[17:33:00] manufacturerData: {65535: [71, 72, 87, 192, 58, 28, 186, 254, 104, 158, 0]}

[17:33:00] 🔍 [BT-SCAN] ✅ Mesh device: " (MAC: :::::AF:43, hops=99)

[17:33:00] 🚩 [Ghost] GHOST detected via manufacturerData fallback! (MAC: :::::AF:43)

[17:33:00] 🔍 [Ghost] Final connection check for GHOST :::::AF:43:

[17:33:00] 📋 Should connect: true (isBridge: false, pending: 2, peerHops: 99, myHops: 100)

[17:33:00] 📋 Cooldown: EXPIRED (key: MAC:48:A0:D4:35:AF:43, remaining: 0s)

[17:33:00] 📋 Transfer active: false

[17:33:00] 🔒 [CASCADE] Starting cascade to 35:AF:43 (active cascades: 1)

[17:33:00] 💾 [CASCADE-FIX] ScanResult saved IMMEDIATELY at cascade start (MAC: 35:AF:43)

[17:33:00] 🧩 Engaging Cascade for node 48:A0:D4:35:AF:43

[17:33:00] 📋 Cooldown will be set ONLY after failed attempt (not before!)

[17:33:00] 🔍 [BT-SCAN] Summary: Found 1 mesh device(s)

[17:33:00] 🔍 [ROLE-CHECK] My role: GHOST, My hops: 100, My pending: 2

[17:33:00] 🔍 [ROLE-CHECK] Peer role: GHOST, Peer hops: 99

[17:33:00] ✅ [BT-SCAN] BLE scan started successfully (no filter - can see both BRIDGE and GHOST by tactical name)

[17:33:00] 🔍 [BT-SCAN] Received 1 scan result(s), updating discovery context...

[17:33:01] 🏠 [GHOST↔GHOST] roleDecision=peer closer to internet, shouldConnect=true

[17:33:01] [BLE][ADAPTIVE][DEGRADED] reason=NO_RELAY

[17:33:01] [BLE-STRATEGY] local=HUAWEI peer=UNKNOWN → peerInitiates

[17:33:01] 🏠 [GHOST↔GHOST] Strategy: not initiating GATT (restrictive vendor or passive), waiting for peer to connect

[17:33:01] 🔍 [BT-SCAN] Received 2 scan result(s), updating discovery context...

[17:33:01] 🔍 [DEBUG] RAW SCAN DATA:

[17:33:01] MAC: ..:..:..:4D:83

[17:33:01] localName: 'EMPTY'

[17:33:01] platformName: 'EMPTY'

[17:33:01] effectiveName: 'EMPTY'

[17:33:01] serviceUUIDs: [bf27730d-860a-4e09-889c-2d8b6a9e0fe7]

[17:33:01] manufacturerData: {65535: [71, 72, 87, 192, 58, 28, 186, 254, 104, 158, 0]}

[17:33:01] 🔍 [BT-SCAN] ✅ Mesh device: " (MAC: ..:..:..:..:4D:83, hops=99)

[17:33:01] 🚫 [Ghost] GHOST detected via manufacturerData fallback! (MAC: ..:..:..:..:4D:83)

[17:33:01] 🔍 [Ghost] Final connection check for GHOST ..:..:..:..:4D:83:

[17:33:01] 📋 Should connect: true (isBridge: false, pending: 2, peerHops: 99, myHops: 100)

[17:33:01] 📋 Cooldown: EXPIRED (key: MAC:70:A3:83:33:4D:83, remaining: 0s)

[17:33:01] 📋 Transfer active: false

[17:33:01] 🔒 [CASCADE] Starting cascade to 33:4D:83 (active cascades: 1)

[17:33:01] 💾 [CASCADE-FIX] ScanResult saved IMMEDIATELY at cascade start (MAC: 33:4D:83)

[17:33:01] 🧬 Engaging Cascade for node 70:A3:83:33:4D:83

[17:33:01] 📋 Cooldown will be set ONLY after failed attempt (not before!)

[17:33:01] 🔍 [BT-SCAN] Summary: Found 1 mesh device(s)

[17:33:01] 🔍 [ROLE-CHECK] My role: GHOST, My hops: 100, My pending: 2

[17:33:01] 🔍 [ROLE-CHECK] Peer role: GHOST, Peer hops: 99

[17:33:01] 📶 [GHOST↔GHOST] roleDecision=peer closer to internet, shouldConnect=true

[17:33:01] [BLE-STRATEGY] local=HUAWEI peer=UNKNOWN → peerInitiates

[17:33:01] 📶 [GHOST↔GHOST] Strategy: not initiating GATT (restrictive vendor or passive), waiting for peer to connect

[17:33:01] 🔍 [BT-SCAN] Received 3 scan result(s), updating discovery context...

[17:33:01] 🔍 [DEBUG] RAW SCAN DATA:

[17:33:01] MAC: :::::4D:83

[17:33:01] localName: 'EMPTY'

[17:33:01] platformName: 'EMPTY'

[17:33:01] effectiveName: 'EMPTY'

[17:33:01] serviceUUIDs: [bf27730d-860a-4e09-889c-2d8b6a9e0fe7]

[17:33:01] manufacturerData: {65535: [71, 72, 87, 192, 58, 28, 186, 254, 104, 158, 0]}

[17:33:01] 🔍 [BT-SCAN] ✅ Mesh device: " (MAC: :::::4D:83, hops=99)

[17:33:01] 🚫 [Ghost] GHOST detected via manufacturerData fallback! (MAC: :::::4D:83)

[17:33:01] 🔍 [Ghost] Final connection check for GHOST :::::4D:83:

[17:33:01] 📋 Should connect: true (isBridge: false, pending: 2, peerHops: 99, myHops: 100)

[17:33:01] 📋 Cooldown: EXPIRED (key: MAC:70:A3:83:33:4D:83, remaining: 0s)

[17:33:01] 📋 Transfer active: false

[17:33:01]  [CASCADE] Starting cascade to 33:4D:83 (active cascades: 1)

[17:33:01]  [CASCADE-FIX] ScanResult saved IMMEDIATELY at cascade start (MAC: 33:4D:83)

[17:33:01]  Engaging Cascade for node 70:A3:83:33:4D:83

[17:33:01]  Cooldown will be set ONLY after failed attempt (not before!)

[17:33:01]  [BT-SCAN] Summary: Found 1 mesh device(s)

[17:33:01]  [ROLE-CHECK] My role: GHOST, My hops: 100, My pending: 2

[17:33:01]  [ROLE-CHECK] Peer role: GHOST, Peer hops: 99

[17:33:01]  [GHOST↔GHOST] roleDecision=peer closer to internet, shouldConnect=true

[17:33:01] [BLE-STRATEGY] local=HUAWEI peer=UNKNOWN → peerInitiates

[17:33:01]  [GHOST↔GHOST] Strategy: not initiating GATT (restrictive vendor or passive), waiting for peer to connect

[17:33:03]  Uplink probe cycle completed.

[17:33:08]  [BT-SCAN] Received 4 scan result(s), updating discovery context...

[17:33:08]  [DEBUG] RAW SCAN DATA:

[17:33:08] MAC: ..:..:..:..:4D:83

[17:33:08] localName: 'EMPTY'

[17:33:08] platformName: 'EMPTY'

[17:33:08] effectiveName: 'EMPTY'

[17:33:08] serviceUUIDs: [bf27730d-860a-4e09-889c-2d8b6a9e0fe7]

[17:33:08] manufacturerData: {65535: [71, 72, 87, 192, 58, 28, 186, 254, 104, 158, 0]}

[17:33:08] 🔍 [BT-SCAN] ✅ Mesh device: " (MAC: ..:..:..:4D:83, hops=99)

[17:33:08] 🚫 [Ghost] GHOST detected via manufacturerData fallback! (MAC: ..:..:..:4D:83)

[17:33:08] 🔍 [Ghost] Final connection check for GHOST ..:..:..:4D:83:

[17:33:08] 📋 Should connect: true (isBridge: false, pending: 2, peerHops: 99, myHops: 100)

[17:33:08] 📋 Cooldown: EXPIRED (key: MAC:70:A3:83:33:4D:83, remaining: 0s)

[17:33:08] 📋 Transfer active: false

[17:33:08] 🔒 [CASCADE] Starting cascade to 33:4D:83 (active cascades: 1)

[17:33:08] 💾 [CASCADE-FIX] ScanResult saved IMMEDIATELY at cascade start (MAC: 33:4D:83)

[17:33:08] 🧩 Engaging Cascade for node 70:A3:83:33:4D:83

[17:33:08] 📋 Cooldown will be set ONLY after failed attempt (not before!)

[17:33:08] 🔍 [BT-SCAN] Summary: Found 1 mesh device(s)

[17:33:08] 🔍 [ROLE-CHECK] My role: GHOST, My hops: 100, My pending: 2

[17:33:08] 🔍 [ROLE-CHECK] Peer role: GHOST, Peer hops: 99

[17:33:08] 🏠 [GHOST↔GHOST] roleDecision=peer closer to internet, shouldConnect=true

[17:33:08] [BLE-STRATEGY] local=HUAWEI peer=UNKNOWN → peerInitiates

[17:33:08] 🏠 [GHOST↔GHOST] Strategy: not initiating GATT (restrictive vendor or passive), waiting for peer to connect

17:33:17 > 🦷 [Gossip] Device prefers PERIPHERAL (Huawei/Honor) — skipping BLE relay, using Sonar

17:33:17 > 🏠 [GOSSIP] Message pulse_nu not found in DB - will relay to neighbors...

17:33:17 > 📶 [Gossip] Querying neighbors for packet: pulse_nu...

[17:33:31] 🔍 [BT-SCAN] Scan session ended

[17:33:31] 📦 [AUTO-SCAN] Found 2 pending message(s) after scan - checking for BRIDGE...

[17:33:31] 🔍 [Ghost] Checking for BRIDGE after scan (pending: 2 messages)...

[17:33:31] ⓘ [Ghost] No BRIDGE found after scan

17:33:36 > 🦷 [Gossip] Device prefers PERIPHERAL (Huawei/Honor) — skipping BLE relay, using Sonar

17:33:36 > 🦠 [Epidemic] run: pending=2, relay_attempts=2

[17:33:43] 📶 [Uplink-Seeker] Probing neighbors for internet access...

[17:33:43] 🔍 [BT-SCAN] Starting BLE scan (role: GHOST)

[17:33:43] 📶 [ADV] Setting tactical name: 'M_100_1_GHOS' (length: 12)

17:33:43 > 🦷 [BT] ⓘ [ADV] Keeping GATT server active (advertising-only stop)

17:33:43 > 🦷 [BT] 🛑 [ADV] Native advertiser stopped

17:33:43 > 🦷 [BT] ⓘ [ADV] isAdvertising=false, skipping stop call

17:33:43 > 🦷 [BT] 🛌 FSM → IDLE

17:33:43 > 🦷 [BT] 🛑 [ADV] Too soon since last operation (74ms), waiting 1925ms...

17:33:45 > 🦷 [BT] 📶 [ADV] State: starting, proceeding with advertising...

17:33:45 > 🦷 [BT] ✅ [ADV] GATT server already running - keeping it active

17:33:45 > 🦷 [BT] 🛑 [ADV] Force stopping all advertising sets (prevent TOO_MANY_ADVERTISERS)...

17:33:45 > 🦷 [BT] ⓘ [ADV] Skipping pre-start cleanup (no previous advertising detected)

17:33:46 > 🦷 [BT] 📶 [ADV] Starting with name: 'M_100_1_GHOS' (12 chars)

17:33:46 > 🦷 [BT] 🔍 [ADV] Advertising with manufacturerData: GHOST (0xFFFF: 11 bytes)

17:33:46 > 🦷 [BT] 🛠️ [ADV] Using native BLE advertiser (Huawei/Honor mode)

17:33:46 > 🦷 [BT] ✅ [ADV] Native advertiser started successfully

17:33:46 > 🦷 [BT] ✅ [ADV] ADVERTISING ACTIVE: 'M_100_1_GHOS'

17:33:46 > 🦷 [BT] ✅ [GATT-SERVER] GATT server started successfully

[17:33:46] 🔍 [BT-SCAN] Configuring scan: duration=30s, role=GHOST, filter=NONE (check tactical names for both BRIDGE and GHOST)

[17:33:46] 🔍 [BT-SCAN] Received 4 scan result(s), updating discovery context...

[17:33:46] 🔍 [DEBUG] RAW SCAN DATA:

[17:33:46] MAC: ..:..:..:..:4D:83

[17:33:46] localName: 'EMPTY'

[17:33:46] platformName: 'EMPTY'

[17:33:46] effectiveName: 'EMPTY'

[17:33:46] serviceUUIDs: [bf27730d-860a-4e09-889c-2d8b6a9e0fe7]

[17:33:46] manufacturerData: {65535: [71, 72, 87, 192, 58, 28, 186, 254, 104, 158, 0]}

[17:33:46] 🔍 [BT-SCAN] ✅ Mesh device: " (MAC: ..:..:..:4D:83, hops=99)

[17:33:46] 🚫 [Ghost] GHOST detected via manufacturerData fallback! (MAC: ..:..:..:4D:83)

[17:33:46] 🔍 [Ghost] Final connection check for GHOST ..:..:..:4D:83:

[17:33:46] 📋 Should connect: true (isBridge: false, pending: 2, peerHops: 99, myHops: 100)

[17:33:46] 📋 Cooldown: EXPIRED (key: MAC:70:A3:83:33:4D:83, remaining: 0s)

[17:33:46] 📋 Transfer active: false

[17:33:46] 🔒 [CASCADE] Starting cascade to 33:4D:83 (active cascades: 1)

[17:33:46] 💾 [CASCADE-FIX] ScanResult saved IMMEDIATELY at cascade start (MAC: 33:4D:83)

[17:33:46] 🧩 Engaging Cascade for node 70:A3:83:33:4D:83

[17:33:46] 📋 Cooldown will be set ONLY after failed attempt (not before!)

[17:33:46] 🔍 [BT-SCAN] Summary: Found 1 mesh device(s)

[17:33:46] 🔍 [ROLE-CHECK] My role: GHOST, My hops: 100, My pending: 2

[17:33:46] 🔍 [ROLE-CHECK] Peer role: GHOST, Peer hops: 99

[17:33:46] ✅ [BT-SCAN] BLE scan started successfully (no filter - can see both BRIDGE and GHOST by tactical name)

[17:33:46] 🔍 [BT-SCAN] Received 1 scan result(s), updating discovery context...

[17:33:46] 🔍 [DEBUG] RAW SCAN DATA:

[17:33:46] MAC: ..:..:..:..:4D:83

[17:33:46] localName: 'EMPTY'

[17:33:46] platformName: 'EMPTY'

[17:33:46] effectiveName: 'EMPTY'

[17:33:46] serviceUUIDs: [bf27730d-860a-4e09-889c-2d8b6a9e0fe7]

[17:33:46] manufacturerData: {65535: [71, 72, 87, 192, 58, 28, 186, 254, 104, 158, 0]}

[17:33:46] 🔍 [BT-SCAN] ✅ Mesh device: " (MAC: ..:..:..:..:4D:83, hops=99)

[17:33:46] 🚫 [Ghost] GHOST detected via manufacturerData fallback! (MAC: ..:..:~:~:~:4D:83)

[17:33:46] 🔍 [Ghost] Final connection check for GHOST ..:~:~:~:4D:83:

[17:33:46] 📋 Should connect: true (isBridge: false, pending: 2, peerHops: 99, myHops: 100)

[17:33:46] 📋 Cooldown: EXPIRED (key: MAC:70:A3:83:33:4D:83, remaining: 0s)

[17:33:46] 📋 Transfer active: true (0s)

[17:33:46] ⏸ [Ghost] Connection blocked: Transfer already in progress

[24.06.2026 14:49] МамaH: [17:33:46] 🔍 [BT-SCAN] Summary: Found 1 mesh device(s)

[17:33:46] 🔍 [BT-SCAN] Received 2 scan result(s), updating discovery context...

[17:33:46] 🔍 [DEBUG] RAW SCAN DATA:

[17:33:46] MAC: ..:~:~:~:~:4D:83

[17:33:46] localName: 'EMPTY'

[17:33:46] platformName: 'EMPTY'

[17:33:46] effectiveName: 'EMPTY'

[17:33:46] serviceUUIDs: [bf27730d-860a-4e09-889c-2d8b6a9e0fe7]

[17:33:46] manufacturerData: {65535: [71, 72, 87, 192, 58, 28, 186, 254, 104, 158, 0]}

[17:33:46] 🔍 [BT-SCAN] ✅ Mesh device: " (MAC: ..:..:..:..:4D:83, hops=99)

[17:33:46] 📄 [Ghost] GHOST detected via manufacturerData fallback! (MAC: ..:..:..:..:4D:83)

[17:33:46] 🔍 [Ghost] Final connection check for GHOST ..:..:..:..:4D:83:

[17:33:46] 📋 Should connect: true (isBridge: false, pending: 2, peerHops: 99, myHops: 100)

[17:33:46] 📋 Cooldown: EXPIRED (key: MAC:70:A3:83:33:4D:83, remaining: 0s)

[17:33:46] 📋 Transfer active: true (0s)

[17:33:46] ⏸ [Ghost] Connection blocked: Transfer already in progress

[17:33:46] 🔍 [BT-SCAN] Summary: Found 1 mesh device(s)

[17:33:46] 📄 [GHOST↔GHOST] roleDecision=peer closer to internet, shouldConnect=true

[17:33:46] [BLE-STRATEGY] local=HUAWEI peer=UNKNOWN → peerInitiates

[17:33:46] 📄 [GHOST↔GHOST] Strategy: not initiating GATT (restrictive vendor or passive), waiting for peer to connect

[17:33:46] 🔍 [BT-SCAN] Received 3 scan result(s), updating discovery context...

[17:33:46] 🔍 [DEBUG] RAW SCAN DATA:

[17:33:46] MAC: ..:..:..:..:4D:83

[17:33:46] localName: 'EMPTY'

[17:33:46] platformName: 'EMPTY'

[17:33:46] effectiveName: 'EMPTY'

[17:33:46] serviceUUIDs: [bf27730d-860a-4e09-889c-2d8b6a9e0fe7]

[17:33:46] manufacturerData: {65535: [71, 72, 87, 192, 58, 28, 186, 254, 104, 158, 0]}

[17:33:46] 🔍 [BT-SCAN] ✅ Mesh device: " (MAC: ..:..:..:..:4D:83, hops=99)

[17:33:46] 🚫 [Ghost] GHOST detected via manufacturerData fallback! (MAC: ..:..:..:..:4D:83)

[17:33:46] 🔍 [Ghost] Final connection check for GHOST ..:..:~:~:~:4D:83:

[17:33:46] 📋 Should connect: true (isBridge: false, pending: 2, peerHops: 99, myHops: 100)

[17:33:46] 📋 Cooldown: EXPIRED (key: MAC:70:A3:83:33:4D:83, remaining: 0s)

[17:33:46] 📋 Transfer active: false

[17:33:46] 🔒 [CASCADE] Starting cascade to 33:4D:83 (active cascades: 1)

[17:33:46] 💾 [CASCADE-FIX] ScanResult saved IMMEDIATELY at cascade start (MAC: 33:4D:83)

[17:33:46] 🧩 Engaging Cascade for node 70:A3:83:33:4D:83

[17:33:46] 📋 Cooldown will be set ONLY after failed attempt (not before!)

[17:33:46] 🔍 [BT-SCAN] Summary: Found 1 mesh device(s)

[17:33:47] 🔍 [ROLE-CHECK] My role: GHOST, My hops: 100, My pending: 2

[17:33:47] 🔍 [ROLE-CHECK] Peer role: GHOST, Peer hops: 99

[17:33:47] 🔍 [BT-SCAN] Received 4 scan result(s), updating discovery context...

[17:33:47] 🔍 [DEBUG] RAW SCAN DATA:

[17:33:47] MAC: ..:..:..:4D:83

[17:33:47] localName: 'EMPTY'

[17:33:47] platformName: 'EMPTY'

[17:33:47] effectiveName: 'EMPTY'

[17:33:47] serviceUUIDs: [bf27730d-860a-4e09-889c-2d8b6a9e0fe7]

[17:33:47] manufacturerData: {65535: [71, 72, 87, 192, 58, 28, 186, 254, 104, 158, 0]}

[17:33:47] 🔍 [BT-SCAN] ✅ Mesh device: " (MAC: ..:..:..:4D:83, hops=99)

[17:33:47] 🚫 [Ghost] GHOST detected via manufacturerData fallback! (MAC: ..:..:..:4D:83)

[17:33:47] 🔍 [Ghost] Final connection check for GHOST ..:..:..:4D:83:

[17:33:47] 📋 Should connect: true (isBridge: false, pending: 2, peerHops: 99, myHops: 100)

[17:33:47] 📋 Cooldown: EXPIRED (key: MAC:70:A3:83:33:4D:83, remaining: 0s)

[17:33:47] 📋 Transfer active: true (0s)

[17:33:47] 🛑 [Ghost] Connection blocked: Transfer already in progress

[17:33:47] 🔍 [BT-SCAN] Summary: Found 1 mesh device(s)

[17:33:47] 📶 [GHOST↔GHOST] roleDecision=peer closer to internet, shouldConnect=true

[17:33:47] [BLE-STRATEGY] local=HUAWEI peer=UNKNOWN → peerInitiates

[17:33:47] 📶 [GHOST↔GHOST] Strategy: not initiating GATT (restrictive vendor or passive), waiting for peer to connect

[17:33:53] 🧹 Pruned dead nodes. Active: 1

17:33:56 > 🦠 [Epidemic] Infecting superior node: D:83

17:33:57 > 📶 [GOSSIP] Message pulse_nu not found in DB - will relay to neighbors...

17:33:57 > 📶 [Gossip] Querying neighbors for packet: pulse_nu...

[17:34:03] ⌚ Uplink probe cycle completed.

17:34:16 > 🦷 [Gossip] Device prefers PERIPHERAL (Huawei/Honor) — skipping BLE relay, using Sonar

[17:34:17] 🔍 [BT-SCAN] Scan session ended

17:34:17 > 📶 [GOSSIP] Message pulse_nu not found in DB - will relay to neighbors...

17:34:17 > 📶 [Gossip] Querying neighbors for packet: pulse_nu...

[17:34:17] 📦 [AUTO-SCAN] Found 2 pending message(s) after scan - checking for BRIDGE...

[17:34:17] 🔍 [Ghost] Checking for BRIDGE after scan (pending: 2 messages)...

[17:34:17] ⓘ [Ghost] No BRIDGE found after scan

17:34:23 > [OUTBOX] Sending via sendAuto: chatId=BEACON_NEARBY length=4

17:34:23 > [P2P] [WIFI-DIAG] P2P:action |
action=android.net.wifi.p2p.PEERS_CHANGED

17:34:23 > [P2P] [WIFI-DIAG] P2P:PEERS | received

17:34:24 > [P2P] 📶 [PEERS] Found 1 device(s)

[17:34:24] 📶 [Wi-Fi Direct] GHOST detected Wi-Fi peer: TECNO SPARK 20 Pro+ (2b73f418569370f4)

[17:34:24] 📋 Initiating automatic Wi-Fi Direct connection...

[17:34:24] [WIFI-GUARD] Conditions evaluated

[17:34:24] [WIFI] Connect approved by guard

17:34:24 > [P2P] [WIFI-DIAG] requestGroupInfo | null=true nn=null
pass=null... go=null owner=null clients=0

[17:34:24] [WIFI] Connect attempt started

[17:34:24] [WIFI] Existing group state: none

[17:34:24] [WIFI] No reset required

[17:34:24] [WIFI] Aborted due to BLE activity

[17:34:24] [OUTBOX] sendAuto entered: target=BEACON_NEARBY
role=GHOST messageId=temp_1773326063459

[17:34:24] 🚀 Initiating Multi-Channel Uplink for: BEACON_NEARBY

[17:34:24] 📦 [SEND-AUTO] Starting message send:

[17:34:24] 📋 Content length: 4 chars

[17:34:24] 📋 Target: BEACON_NEARBY

[17:34:24] 📋 Receiver: Рядом

[17:34:24] 📋 Message ID: temp_1773326063459

[17:34:25]  [SEND-AUTO] Message encrypted, tempId: temp_1773326063459

[17:34:25] [ROUTER] Resolved path: DeliveryPath.meshDtn for BEACON_NEARBY

[17:34:25] [ROUTER][SKIP] Channel 1 Cloud: path=DeliveryPath.meshDtn

[17:34:25]  [HW] BLE-first mode (weak Wi-Fi Direct hardware)

[17:34:25]  [SEND-AUTO] GHOST: BLE left to cascade only (avoid duplicate)

[17:34:25]  [Channel 2] _isP2pConnected=false isRouteReady=false

[17:34:25]  [SEND-AUTO] Channel 4: Sonar (ultrasonic)

[17:34:25]  Emergency: false, Content length: 4 chars

[17:34:25]  Sonar: Escalating to Acoustic Link...

[17:34:25]  [SEND-AUTO] Channel 4: Sonar transmission initiated

[17:34:25]  [OBSERVE] sendAuto used channels: BLE, Sonar

[17:34:25]  Virus: Signal incubated in Outbox.

[17:34:25] [OUTBOX] Message added to outbox (GHOST, not delivered). id=temp_1773326063459

[17:34:25]  [AUTO-TRIGGER] Message added to outbox - triggering automatic scan...

[17:34:25]  [SEND-AUTO] Send summary:

[17:34:25]  Delivered to network: false

[17:34:25]  Delivered to participants: false

[17:34:25]  Message ID: temp_1773326063459

[17:34:25]  Target: BEACON_NEARBY

[17:34:25] 📋 Role: GHOST

[17:34:25] ⚠️ [SEND-AUTO] Message queued in outbox (no channels available)

[17:34:25] 🚀 [AUTO-TRIGGER] Found 3 pending message(s) - starting automatic scan...

[17:34:25] 📶 [Grosii] Skipped (Sonar busy)

[17:34:25] 📡 [Uplink-Seeker] Probing neighbors for internet access...

[17:34:26] 🔗 Probing Wi-Fi peer via TCP: 2b73f418569370f4

[17:34:26] 🔍 [BT-SCAN] Starting BLE scan (role: GHOST)

[17:34:26] 📡 [ADV] Setting tactical name: 'M_100_1_GHOS' (length: 12)

17:34:26 > 🦷 [BT] ⓘ [ADV] Keeping GATT server active (advertising-only stop)

17:34:26 > 🦷 [BT] 🛑 [ADV] Native advertiser stopped

17:34:26 > 🦷 [BT] ⓘ [ADV] isAdvertising=false, skipping stop call

17:34:26 > 🦷 [BT] 🛌 FSM → IDLE

17:34:26 > 🦷 [BT] ⏸️ [ADV] Too soon since last operation (10ms), waiting 1989ms...

17:34:28 > 🦷 [BT] 📡 [ADV] State: starting, proceeding with advertising...

17:34:28 > 🦷 [BT] ✅ [ADV] GATT server already running - keeping it active

17:34:28 > 🦷 [BT] 🛑 [ADV] Force stopping all advertising sets (prevent TOO_MANY_ADVERTISERS)...

17:34:28 > 🦷 [BT] ⓘ [ADV] Skipping pre-start cleanup (no previous advertising detected)

17:34:28 > 🦷 [BT] 📡 [ADV] Starting with name: 'M_100_1_GHOS' (12 chars)

17:34:28 > 🦷 [BT] 🔍 [ADV] Advertising with manufacturerData: GHOST (0xFFFF: 11 bytes)

17:34:28 > 🦷 [BT] 🛠️ [ADV] Using native BLE advertiser (Huawei/Honor mode)

17:34:29 > 🦷 [BT] ✅ [ADV] Native advertiser started successfully

17:34:29 > 🦷 [BT] ✅ [ADV] ADVERTISING ACTIVE: 'M_100_1_GHOS'

17:34:29 > 🦷 [BT] ✅ [GATT-SERVER] GATT server started successfully

[17:34:29] 🔍 [BT-SCAN] Configuring scan: duration=30s, role=GHOST, filter=NONE (check tactical names for both BRIDGE and GHOST)

[17:34:29] 🔍 [BT-SCAN] Received 4 scan result(s), updating discovery context...

[17:34:29] 🔍 [DEBUG] RAW SCAN DATA:

[17:34:29] MAC: ..:..:..:4D:83

[17:34:29] localName: 'EMPTY'

[17:34:29] platformName: 'EMPTY'

[17:34:29] effectiveName: 'EMPTY'

[17:34:29] serviceUUIDs: [bf27730d-860a-4e09-889c-2d8b6a9e0fe7]

[17:34:29] manufacturerData: {65535: [71, 72, 87, 192, 58, 28, 186, 254, 104, 158, 0]}

[17:34:29] 🔍 [BT-SCAN] ✅ Mesh device: " (MAC: ..:..:..:4D:83, hops=99)

[17:34:29] 🚫 [Ghost] GHOST detected via manufacturerData fallback! (MAC: ..:..:..:4D:83)

[17:34:29] 🔍 [Ghost] Final connection check for GHOST ..:..:..:4D:83:

[17:34:29] 📋 Should connect: true (isBridge: false, pending: 3, peerHops: 99, myHops: 100)

[17:34:29] 📋 Cooldown: EXPIRED (key: MAC:70:A3:83:33:4D:83, remaining: 0s)

[17:34:29] 📋 Transfer active: false

[17:34:29] 🔒 [CASCADE] Starting cascade to 33:4D:83 (active cascades: 1)

[17:34:29] 💾 [CASCADE-FIX] ScanResult saved IMMEDIATELY at cascade start (MAC: 33:4D:83)

[17:34:29] 🔗 Engaging Cascade for node 70:A3:83:33:4D:83

[17:34:29] 📋 Cooldown will be set ONLY after failed attempt (not before!)

[17:34:29] 🔍 [BT-SCAN] Summary: Found 1 mesh device(s)

[17:34:29] ✅ [BT-SCAN] BLE scan started successfully (no filter - can see both BRIDGE and GHOST by tactical name)

[17:34:29] 🔍 [ROLE-CHECK] My role: GHOST, My hops: 100, My pending: 3

[17:34:29] 🔍 [ROLE-CHECK] Peer role: GHOST, Peer hops: 99

[17:34:29] 🔍 [BT-SCAN] Received 1 scan result(s), updating discovery context...

[17:34:29] 🔍 [DEBUG] RAW SCAN DATA:

[17:34:29] MAC: ..:..:..:..:01:3E

[17:34:29] localName: 'EMPTY'

[17:34:29] platformName: 'EMPTY'

[17:34:29] effectiveName: 'EMPTY'

[17:34:29] serviceUUIDs: [bf27730d-860a-4e09-889c-2d8b6a9e0fe7]

[17:34:29] manufacturerData: {65535: [71, 72, 87, 192, 58, 28, 186, 254, 104, 158, 1]}

[17:34:29] 🔍 [BT-SCAN] ✅ Mesh device: " (MAC: ..:..:..:01:3E, hops=99)

[17:34:29] 🚫 [Ghost] GHOST detected via manufacturerData fallback! (MAC: ..:..:..:01:3E)

[17:34:29] 🔍 [Ghost] Final connection check for GHOST ..:..:..:01:3E:

[17:34:29] 📋 Should connect: true (isBridge: false, pending: 3, peerHops: 99, myHops: 100)

[17:34:29] 📋 Cooldown: EXPIRED (key: MAC:72:AA:DC:D6:01:3E, remaining: 0s)

[17:34:29] 📋 Transfer active: true (0s)

[17:34:29] ⏸ [Ghost] Connection blocked: Transfer already in progress

[17:34:29] 🔍 [BT-SCAN] Summary: Found 1 mesh device(s)

[17:34:29] 🏠 [GHOST↔GHOST] roleDecision=peer closer to internet, shouldConnect=true

[17:34:29] [BLE-STRATEGY] local=HUAWEI peer=UNKNOWN → peerInitiates

[17:34:29] 🏠 [GHOST↔GHOST] Strategy: not initiating GATT (restrictive vendor or passive), waiting for peer to connect

[17:34:31] 🔍 [BT-SCAN] Received 2 scan result(s), updating discovery context...

[17:34:31] 🔍 [DEBUG] RAW SCAN DATA:

[17:34:31] MAC: ..:..:..:01:3E

[17:34:31] localName: 'EMPTY'

[17:34:31] platformName: 'EMPTY'

[17:34:31] effectiveName: 'EMPTY'

[17:34:31] serviceUUIDs: [bf27730d-860a-4e09-889c-2d8b6a9e0fe7]

[17:34:31] manufacturerData: {65535: [71, 72, 87, 192, 58, 28, 186, 254, 104, 158, 1]}

[17:34:31] 🔍 [BT-SCAN] ✅ Mesh device: " (MAC: ..:..:..:01:3E, hops=99)

[17:34:31] 🚫 [Ghost] GHOST detected via manufacturerData fallback! (MAC: ..:..:..:01:3E)

[17:34:31] 🔍 [Ghost] Final connection check for GHOST ..:..:..:01:3E:

[17:34:31] 📋 Should connect: true (isBridge: false, pending: 3, peerHops: 99, myHops: 100)

[17:34:31] 📋 Cooldown: EXPIRED (key: MAC:72:AA:DC:D6:01:3E, remaining: 0s)

[17:34:31] 📋 Transfer active: false

[17:34:31] 🔒 [CASCADE] Starting cascade to D6:01:3E (active cascades: 1)

[17:34:31] 💾 [CASCADE-FIX] ScanResult saved IMMEDIATELY at cascade start (MAC: D6:01:3E)

[17:34:31] 🧩 Engaging Cascade for node 72:AA:DC:D6:01:3E

[17:34:31] 📋 Cooldown will be set ONLY after failed attempt (not before!)

[17:34:31] 🔍 [BT-SCAN] Summary: Found 1 mesh device(s)

[17:34:31] 🔍 [ROLE-CHECK] My role: GHOST, My hops: 100, My pending: 3

[17:34:31] 🔍 [ROLE-CHECK] Peer role: GHOST, Peer hops: 99

[17:34:32] 🔍 [BT-SCAN] Received 3 scan result(s), updating discovery context...

[17:34:32] 🔍 [DEBUG] RAW SCAN DATA:

[17:34:32] MAC: ..:..:..:01:3E

[17:34:32] localName: 'EMPTY'

[17:34:32] platformName: 'EMPTY'

[17:34:32] effectiveName: 'EMPTY'

[17:34:32] serviceUUIDs: [bf27730d-860a-4e09-889c-2d8b6a9e0fe7]

[17:34:32] manufacturerData: {65535: [71, 72, 87, 192, 58, 28, 186, 254, 104, 158, 1]}

[17:34:32] 🔍 [BT-SCAN] ✅ Mesh device: " (MAC: ..:..:..:01:3E, hops=99)

[17:34:32] 🚫 [Ghost] GHOST detected via manufacturerData fallback! (MAC: ..:..:..:01:3E)

[17:34:32] 🔍 [Ghost] Final connection check for GHOST ..:..:..:01:3E:

[17:34:32] 📋 Should connect: true (isBridge: false, pending: 3, peerHops: 99, myHops: 100)

[17:34:32] 📋 Cooldown: EXPIRED (key: MAC:72:AA:DC:D6:01:3E, remaining: 0s)

[17:34:32] 📋 Transfer active: true (0s)

[17:34:32] ⏸ [Ghost] Connection blocked: Transfer already in progress

[17:34:32] 🔍 [BT-SCAN] Summary: Found 1 mesh device(s)

[17:34:32] 🏠 [GHOST↔GHOST] roleDecision=peer closer to internet, shouldConnect=true

[17:34:32] [BLE-STRATEGY] local=HUAWEI peer=UNKNOWN → peerInitiates

[17:34:32] 🏠 [GHOST↔GHOST] Strategy: not initiating GATT (restrictive vendor or passive), waiting for peer to connect

[17:34:35] 🔍 [BT-SCAN] Received 4 scan result(s), updating discovery context...

[17:34:35] 🔍 [DEBUG] RAW SCAN DATA:

[17:34:35] MAC: ..:..:..:..:01:3E

[17:34:35] localName: 'EMPTY'

[17:34:35] platformName: 'EMPTY'

[17:34:35] effectiveName: 'EMPTY'

[17:34:35] serviceUUIDs: [bf27730d-860a-4e09-889c-2d8b6a9e0fe7]

[17:34:35] manufacturerData: {65535: [71, 72, 87, 192, 58, 28, 186, 254, 104, 158, 1]}

[17:34:35] 🔍 [BT-SCAN] ✅ Mesh device: " (MAC: ..:..:..:..:01:3E, hops=99)

[17:34:35] 🚫 [Ghost] GHOST detected via manufacturerData fallback! (MAC: ..:..:..:..:01:3E)

[17:34:35] 🔍 [Ghost] Final connection check for GHOST ..:..:..:..:01:3E:

[17:34:35] 📋 Should connect: true (isBridge: false, pending: 3, peerHops: 99, myHops: 100)

[17:34:35] 📋 Cooldown: EXPIRED (key: MAC:72:AA:DC:D6:01:3E, remaining: 0s)

[17:34:35] 📋 Transfer active: false

[17:34:35] 🔒 [CASCADE] Starting cascade to D6:01:3E (active cascades: 1)

[17:34:35] 💾 [CASCADE-FIX] ScanResult saved IMMEDIATELY at cascade start (MAC: D6:01:3E)

[17:34:35] 🌀 Engaging Cascade for node 72:AA:DC:D6:01:3E

[17:34:35] 📋 Cooldown will be set ONLY after failed attempt (not before!)

[17:34:35] 🔍 [BT-SCAN] Summary: Found 1 mesh device(s)

[17:34:35] 🔍 [ROLE-CHECK] My role: GHOST, My hops: 100, My pending: 3

[17:34:35] 🔍 [ROLE-CHECK] Peer role: GHOST, Peer hops: 99

[17:34:36] 🏠 [GHOST↔GHOST] roleDecision=peer closer to internet, shouldConnect=true

[17:34:36] [BLE-STRATEGY] local=HUAWEI peer=UNKNOWN → peerInitiates

[17:34:36] 🏠 [GHOST↔GHOST] Strategy: not initiating GATT (restrictive vendor or passive), waiting for peer to connect

17:34:38 > 🦷 [Gossip] Device prefers PERIPHERAL (Huawei/Honor) — skipping BLE relay, using Sonar

17:34:38 > 🦠 [Epidemic] run: pending=2, relay_attempts=2

17:34:39 > 🦷 [BT] ✅ [GATT-SERVER] Client connected: ••:••:••:••:20:E1

17:34:39 > 🦷 [BT] 📋 [GATT-SERVER] Active clients: 1

17:34:39 > 🦷 [BT] 🔄 [BRIDGE-SYNC] Delaying sync 3s to allow GHOST uplink write first...

17:34:43 > 🦷 [BT] 🏠 [BRIDGE] BLE GATT: Received COMPLETE data from GHOST ••:••:••:••:20:E1

17:34:43 > 🦷 [BT] 📋 Data preview:
{ "type": "MSG_FRAG", "mid": "temp_1773326054244", "idx": 0, "tot": 2, "data": "F8BSb2Tw7bvKKSRjl+NVPCydYLilcz..." }

17:34:43 > 🦷 [BT] 📋 Full data length: 245 bytes

17:34:43 > 🦷 [BT] [BLE-DIAG] raw data length: 245

17:34:43 > 🦷 [BT] [BLE-DIAG] first 50 bytes (base64):
eyJ0eXBlljoiTVNHX0ZSQUciLCJtaWQiOiJ0ZW1wXzE3NzMzMjYwNTQyNDQiLCJpZHg=

17:34:43 > 🦷 [BT] ✅ [JSON] Parsed complete message successfully!

17:34:43 > 🦷 [BT] 📋 Message type: MSG_FRAG

17:34:43 > 🦷 [BT] 📋 Message ID: temp_177...

17:34:43 > 🦷 [BT] [BLE-DIAG] jsonDecode: success

17:34:43 > 🦷 [BT] [BLE-DIAG] type: MSG_FRAG chatId:
THE_BEACON_GLOBAL senderId: 36 chars identityKey present: false

17:34:43 > 🦷 [BT] 📦 Forwarding to
MeshService.processIncomingPacket()...

[17:34:43] 🧬 [GHOST] processIncomingPacket: New packet received.
Analyzing...

[17:34:43] 🔄 [FIX] rawData is already message object, serialized to JSON

[17:34:43] 📋 Transport: BLE_GATT

[17:34:43] 📋 Sender: 72:2C:DB:9D:20:E1

[17:34:43] 📋 Raw data length: 294 bytes

[17:34:43] ✅ JSON parsed successfully

[17:34:43] 📋 Data keys: [type, mid, idx, tot, data, chatId, senderId, ttl,
timestamp, _relayRecipientsSnapshot]

[17:34:43] 📋 Raw chatId from data: 'THE_BEACON_GLOBAL'

[17:34:43] [IDENTITY] Legacy message (no identity)

17:34:43 > 🦷 [BT] 📦 [FRAG] Fragment received, checking if message
is complete...

17:34:43 > 🦷 [BT] ⌚ [FRAG] Message temp_1773326054244 not yet
complete - ACK deferred

[17:34:43] 📍 [GHOST] Peer Locked -> 72:2C:DB:9D:20:E1 (expires in 5min)

[17:34:43] 📋 Packet type: MSG_FRAG

[17:34:43] 📋 Sender ID: GHOST_17...

[17:34:43] 📋 Chat ID: THE_BEACON_GLOBAL

[17:34:43] 📦 [GHOST] MSG_FRAG detected for room: THE_BEACON_GLOBAL

[17:34:43] 📋 Transport: BLE_GATT

[17:34:43] 📋 Sender: GHOST_17...

[17:34:43] 📋 Message ID: frag_tem...

[17:34:43] 📦 [GHOST] ✅ Fragment received from GHOST_17... via BLE_GATT

[17:34:43] 📦 [GHOST↔GHOST] Message from peer (relay or direct) — will process and show in chat

[17:34:43] 📋 Content length: 60 bytes

[17:34:43] 📋 Chat ID: THE_BEACON_GLOBAL

[17:34:43] 📋 Sender IP: 72:2C:DB:9D:20:E1

[17:34:43] [BLE-DIAG] processIncomingPacket: isFragment=true isForMe=false isGlobal=true incomingChatId='THE_BEACON_GLOBAL'

[17:34:43] [BLE-DIAG] UI stream condition: sendToUi=false (false reasons: isFragment? true | !isForMe&&!isGlobal? false | incomingChatId.isEmpty? false)

[17:34:43] 📦 [Mesh] Fragment - will be delivered to UI after assembly.

17:34:43 > 🔍 [FRAGMENT-DEBUG] Raw fragment keys: [type, mid, idx, tot, data, chatId, senderId, ttl, timestamp, _relayRecipientsSnapshot]

17:34:43 > 🔍 [FRAGMENT-DEBUG] frag['mid']: temp_1773326054244

17:34:43 > 🔍 [FRAGMENT-DEBUG] frag['idx']: 0 (type: int)

17:34:43 > 🔍 [FRAGMENT-DEBUG] frag['tot']: 2

17:34:43 > 🔍 [FRAGMENT-DEBUG] frag['data']: 60 bytes

17:34:43 > 📦 [FRAGMENT] fragment_received: mid=temp_177... idx=0/2
sender=GHOST_17...

17:34:43 > 💾 [FRAGMENT] fragment_stored: temp_1773326054244
idx=0/2

17:34:43 > 📊 [FRAGMENT] Progress: 1/2 for temp_1773326054244

17:34:43 > 🔍 [FRAGMENT-DEBUG] Saved fragments indices: [0]

17:34:43 > 🔍 [FRAGMENT-DEBUG] Expected indices: [0, 1]

17:34:43 > [BLE-DIAG] GossipManager: fragment assembly incomplete
(1/2 for temp_1773326054244)

17:34:44 > 🦷 [BT] 📦 [BRIDGE] BLE GATT: Received COMPLETE data
from GHOST ..:::20:E1

17:34:44 > 🦷 [BT] 📋 Data preview:
{"type":"MSG_FRAG","mid":"temp_1773326054244","idx":1,"tot":2,"data":
"BSN0/ZV++8Bg9ifOIIOAhbTDBDSuAnA...

17:34:44 > 🦷 [BT] 📋 Full data length: 217 bytes

17:34:44 > 🦷 [BT] [BLE-DIAG] raw data length: 217

17:34:44 > 🦷 [BT] [BLE-DIAG] first 50 bytes (base64):
eyJ0eXBlljoiTVNHX0ZSQUciLCJtaWQiOiJ0ZW1wXzE3NzMzMjYwNTQyNDQ
iLCJpZHg=

17:34:44 > 🦷 [BT] ✅ [JSON] Parsed complete message successfully!

17:34:44 > 🦷 [BT] 📋 Message type: MSG_FRAG

17:34:44 > 🦷 [BT] 📋 Message ID: temp_177...

17:34:44 > 🦷 [BT] [BLE-DIAG] jsonDecode: success

17:34:44 > 🦷 [BT] [BLE-DIAG] type: MSG_FRAG chatId:
THE_BEACON_GLOBAL senderId: 36 chars identityKey present: false

17:34:44 > 🦷 [BT] 📦 Forwarding to
MeshService.processIncomingPacket()...

[17:34:44] 🧬 [GHOST] processIncomingPacket: New packet received.
Analyzing...

[17:34:44] 🔄 [FIX] rawData is already message object, serialized to JSON

[17:34:44] 📋 Transport: BLE_GATT

[17:34:44] 📋 Sender: 72:2C:DB:9D:20:E1

[17:34:44] 📋 Raw data length: 266 bytes

[17:34:44] ✅ JSON parsed successfully

[17:34:44] 📋 Data keys: [type, mid, idx, tot, data, chatId, senderId, ttl,
timestamp, _relayRecipientsSnapshot]

[17:34:44] 📋 Raw chatId from data: 'THE_BEACON_GLOBAL'

[17:34:44] [IDENTITY] Legacy message (no identity)

17:34:44 > 🦷 [BT] 📦 [FRAG] Fragment received, checking if message
is complete...

17:34:44 > 🦷 [BT] ⌚ [FRAG] Message temp_1773326054244 not yet
complete - ACK deferred

[17:34:44] 📋 Packet type: MSG_FRAG

[17:34:44] 📋 Sender ID: GHOST_17...

[17:34:44] 📋 Chat ID: THE_BEACON_GLOBAL

[17:34:44] 📦 [GHOST] MSG_FRAG detected for room:
THE_BEACON_GLOBAL

[17:34:44] 📋 Transport: BLE_GATT

[17:34:44] 📋 Sender: GHOST_17...

[17:34:44] 📋 Message ID: frag_tem...

[17:34:44] 📦 [GHOST] ✅ Fragment received from GHOST_17... via BLE_GATT

[17:34:44] 📦 [GHOST↔GHOST] Message from peer (relay or direct) — will process and show in chat

[17:34:44] 📋 Content length: 32 bytes

[17:34:44] 📋 Chat ID: THE_BEACON_GLOBAL

[17:34:44] 📋 Sender IP: 72:2C:DB:9D:20:E1

[17:34:44] [BLE-DIAG] processIncomingPacket: isFragment=true isForMe=false isGlobal=true incomingChatId='THE_BEACON_GLOBAL'

[17:34:44] [BLE-DIAG] UI stream condition: sendToUi=false (false reasons: isFragment? true | !isForMe&&!isGlobal? false | incomingChatId.isEmpty? false)

[17:34:44] 📦 [Mesh] Fragment - will be delivered to UI after assembly.

17:34:44 > 🔍 [FRAGMENT-DEBUG] Raw fragment keys: [type, mid, idx, tot, data, chatId, senderId, ttl, timestamp, _relayRecipientsSnapshot]

17:34:44 > 🔍 [FRAGMENT-DEBUG] frag['mid']: temp_1773326054244

17:34:44 > 🔍 [FRAGMENT-DEBUG] frag['idx']: 1 (type: int)

17:34:44 > 🔍 [FRAGMENT-DEBUG] frag['tot']: 2

17:34:44 > 🔍 [FRAGMENT-DEBUG] frag['data']: 32 bytes

17:34:44 > 📦 [FRAGMENT] fragment_received: mid=temp_177... idx=1/2 sender=GHOST_17...

17:34:44 > 🦷 [BT] 📦 [BRIDGE] BLE GATT: Received COMPLETE data from GHOST ..:::20:E1

17:34:44 > 🦷 [BT] 📋 Data preview: {"type":"OUTBOX_REQUEST"}...

17:34:44 > 🦷 [BT] 📋 Full data length: 25 bytes

17:34:44 > 🦷 [BT] [BLE-DIAG] raw data length: 25

17:34:44 > 🦷 [BT] [BLE-DIAG] first 50 bytes (base64):
eyJ0eXBlljoiT1VUQk9YX1JFUUVFU1QifQ==

17:34:44 > 🦷 [BT] ✅ [JSON] Parsed complete message successfully!

17:34:44 > 🦷 [BT] 📋 Message type: OUTBOX_REQUEST

17:34:44 > 🦷 [BT] 📋 Message ID: unknown...

17:34:44 > 🦷 [BT] [BLE-DIAG] jsonDecode: success

17:34:44 > 🦷 [BT] [BLE-DIAG] type: OUTBOX_REQUEST chatId: null
senderId: 0 chars identityKey present: false

17:34:44 > 🦷 [BT] 📦 [OUTBOX_REQUEST] Central requested outbox
pull — responding via notify

17:34:44 > 🦷 [BT] 📋 [OUTBOX_REQUEST] Sending 3 pending
message(s) via notify

17:34:45 > 💾 [FRAGMENT] fragment_stored: temp_1773326054244
idx=1/2

17:34:45 > 📊 [FRAGMENT] Progress: 2/2 for temp_1773326054244

17:34:45 > 🔍 [FRAGMENT-DEBUG] Saved fragments indices: [0, 1]

17:34:45 > 🔍 [FRAGMENT-DEBUG] Expected indices: [0, 1]

17:34:45 > 🎉 [FRAGMENT] message_assembled: temp_1773326054244
(2 fragments)

17:34:45 > 🔍 [FRAGMENT-DEBUG] Sorted indices: [0, 1]

17:34:45 > 📝 [FRAGMENT] Assembled content: 92 bytes

[17:34:46] ⌚ Uplink probe cycle completed.

17:34:46 >  [FRAGMENT] message_committed: temp_1773326054244 to chat THE_BEACON_GLOBAL

17:34:46 >  [BT]  [OUTBOX_REQUEST] Removed temp_1773325866751 from outbox after send

17:34:47 >  [BT]  [OUTBOX_REQUEST] Removed temp_1773325881129 from outbox after send

17:34:47 >  [GOSSIP] Message temp_177 already exists in DB - skipping relay (Gossip deduplication)

17:34:47 >  [FRAGMENT] relay_forwarded: assembled message temp_1773326054244

17:34:47 > [BLE-DIAG] GossipManager: message_assembled and delivered to UI stream

17:34:48 >  [BT]  [OUTBOX_REQUEST] Removed temp_1773326063459 from outbox after send

17:34:48 >  [BT]  [OUTBOX_REQUEST] Outbox pull completed

17:34:48 >  [BT] [BEACON-SYNC] Outbox done — starting THE BEACON chat sync (CRDT) with peer

[17:34:48] [BEACON-SYNC] Starting chat sync with peer (HEADS for 3 chat(s), Beacon: [BEACON_NEARBY, THE_BEACON_GLOBAL])

[17:34:48] [CRDT] Heads exchanged

[17:34:48] [BEACON-SYNC] HEAD_EXCHANGE sent — waiting for peer response (REQUEST_RANGE / LOG_ENTRIES)

[17:35:00]  [BT-SCAN] Scan session ended

[17:35:00]  [AUTO-SCAN] No pending messages in outbox

17:35:03 >  [BT]  [GATT-SERVER] Client disconnected: ..:..:..:20:E1

17:35:03 >  [BT]  [GATT-SERVER] Active clients: 0

[17:35:13] 🧹 Pruned dead nodes. Active: 2

[17:35:23] 🧹 Pruned dead nodes. Active: 0

[17:35:43] 🛑 [RELAY] No clients for 222s — stopping relay so others can try

[17:35:43] 🛑 [RELAY] Stopping relay mode...

17:35:43 > 🦷 [BT] [GATT][STATE] gattReady -> idle (server stopped)

17:35:43 > 🦷 [BT] 🛑 [GATT-SERVER] GATT server stopped

[17:35:43] [RELAY] Background TCP stopped (was started as relay GO)

17:35:43 > 📊 [GOSSIP] summary: accepted=2 droppedRate=0
droppedTtl=0 relayGatt=0 relayBle=0 relayNet=0 outbox=0